





Vincotech

flowPACK 0 B	600 V / 20 A
<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; background-color: #cccccc; margin: 0;">Features</p> <ul style="list-style-type: none"> IGBT3 (600 V) technology Open emitter topology New ultra-compact housing Single-screw heat sink mounting </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; background-color: #cccccc; margin: 0;">Target applications</p> <ul style="list-style-type: none"> Dedicated design for motor drive </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #cccccc; margin: 0;">Types</p> <ul style="list-style-type: none"> 10-0B066PA020SB-M995F09 </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; background-color: #cccccc; margin: 0;">flow0 B 17mm housing</p>  </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #cccccc; margin: 0;">Schematic</p>  </div>

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		600	V
Collector current	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	21	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	60	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	41	W
Gate-emitter voltage	V_{GES}		±20	V
Short circuit ratings	t_{SC} V_{CC}	$T_j \leq 150\text{ °C}$ $V_{GE} = 15V$	6 360	µs V
Maximum Junction Temperature	T_{jmax}		175	°C



Vincotech

Parameter	Symbol	Condition	Value	Unit
Inverter Diode				
Peak Repetitive Reverse Voltage	V_{RRM}		600	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	22	A
Repetitive peak forward current	I_{FRM}		40	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	34	W
Maximum Junction Temperature	T_{jmax}		175	°C
Module Properties				
Thermal Properties				
Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C
Isolation Properties				
Isolation voltage	V_{isol}	DC Voltage $t_p = 2s$	4000	V
Creepage distance			min. 12,7	mm
Clearance			min. 12,7	mm
Comparative Tracking Index	CTI		> 200	



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{GS} [V] V_r [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{GE} = V_{CE}$			0,00029	25	5	5,8	6,5	V
Collector-emitter saturation voltage	V_{CEsat}		15		20	25 150	1,1	1,52 1,84	1,9	V
Collector-emitter cut-off current	I_{CES}		0	600		25			1,1	μA
Gate-emitter leakage current	I_{GES}		20	0		25			300	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}							1100		pF
Output capacitance	C_{oes}	$f = 1$ MHz	0	25		25		71		
Reverse transfer capacitance	C_{res}							32		
Gate charge	Q_g		15	480	20	25		120		nC

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	Thermal grease thickness ≤ 50 μm $\lambda = 1$ W/mK						2,30		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

IGBT Switching

Turn-on delay time	$t_{d(on)}$					25 150		71 70		ns
Rise time	t_r	$R_{goff} = 16$ Ω $R_{gon} = 16$ Ω				25 150		11 16		
Turn-off delay time	$t_{d(off)}$		±15	300	20	25 150		122 143		
Fall time	t_f					25 150		91 111		
Turn-on energy (per pulse)	E_{on}	$Q_{rFWD} = 0,8$ μC $Q_{rFWD} = 1,7$ μC				25 150		0,259 0,380		mWs
Turn-off energy (per pulse)	E_{off}					25 150		0,448 0,613		



Vincotech

Parameter	Symbol	Conditions					Value			Unit	
		V_{GE} [V]	V_{GS} [V]	V_{CE} [V]	V_{GS} [V]	V_r [V]	I_C [A]	I_D [A]	I_F [A]		T_j [°C]

Inverter Diode

Static

Forward voltage	V_F				20	25 125		1,70 1,58	1,95	V
Reverse leakage current	I_r			600		25 150			27	μ A

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	Thermal grease thickness $\leq 50 \mu\text{m}$ $\lambda = 1 \text{ W/mK}$						2,80		K/W
-------------------------------------	---------------	--	--	--	--	--	--	------	--	-----

FWD Switching

Peak recovery current	I_{RRM}					25 150		22 26		A
Reverse recovery time	t_{rr}					25 150		125 204		ns
Recovered charge	Q_r	$di/dt = 2072 \text{ A}/\mu\text{s}$ $di/dt = 1922 \text{ A}/\mu\text{s}$	± 15	300	20	25 150		0,809 1,713		μC
Reverse recovered energy	E_{rec}					25 150		0,171 0,373		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 150		2050 741		A/ μs


Thermistor

Rated resistance	R					25		21,5		k Ω
Deviation of R100	$\Delta_{R/R}$	R100=1486 Ω				100	-4,5		+4,5	%
Power dissipation	P					25		210		mW
Power dissipation constant						25		3,5		mW/K
B-value	$B_{(25/50)}$					25		3884		K
B-value	$B_{(25/100)}$					25		3964		K
Vincotech NTC Reference									F	




Inverter Switch Characteristics

Typical output characteristics IGBT




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted line)
 $150 \text{ } ^\circ C$ (red dashed line)

Typical output characteristics IGBT




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

Typical transfer characteristics IGBT



$t_p = 100 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted line)
 $150 \text{ } ^\circ C$ (red dashed line)

Transient Thermal Impedance as function of Pulse duration IGBT



$D = t_p / T$
 $R_{th(j-s)} = 2,30 \text{ K/W}$
 IGBT thermal model values


R (K/W)	τ (s)
8,31E-02	4,36E+00
2,54E-01	7,20E-01
9,17E-01	1,88E-01
6,06E-01	5,84E-02
4,40E-01	1,40E-02



Vincotech


Inverter Switch Characteristics

Gate voltage vs Gate charge IGBT




At
 $I_C = 20$ A

Short circuit duration as a function of V_{GE} IGBT



At
 $V_{CE} = 600$ V
 $T_j \leq 175$ °C

Typical short circuit current as a function of V_{GE} IGBT




At
 $V_{CE} \leq 600$ V
 $T_j \leq 175$ °C




Vincotech

Inverter Diode Characteristics

Typical forward characteristics FWD



Transient thermal impedance as a function of pulse width FWD



FWD thermal model values


R (K/W)	τ (s)
4,62E-02	8,95E+00
1,39E-01	1,10E+00
6,93E-01	1,96E-01
5,75E-01	6,44E-02
6,19E-01	9,95E-03
2,95E-01	1,01E-03

Thermistor

Thermistor typical temperature characteristic

Typical NTC characteristic
as a function of temperature

$R_T = f(T)$






Inverter Switching Characteristics

figure 1. IGBT


Typical switching energy losses as a function of collector current



With an inductive load at
 $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $R_{g\text{on}} = 16$ Ω
 $R_{g\text{off}} = 16$ Ω
 T_j : 25 °C (blue dotted), 150 °C (red dashed)

figure 2. IGBT


Typical switching energy losses as a function of gate resistor



With an inductive load at
 $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $I_C = 20$ A
 T_j : 25 °C (blue dotted), 150 °C (red dashed)

figure 3. FWD


Typical reverse recovered energy loss as a function of collector current



With an inductive load at
 $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $R_{g\text{on}} = 16$ Ω
 T_j : 25 °C (blue dotted), 150 °C (red dashed)

figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor




With an inductive load at
 $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $I_C = 20$ A
 T_j : 25 °C (blue dotted), 150 °C (red dashed)



Inverter Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	300	V
$V_{GE} =$	±15	V
$R_{g\text{on}} =$	16	Ω
$R_{g\text{off}} =$	16	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	300	V
$V_{GE} =$	±15	V
$I_c =$	20	A

figure 7. FWD


Typical reverse recovery time as a function of collector current



At	$V_{CE} =$	300	V	$T_j:$	25	°C
	$V_{GE} =$	±15	V		150	°C	-----
	$R_{g\text{on}} =$	16	Ω				

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor



At	$V_{CE} =$	300	V	$T_j:$	25	°C
	$V_{GE} =$	±15	V		150	°C	-----
	$I_c =$	20	A				




Inverter Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




At $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $R_{gpn} = 16$ Ω
 $T_j: 25$ °C (blue dotted line)
 150 °C (red dashed line)

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gpn})$$




At $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $I_c = 20$ A
 $T_j: 25$ °C (blue dotted line)
 150 °C (red dashed line)

figure 11. FWD

Typical peak reverse recovery current current as a function of collector current

$$I_{RM} = f(I_c)$$




At $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $R_{gpn} = 16$ Ω
 $T_j: 25$ °C (blue dotted line)
 150 °C (red dashed line)

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gpn})$$



At $V_{CE} = 300$ V
 $V_{GE} = \pm 15$ V
 $I_c = 20$ A
 $T_j: 25$ °C (blue dotted line)
 150 °C (red dashed line)




Vincotech

Inverter Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_F/dt, di_{rr}/dt = f(I_C)$



At $V_{CE} = 300$ V $T_J = 25$ °C
 $V_{CE} = \pm 15$ V $T_J = 150$ °C - - - - -
 $R_{gon} = 16$ Ω

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_F/dt, di_{rr}/dt = f(R_g)$



At $V_{CE} = 300$ V $T_J = 25$ °C
 $V_{CE} = \pm 15$ V $T_J = 150$ °C - - - - -
 $I_C = 20$ A

figure 15. IGBT

Reverse bias safe operating area




At $T_J = 175$ °C
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω



Inverter Switching Definitions


General conditions	
T_j	= 150 °C
R_{gon}	= 16 Ω
R_{goff}	= 16 Ω

figure 1. IGBT
Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	300	V
$I_C(100\%) =$	20	A
$t_{doff} =$	0,143	μs
$t_{Eoff} =$	0,476	μs

figure 2. IGBT
Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	300	V
$I_C(100\%) =$	20	A
$t_{don} =$	0,070	μs
$t_{Eon} =$	0,196	μs

figure 3. IGBT
Turn-off Switching Waveforms & definition of t_f



$V_C(100\%) =$	300	V
$I_C(100\%) =$	20	A
$t_f =$	0,110	μs

figure 4. IGBT
Turn-on Switching Waveforms & definition of t_r




$V_C(100\%) =$	300	V
$I_C(100\%) =$	20	A
$t_r =$	0,016	μs




Inverter Switching Definitions

figure 5. IGBT
Turn-off Switching Waveforms & definition of t_{Eoff}




$P_{off}(100\%) = 5,98$ kW
 $E_{off}(100\%) = 0,61$ mJ
 $t_{Eoff} = 0,48$ μs

figure 6. IGBT
Turn-on Switching Waveforms & definition of t_{Eon}



$P_{on}(100\%) = 5,98$ kW
 $E_{on}(100\%) = 0,38$ mJ
 $t_{Eon} = 0,20$ μs

figure 7. FWD
Turn-off Switching Waveforms & definition of t_{rr}




$V_d(100\%) = 300$ V
 $I_d(100\%) = 20$ A
 $I_{RRM}(100\%) = -26$ A
 $t_{rr} = 0,204$ μs



Vincotech


Inverter Switching Definitions

figure 8. FWD
Turn-on Switching Waveforms & definition of t_{Qrr} (t_{Qrr} = integrating time for Q_{rr})



I_d (100%) =	20	A
Q_{rr} (100%) =	1,71	μC
t_{Qrr} =	0,44	μs

figure 9. FWD
Turn-on Switching Waveforms & definition of t_{Erec} (t_{Erec} = integrating time for E_{rec})





P_{rec} (100%) =	5,98	kW
E_{rec} (100%) =	0,37	mJ
t_{Erec} =	0,44	μs



Vincotech

Ordering Code & Marking																																								
Version			Ordering Code																																					
without thermal paste with Solder pins 17mm housing			10-0B066PA020SB-M995F09																																					
<table border="1"> <tr> <td rowspan="2"> NN-NNNNNNNNNN NNNN-TTTTTTVV Vinco LLLLL WWYY SSSS UL </td> <td rowspan="2"> </td> <th colspan="2">Text</th> <th>Name</th> <th>Type&Ver</th> <th>Date code</th> <th>Vinco&Lot</th> <th>Serial&UL</th> </tr> <tr> <td colspan="2"></td> <td>NN-NNNNNNNNNNNNNN</td> <td>TTTTTTTVV</td> <td>WWYY</td> <td>Vinco LLLLL</td> <td>SSSS UL</td> </tr> <tr> <th colspan="2">Datamatrix</th> <th>Type&Ver</th> <th>Lot number</th> <th>Serial</th> <th>Date code</th> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="2"></td> <td>TTTTTTTVV</td> <td>LLLLL</td> <td>SSSS</td> <td>WWYY</td> <td></td> <td></td> <td></td> </tr> </table>							NN-NNNNNNNNNN NNNN-TTTTTTVV Vinco LLLLL WWYY SSSS UL		Text		Name	Type&Ver	Date code	Vinco&Lot	Serial&UL			NN-NNNNNNNNNNNNNN	TTTTTTTVV	WWYY	Vinco LLLLL	SSSS UL	Datamatrix		Type&Ver	Lot number	Serial	Date code						TTTTTTTVV	LLLLL	SSSS	WWYY			
NN-NNNNNNNNNN NNNN-TTTTTTVV Vinco LLLLL WWYY SSSS UL		Text		Name	Type&Ver	Date code			Vinco&Lot	Serial&UL																														
				NN-NNNNNNNNNNNNNN	TTTTTTTVV	WWYY	Vinco LLLLL	SSSS UL																																
Datamatrix		Type&Ver	Lot number	Serial	Date code																																			
		TTTTTTTVV	LLLLL	SSSS	WWYY																																			

Pin table [mm]			
Pin	X	Y	Function
1	27,8	0	G6
2	24,9	0	E6
3	19,1	0	G5
4	16,2	0	E5
5	11,6	0	NTC2
6	7,6	0	NTC1
7	2,9	0	E4
8	0	0	G4
9	0	13,7	U
10	2,9	13,7	G1
11	8,8	13,7	DC+
12	14,6	13,7	V
13	17,5	13,7	G2
14	24,9	13,7	G3
15	27,8	13,7	W





Tolerance of pinpositions: ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance
PCB cutouts and holes see in handling instruction document



Vincotech

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T1-T6	IGBT	600 V	20 A	Inverter Switch	
D1-D6	FWD	600 V	20 A	Inverter Diode	
NTC	NTC			Thermistor	



Vincotech

Packaging instruction					
Standard packaging quantity (SPQ)	160	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> 0 B packages see vincotech.com website.

Package data
Package data for <i>flow</i> 0 B packages see vincotech.com website.

Document No.:	Date:	Modification:	Pages
10-0B066PA020SB-M995F09-D3-14	23 Jun. 2017		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.