



Vincotech

# V23990-P629-L59-PM

datasheet

flowBOOST 0 dual

1200 V / 40 A

## Features

- High efficiency dual boost
- Ultra fast switching frequency
- Low Inductance Layout
- 1200V IGBT and 1200V Si diode


## Target applications

- solar inverter


## Types

- V23990-P629-L59-PM

## flow 0 17 mm housing



## Schematic





Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>Boost Switch</b>				
Collector-emitter voltage	$V_{CES}$		1200	V
Collector current (DC current)	$I_C$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	42	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{jmax}$	120	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	115	W
Gate-emitter voltage	$V_{GES}$		$\pm 20$	V
Short circuit ratings	$t_{SC}$	$V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	$\mu\text{s}$
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

## Boost Diode

Peak repetitive reverse voltage	$V_{RRM}$		1200	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	43	A
Surge (non-repetitive) forward current	$I_{FSM}$	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	270	A
Surge current capability	$I^2t$		365	$\text{A}^2\text{s}$
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	98	W
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

## Boost Sw. Protection Diode

Peak repetitive reverse voltage	$V_{RRM}$		1200	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	10	A
Repetitive peak forward current	$I_{FRM}$	$t_p$ limited by $T_{jmax}$	6	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	25	W
Maximum junction temperature	$T_{jmax}$		150	$^{\circ}\text{C}$

**Vincotech**

## Maximum Ratings

 $T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>ByPass Diode</b>				
Peak repetitive reverse voltage	$V_{RRM}$		1600	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	38	A
Surge (non-repetitive) forward current	$I_{FSM}$	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	200	A
Surge current capability	$I^2t$		200	A <sup>2</sup> s
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	47	W
Maximum junction temperature	$T_{jmax}$		150	°C

## Module Properties

### Thermal Properties

Storage temperature	$T_{stg}$		-40...+125	°C
Operation temperature under switching condition	$T_{jop}$		-40...+( $T_{jmax} - 25$ )	°C

### Isolation Properties

Isolation voltage	$V_{isol}$	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	$V_{isol}$	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			>12,7	mm
Comparative Tracking Index	CTI		≥ 200	

\*100 % tested in production



## Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		

### Boost Switch

#### Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0015	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CEsat}$		15		40	25 125	1,78	2,11 2,48	2,42 <sup>(1)</sup>	V
Collector-emitter cut-off current	$I_{CES}$		0	1200		25			5	µA
Gate-emitter leakage current	$I_{GES}$		20	0		25			120	nA
Internal gate resistance	$r_g$							None		Ω
Input capacitance	$C_{ies}$	$f = 1 \text{ Mhz}$	0	25	25			2330		pF
Output capacitance	$C_{oes}$							150		pF
Reverse transfer capacitance	$C_{res}$							130		pF
Gate charge	$Q_g$	$V_{CC} = 960 \text{ V}$	15		40	25		185		nC

#### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,82		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

#### Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \Omega$ $R_{goff} = 4 \Omega$	0/15	700	24	25 125		22,4 20,8		ns
Rise time	$t_r$					25 125		8,4 10,6		ns
Turn-off delay time	$t_{d(off)}$					25 125		224,6 293		ns
Fall time	$t_f$					25 125		34,48 67,86		ns
Turn-on energy (per pulse)	$E_{on}$	$Q_{tFWD}=2,24 \mu\text{C}$ $Q_{tFWD}=5,02 \mu\text{C}$				25 125		1,09 1,82		mWs
Turn-off energy (per pulse)	$E_{off}$					25 125		1 1,61		mWs



## Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]		Min	Typ	Max	

### Boost Diode

#### Static

Forward voltage	$V_F$				50	25 125 150		2,29 2,37	2,54 <sup>(1)</sup> 2,5 <sup>(1)</sup>	V
Reverse leakage current	$I_R$	$V_i = 1200$ V				25 150		4400	60 8800	µA

#### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,97		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

#### Dynamic

Peak recovery current	$I_{RRM}$	$di/dt=3264$ A/µs $di/dt=3300$ A/µs	0/15	700	24	25 125		62,76 78,31		A
Reverse recovery time	$t_{rr}$					25 125		82,95 207,96		ns
Recovered charge	$Q_r$					25 125		2,24 5,02		µC
Reverse recovered energy	$E_{rec}$					25 125		0,982 2,42		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125		5304 3201		A/µs



## Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]		Min	Typ	Max	

### Boost Sw. Protection Diode

#### Static

Forward voltage	$V_F$				3	25 125		1,23	1,67 1,58	1,97 <sup>(1)</sup>	V
Reverse leakage current	$I_R$	$V_r = 1200$ V				25				27	μA

#### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)							2,8		K/W
--	---------------	---------------------------------------	--	--	--	--	--	--	-----	--	-----

### ByPass Diode

#### Static

Forward voltage	$V_F$				8	25 125			0,96 0,865	1,21 <sup>(1)</sup> 1,1 <sup>(1)</sup>	V
Reverse leakage current	$I_R$	$V_r = 1600$ V				25				50	μA

#### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)							1,49		K/W
--	---------------	---------------------------------------	--	--	--	--	--	--	------	--	-----

### Thermistor

#### Static

Rated resistance	$R$					25			22		kΩ
Deviation of $R_{100}$	$\Delta R/R$	$R_{100} = 1484$ Ω				100	-5			5	%
Power dissipation	$P$								5		mW
Power dissipation constant	$d$					25			1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1$ %							3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1$ %							4000		K
Vincotech Thermistor Reference										I	

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.



Vincotech


**V23990-P629-L59-PM**  
datasheet

## Boost Switch Characteristics

**figure 1.** IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_j: 25 \text{ } ^\circ C$  (blue line)  
 $125 \text{ } ^\circ C$  (red line)

**figure 2.** IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_j = 125 \text{ } ^\circ C$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

**figure 3.** IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_j: 25 \text{ } ^\circ C$  (blue line)  
 $125 \text{ } ^\circ C$  (red line)

**figure 4.** IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0,825 K/W$   
IGBT thermal model values  

$R (K/W)$	$\tau (s)$
8,14E-02	1,87E+00
2,77E-01	2,47E-01
3,52E-01	7,24E-02
8,40E-02	1,01E-02
3,10E-02	1,06E-03



Vincotech


**V23990-P629-L59-PM**  
datasheet

## Boost Switch Characteristics

**figure 5.** IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$

$V_{GE} = 15 \text{ V}$

$T_j = T_{jmax}$





## Boost Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	$t_p / T$	
$R_{th(j-s)} =$	0,971	K/W
FWD thermal model values		
$R$ (K/W)	$\tau$ (s)	
6,69E-02	3,87E+00	
1,47E-01	4,68E-01	
4,96E-01	9,12E-02	
1,74E-01	2,26E-02	
8,75E-02	5,01E-03	



Vincotech

## Boost Sw. Protection Diode Characteristics

figure 8.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 9.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	$t_p / T$	
$R_{th(j-s)} =$	2,796	K/W
FWD thermal model values		
$R$ (K/W)	$\tau$ (s)	
7,82E-02	2,45E+00	
1,95E-01	2,65E-01	
9,84E-01	4,77E-02	
6,58E-01	1,23E-02	
5,09E-01	2,70E-03	
3,71E-01	5,98E-04	



## ByPass Diode Characteristics

figure 10.

Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 11.

Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	$t_p / T$	
$R_{th(j-s)} =$	1,487	K/W
Rectifier thermal model values		
$R$ (K/W)	$\tau$ (s)	
1,10E-01	7,06E+00	
1,38E-01	3,93E-01	
6,16E-01	6,84E-02	
3,90E-01	1,63E-02	
1,63E-01	2,51E-03	
7,11E-02	5,88E-04	



Vincotech

**V23990-P629-L59-PM**  
datasheet

## Thermistor Characteristics

figure 12.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

V23990-P629-L59-PM  
datasheet


## Boost Switching Characteristics

figure 13.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 4$   $\Omega$   
 $R_{goff} = 4$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 14.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $I_C = 24$  A


$T_j$ : — 25 °C  
— 125 °C

figure 15.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 4$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 16.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $I_C = 24$  A

$T_j$ : — 25 °C  
— 125 °C



Vincotech


V23990-P629-L59-PM  
datasheet

## Boost Switching Characteristics

figure 17.

IGBT

Typical switching times as a function of collector current  
 $t = f(I_C)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 4$   $\Omega$   
 $R_{goff} = 4$   $\Omega$

figure 18.

IGBT

Typical switching times as a function of gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $I_C = 24$  A

figure 19.

FWD

Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 4$   $\Omega$

$T_j$ : — 25 °C  
— 125 °C

figure 20.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor  
 $t_{rr} = f(R_{goff})$



With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $I_C = 24$  A

$T_j$ : — 25 °C  
— 125 °C




## Boost Switching Characteristics

figure 21.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 700 \text{ V} \\ V_{GE} &= 0/15 \text{ V} \\ R_{gon} &= 4 \text{ } \Omega \end{aligned}$$


$T_j$ : — 25 °C  
— 125 °C

figure 22.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 700 \text{ V} \\ V_{GE} &= 0/15 \text{ V} \\ I_C &= 24 \text{ A} \end{aligned}$$


$T_j$ : — 25 °C  
— 125 °C

figure 23.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 700 \text{ V} \\ V_{GE} &= 0/15 \text{ V} \\ R_{gon} &= 4 \text{ } \Omega \end{aligned}$$


$T_j$ : — 25 °C  
— 125 °C

figure 24.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 700 \text{ V} \\ V_{GE} &= 0/15 \text{ V} \\ I_C &= 24 \text{ A} \end{aligned}$$

$T_j$ : — 25 °C  
— 125 °C




Vincotech

V23990-P629-L59-PM  
datasheet

## Boost Switching Characteristics

figure 25. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $R_{goff} = 4$   $\Omega$

$T_j$ : — 25 °C  
— 125 °C

figure 26. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor  
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 700$  V  
 $V_{GE} = 0/15$  V  
 $I_C = 24$  A

$T_j$ : — 25 °C  
— 125 °C

figure 27. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At  $T_j = 125$  °C  
 $R_{goff} = 4$   $\Omega$   
 $R_{goff} = 4$   $\Omega$





Vincotech

## Boost Switching Definitions

figure 28. IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 29. IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 30. IGBT

Turn-off Switching Waveforms & definition of  $t_f$





figure 31. IGBT

Turn-on Switching Waveforms & definition of  $t_r$





## Boost Switching Definitions

figure 32.

FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$





figure 33.

FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )





Vincotech

# V23990-P629-L59-PM

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	V23990-P629-L59-PM
With thermal paste (5,2 W/mK, PTM6000HV)	V23990-P629-L59-/7/-PM
With thermal paste (3,4 W/mK, PSX-P7)	V23990-P629-L59-/3/-PM


Marking							
	Text	VIN	Date code	Type&Ver	UL	Lot	Serial
		VIN	WWYY	TTTTTTTV	UL	LLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
		TTTTTTTV	LLLL	SSSS	WWYY		

Outline																																																																																															
<p>Pin table [mm]</p> <table><tr><th>Pin</th><th>X</th><th>Y</th><th>Function</th></tr><tr><td>1</td><td>0</td><td>22,5</td><td>G1</td></tr><tr><td>2</td><td>2,9</td><td>22,5</td><td>S1</td></tr><tr><td>3</td><td>8,3</td><td>22,5</td><td>DC1-</td></tr><tr><td>4</td><td>10,8</td><td>22,5</td><td>DC1-</td></tr><tr><td>5</td><td>19,6</td><td>22,5</td><td>Out1</td></tr><tr><td>6</td><td>22,1</td><td>22,5</td><td>Out1</td></tr><tr><td>7</td><td>29,1</td><td>22,5</td><td>Sol1A</td></tr><tr><td>8</td><td>32</td><td>22,5</td><td>Sol1B</td></tr><tr><td>9</td><td>33,5</td><td>17,8</td><td>Boost1A</td></tr><tr><td>10</td><td>33,5</td><td>15,3</td><td>Boost1B</td></tr><tr><td>11</td><td>33,5</td><td>7,2</td><td>Boost2A</td></tr><tr><td>12</td><td>33,5</td><td>4,7</td><td>Boost2B</td></tr><tr><td>13</td><td>32</td><td>0</td><td>Sol2A</td></tr><tr><td>14</td><td>29,1</td><td>0</td><td>Sol2B</td></tr><tr><td>15</td><td>22,1</td><td>0</td><td>Out1</td></tr><tr><td>16</td><td>19,6</td><td>0</td><td>Out1</td></tr><tr><td>17</td><td>10,8</td><td>0</td><td>DC2-</td></tr><tr><td>18</td><td>8,3</td><td>0</td><td>DC2-</td></tr><tr><td>19</td><td>2,9</td><td>0</td><td>S2</td></tr><tr><td>20</td><td>0</td><td>0</td><td>G2</td></tr><tr><td>21</td><td>0</td><td>8</td><td>NTC1</td></tr><tr><td>22</td><td>0</td><td>14,5</td><td>NTC2</td></tr></table>				Pin	X	Y	Function	1	0	22,5	G1	2	2,9	22,5	S1	3	8,3	22,5	DC1-	4	10,8	22,5	DC1-	5	19,6	22,5	Out1	6	22,1	22,5	Out1	7	29,1	22,5	Sol1A	8	32	22,5	Sol1B	9	33,5	17,8	Boost1A	10	33,5	15,3	Boost1B	11	33,5	7,2	Boost2A	12	33,5	4,7	Boost2B	13	32	0	Sol2A	14	29,1	0	Sol2B	15	22,1	0	Out1	16	19,6	0	Out1	17	10,8	0	DC2-	18	8,3	0	DC2-	19	2,9	0	S2	20	0	0	G2	21	0	8	NTC1	22	0	14,5	NTC2
Pin	X	Y	Function																																																																																												
1	0	22,5	G1																																																																																												
2	2,9	22,5	S1																																																																																												
3	8,3	22,5	DC1-																																																																																												
4	10,8	22,5	DC1-																																																																																												
5	19,6	22,5	Out1																																																																																												
6	22,1	22,5	Out1																																																																																												
7	29,1	22,5	Sol1A																																																																																												
8	32	22,5	Sol1B																																																																																												
9	33,5	17,8	Boost1A																																																																																												
10	33,5	15,3	Boost1B																																																																																												
11	33,5	7,2	Boost2A																																																																																												
12	33,5	4,7	Boost2B																																																																																												
13	32	0	Sol2A																																																																																												
14	29,1	0	Sol2B																																																																																												
15	22,1	0	Out1																																																																																												
16	19,6	0	Out1																																																																																												
17	10,8	0	DC2-																																																																																												
18	8,3	0	DC2-																																																																																												
19	2,9	0	S2																																																																																												
20	0	0	G2																																																																																												
21	0	8	NTC1																																																																																												
22	0	14,5	NTC2																																																																																												
<p>Tolerance of pinpositions: +0,5mm at the end of pins Dimension of coordinate axis is only offset without tolerance</p>																																																																																															



Vincotech


### Pinout



### Identification

ID	Component	Voltage	Current	Function	Comment
T1, T2	IGBT	1200 V	40 A	Boost Switch	
D1, D4	FWD	1200 V	50 A	Boost Diode	
D9, D10	FWD	1200 V	3 A	Boost Sw. Protection Diode	
D7, D8	Rectifier	1600 V	25 A	ByPass Diode	
NTC	Thermistor			Thermistor	



Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow 0</i> packages see vincotech.com website.				
Package data				
Package data for <i>flow 0</i> packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
V23990-P629-L59-PM-D3-14	11 Sep. 2021	New Datasheet format, module is unchanged Introduce Rth values with PSX-P7 TIM Separate datasheet for pressfit pin version	

#### DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

#### LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.