



Vincotech

10-PY12M3A040SH09-M749F38Y

datasheet

flow3xMNPC 1

1200 V / 40 A

Features

- Mixed voltage neutral point clamped inverter
- 3 phase mixed voltage component topology
- Reactive power capability
- Low inductance layout
- Integrated NTC


Target applications

- Energy Storage Systems


Types

- 10-PY12M3A040SH09-M749F38Y

flow 1 12 mm housing



Schematic





Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Buck Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	43	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	120	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	111	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Buck Diode

Peak repetitive reverse voltage	V_{RRM}		650	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	33	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	48	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Boost Switch

Collector-emitter voltage	V_{CES}		650	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	35	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	120	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	49	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Boost Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	24	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	91	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 25\text{ °C}$	130	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	56	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			7,89	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0015	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		40	25 125	1,78	1,96 2,29	2,42 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			5	µA
Gate-emitter leakage current	I_{GES}		20	0		25			120	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		2330		pF
Output capacitance	C_{oes}							150		pF
Reverse transfer capacitance	C_{res}							130		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	15		40	25		185		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,86		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	± 15	350	40	25 125 150		69,44 70,08 71,04		ns
Rise time	t_r					25 125 150		18,56 22,08 23,04		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		140,48 182,08 192,64		ns
Fall time	t_f					25 125 150		43,83 69,88 77,06		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=0,609 \mu\text{C}$ $Q_{tFWD}=1,7 \mu\text{C}$ $Q_{tFWD}=2,13 \mu\text{C}$				25 125 150		0,684 1,15 1,32		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		1,1 1,72 1,92		mWs



Vincotech

10-PY12M3A040SH09-M749F38Y

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Diode

Static

Forward voltage	V_F				30	25 125 150		1,98 1,58 1,49	3 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 650$ V				25			5	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,98		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=2676$ A/µs $di/dt=2355$ A/µs $di/dt=2064$ A/µs	± 15	350	40	25 125 150		34,76 41,37 46,28		A
Reverse recovery time	t_{rr}					25 125 150		29,12 98,71 114,44		ns
Recovered charge	Q_r					25 125 150		0,609 1,7 2,13		µC
Reverse recovered energy	E_{rec}					25 125 150		0,078 0,283 0,366		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		3624 1823 1739		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0004	25	3,2	4	4,8	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		40	25 125 150		1,34 1,42 1,46	1,75 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	650		25			50	µA
Gate-emitter leakage current	I_{GES}		20	0		25			100	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		2500		pF
Reverse transfer capacitance	C_{res}							9		pF

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						1,95		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	± 15	350	30	25 125 150		46,4 47,68 47,68		ns
Rise time	t_r					25 125 150		6,4 7,36 7,68		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		75,2 93,44 99,52		ns
Fall time	t_f					25 125 150		11,11 45,82 59,12		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		0,258 0,302 0,31		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,308 0,48 0,543		mWs



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Boost Diode

Static

Forward voltage	V_F				20	25 125 150		1,5 1,88 2,03	1,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25		35	200	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,71		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=4341$ A/μs $di/dt=3859$ A/μs $di/dt=3507$ A/μs	± 15	350	30	25 125 150		20,18 18,58 18,27		A
Reverse recovery time	t_{rr}					25 125 150		9,68 10,7 10,81		ns
Recovered charge	Q_r					25 125 150		0,117 0,113 0,114		μC
Reverse recovered energy	E_{rec}					25 125 150		$8,094 \times 10^{-3}$ $8,471 \times 10^{-3}$ $8,739 \times 10^{-3}$		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		5981 5094 4970		A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P							5		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-PY12M3A040SH09-M749F38Y


datasheet

Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$
 $125 \text{ } ^\circ C$

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 125 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$
 $125 \text{ } ^\circ C$

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,856 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
1,40E-01	8,31E-01
4,53E-01	1,26E-01
1,58E-01	3,84E-02
7,23E-02	8,41E-03
3,25E-02	8,46E-04



Vincotech


10-PY12M3A040SH09-M749F38Y
datasheet

Buck Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



D = single pulse

$T_s = 80$ °C

$V_{GE} = 15$ V

$T_j = T_{jmax}$



Vincotech


10-PY12M3A040SH09-M749F38Y datasheet

Buck Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$

T_j : 25 °C, 125 °C, 150 °C

figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 1,978 \text{ K/W}$

FWD thermal model values

R (K/W)	τ (s)
1,10E-01	2,27E+00
3,94E-01	2,26E-01
1,08E+00	6,33E-02
2,47E-01	6,38E-03
1,46E-01	1,03E-03



Vincotech

10-PY12M3A040SH09-M749F38Y

datasheet


Boost Switch Characteristics

figure 8.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$



$t_p = 250 \mu s$
 $V_{GE} = 15 V$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 9.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 10.

IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$



$t_p = 250 \mu s$
 $V_{CE} = 10 V$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 11.

IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,954 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
1,10E-01	1,26E+00
4,76E-01	1,75E-01
1,06E+00	5,29E-02
2,03E-01	6,26E-03
1,10E-01	5,43E-04



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet


Boost Switch Characteristics

figure 12.

IGBT

Safe operating area

$I_C = f(V_{CE})$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet


Boost Diode Characteristics

figure 13.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 14.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,707 \text{ K/W}$
 FWD thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
1,11E-01	1,83E+00
3,80E-01	1,78E-01
9,44E-01	4,49E-02
2,12E-01	5,63E-03
6,02E-02	9,17E-04



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet


Thermistor Characteristics

figure 15.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-PY12M3A040SH09-M749F38Y datasheet


Buck Switching Characteristics

figure 16.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$
 $R_{goff} = 8 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 18.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 17.

IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 40 \text{ A}$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 19.

FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 40 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech


10-PY12M3A040SH09-M749F38Y
datasheet

Buck Switching Characteristics

figure 20.

IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω

figure 21.

IGBT

Typical switching times as a function of gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 40$ A

figure 22.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $T_j: 25$ °C (blue)
 125 °C (black)
 150 °C (red)

figure 23.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 40$ A
 $T_j: 25$ °C (blue)
 125 °C (black)
 150 °C (red)



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet


Buck Switching Characteristics

figure 24.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 26.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 25.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 40$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 27.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 40$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Buck Switching Characteristics

figure 28. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 29. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 40$ A

T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 30. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω



Vincotech


10-PY12M3A040SH09-M749F38Y datasheet

Boost Switching Characteristics

figure 31. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω

T_j : 25 °C
125 °C
150 °C

figure 32. IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 30$ A

T_j : 25 °C
125 °C
150 °C

figure 33. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C
125 °C
150 °C

figure 34. FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 30$ A

T_j : 25 °C
125 °C
150 °C



Vincotech


10-PY12M3A040SH09-M749F38Y
datasheet

Boost Switching Characteristics

figure 35.

IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$
 $R_{goff} = 8 \text{ } \Omega$

figure 36.

IGBT

Typical switching times as a function of gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 30 \text{ A}$

figure 37.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$




With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 8 \text{ } \Omega$
 $T_j: 25 \text{ } ^\circ\text{C}$
 $125 \text{ } ^\circ\text{C}$
 $150 \text{ } ^\circ\text{C}$

figure 38.

FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 30 \text{ A}$
 $T_j: 25 \text{ } ^\circ\text{C}$
 $125 \text{ } ^\circ\text{C}$
 $150 \text{ } ^\circ\text{C}$



Vincotech

10-PY12M3A040SH09-M749F38Y

datasheet


Boost Switching Characteristics

figure 39.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 40.

FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 30$ A


T_j : 25 °C
125 °C
150 °C

figure 41.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 42.

FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 30$ A

T_j : 25 °C
125 °C
150 °C




Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Boost Switching Characteristics

figure 43. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 8$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 44. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 30$ A

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 45. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{goff} = 8$ Ω
 $R_{goff} = 8$ Ω



Vincotech

Switching Definitions

figure 46. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 47. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 48. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 49. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 50.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 51.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

10-PY12M3A040SH09-M749F38Y

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-PY12M3A040SH09-M749F38Y
With thermal paste (4,4 W/mK, PTM6000)	10-PY12M3A040SH09-M749F38Y-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-PY12M3A040SH09-M749F38Y-/3/


Marking						
Text	Name		Date code	UL & VIN	Lot	Serial
	NN-NNNNNNNNNNNNNN- TTTTTVV		WWYY	UL VIN	LLLLL	SSSS
Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTVV	LLLLL	SSSS	WWYY		

Outline				
Pin table [mm]				
Pin	X	Y	Function	
1	52,2	0	+DC	
2	46,2	0	GND	
3	47	3	G3	
4	40,9	0	GND	
5	44	3	S3	
6	34,9	0	-DC	
7	34,9	3	-DC	
8	28,9	0	GND	
9	25,9	2	S7	
10	22,9	0	GND	
11	22,9	3	G7	
12	16,9	0	+DC	
13	16,9	3	+DC	
14	10,9	0	GND	
15	10,9	3	G11	
16	6	0	GND	
17	7,9	3	S11	
18	0	0	-DC	
19	4,75	8,9	S12	
20	1,75	7,9	G12	
21	13,25	13,7	S10	
22	13,25	10,7	G10	
23	21,25	10,7	G6	
24	21,25	13,7	S6	
25	30,4	9,7	S8	
26	33,4	9,7	G8	
27	40,15	11,2	S4	
28	40,15	8,2	G4	
29	50,45	10,7	S2	
30	50,45	13,7	G2	
31	0	16,35	NTC	
32	0	19,35	NTC	
33	5,45	28,2	OUT3	
34	8,25	28,2	OUT3	
35	11,25	28,2	G9	
36	14,25	28,2	S9	
37	23	28,2	S5	
38	26	28,2	G5	
39	29	28,2	OUT2	
40	31,8	28,2	OUT2	
41	40,4	28,2	OUT1	
42	43,2	28,2	OUT1	
43	46,2	28,2	G1	
44	49,2	28,2	S1	



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T21, T22, T31, T32	IGBT	1200 V	40 A	Buck Switch	
D11, D12, D21, D22, D31, D32	FWD	650 V	30 A	Buck Diode	
T13, T14, T23, T24, T33, T34	IGBT	650 V	40 A	Boost Switch	
D13, D14, D23, D24, D33, D34	FWD	1200 V	20 A	Boost Diode	
Rt	Thermistor			Thermistor	



Vincotech

10-PY12M3A040SH09-M749F38Y
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 1</i> packages see vincotech.com website.

Package data
Package data for <i>flow 1</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-PY12M3A040SH09-M749F38Y-D1-14	29 Jul. 2021		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.