



Vincotech

10-PG12ORA080CD-LJ59I18T

datasheet

fastPACK 1 SiC

1200 V / 80 A

Topology features

- Temperature sensor
- Single-phase non-controlled rectifier

Component features

- No diode recovery losses
- Very fast switching

Housing features

- Base isolation: Al_2O_3
- Convex shaped substrate for superior thermal contact
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection


Target applications

- Charging Stations


Types

- 10-PG12ORA080CD-LJ59I18T

flow 1 12 mm housing



Schematic





Vincotech

10-PG120RA080CD-LJ59I18T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Rectifier Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	119	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	356	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 110\text{ °C}$	516	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	246	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			>12,7	mm
Clearance			8,38	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Rectifier Diode

Static

Forward voltage	V_F				80	25 125 150		1,37 1,56 1,63	2 ⁽¹⁾		V
Reverse leakage current	I_R	$V_r = 1200$ V				25		20	2000		μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,39			K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	--	-----

Thermistor

Static

Rated resistance	R					25		22			kΩ
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 1484$ Ω				100	-5		5		%
Power dissipation	P					25		130			mW
Power dissipation constant	d					25		1,5			mW/K
B-value	$B_{(25/50)}$	Tol. ±1 %						3962			K
B-value	$B_{(25/100)}$	Tol. ±1 %						4000			K
Vincotech Thermistor Reference									I		

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

Rectifier Diode Characteristics

figure 1. FWD





figure 2. FWD





Vincotech


10-PG120RA080CD-LJ59I18T
datasheet

Thermistor Characteristics

figure 3. Thermistor

Typical NTC characteristic as function of temperature


$$R_T = f(T)$$





datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-PG120RA080CD-LJ59I18T
With thermal paste (5,2 W/mK, PTM6000HV)	10-PG120RA080CD-LJ59I18T-/7/

Marking							
	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNN- TTTTTIVV		WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTIVV	LLLLL	SSSS	WWYY			

Outline

Pin table [mm]			
Pin	X	Y	Function
1	42,8	0	DC-Rect
2	40,1	0	DC-Rect
3	37,4	0	DC-Rect
4	34,7	0	DC-Rect
5	29,6	0	Therm1
6	22,6	0	Therm2
7	17,5	0	DC-Rect
8	14,8	0	DC-Rect
9	12,1	0	DC-Rect
10	9,4	0	DC-Rect
11	0	0	DC+Rect
12	0	2,7	DC+Rect
13	0	5,4	DC+Rect
14	0	8,1	DC+Rect
15	0	28,2	ACin1
16	2,7	28,2	ACin1
17	5,4	28,2	ACin1
18	8,1	28,2	ACin1
19	10,8	28,2	ACin1
20	13,5	28,2	ACin1
21	16,2	28,2	ACin1
22	36	28,2	ACin2
23	38,7	28,2	ACin2
24	41,4	28,2	ACin2
25	44,1	28,2	ACin2
26	46,8	28,2	ACin2
27	49,5	28,2	ACin2
28	52,2	28,2	ACin2
29	52,2	8,1	DC+Rect
30	52,2	5,4	DC+Rect
31	52,2	2,7	DC+Rect
32	52,2	0	DC+Rect

The technical drawing consists of two views: a side view (top) and a top view (bottom).
Side View: Shows the profile of the module. It has a central section with 10 pins (pins 1-10) and two end sections with 12 pins each (pins 11-22 on the left, pins 29-40 on the right). The total width is 132 ± 0,1 mm. The height of the central section is 16,4 ± 0,5 mm. A note indicates the center of the press-fit pinhead for connection parameter see the handling instruction.
Top View: Shows the layout of the pins on the module's surface. The pins are numbered 1 to 32. The module has a central circular feature. Dimensions include a width of 136,1 mm and a height of 26,1 mm. Coordinate axes X and Y are shown.


Tolerance of pinpositions ±0,4mm at the end of pins
 Dimension of coordinate axis is only offset without tolerance



Vincotech

10-PG120RA080CD-LJ59I18T
datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
D31, D32, D33, D34	FWD	1200 V	80 A	Rectifier Diode	
Rt	Thermistor			Thermistor	



Vincotech

10-PG12ORA080CD-LJ59I18T
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> 1 packages see vincotech.com website.

Package data
Package data for <i>flow</i> 1 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-PG12ORA080CD-LJ59I18T-D2-14	27 Mar. 2026	Change Rectifier Diode according to PCN-2025-001	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.