



Vincotech

10-FZ124PA040F2-P629F38

datasheet

fastPACK 0

1200 V / 40 A

Topology features

- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- 5 μ s short circuit withstand time
- High speed switching
- Minimized tail current

Housing features

- Base isolation: Al₂O₃
- Clip-in, reliable mechanical connection, qualified for wave soldering
- Convex shaped substrate for superior thermal contact
- Thermo-mechanical push-and-pull force relief
- Solder pin


Target applications

- Charging Stations
- Power Supply


Types

- 10-FZ124PA040F2-P629F38

flow 0 12 mm housing



Schematic





Vincotech

10-FZ124PA040F2-P629F38
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	45	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	120	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	118	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 600\text{ V}$ $T_j = 150\text{ °C}$	5	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	24	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	100	A
Surge current capability	I^2t		50	A^2s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	61	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Module Properties

Thermal Properties

Storage temperature	T_{stg}		$-40\dots+125$	$^{\circ}\text{C}$
Operation temperature under switching condition	T_{jop}		$-40\dots+(T_{jmax} - 25)$	$^{\circ}\text{C}$

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			$>12,7$	mm
Clearance			9,55	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

10-FZ124PA040F2-P629F38
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,002	25	5	6	7	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		40	25 125 150		2,18 2,39 2,44	2,6 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		20	0		25			25	µA
Gate-emitter leakage current	I_{GES}		20	0		25			250	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		3200		pF
Output capacitance	C_{oes}							220		pF
Reverse transfer capacitance	C_{res}							80		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	0/15		40	25		158		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,8		K/W
--	---------------	---	--	--	--	--	--	-----	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 16 \Omega$ $R_{goff} = 16 \Omega$	± 15	600	40	25 125 150		95,52 93,17 92,33		ns
Rise time	t_r					25 125 150		14,35 15,21 15,86		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		91,37 108,21 112,93		ns
Fall time	t_f					25 125 150		54,43 75,79 88,24		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		1,54 2,14 2,36		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		1,2 2 2,24		mWs



Vincotech

10-FZ124PA040F2-P629F38

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				25	25 125 150		2,43 2,55 2,44	2,74 ⁽¹⁾ 2,79 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150		1600	60 3300	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,56		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=3246$ A/µs $di/dt=2581$ A/µs $di/dt=2610$ A/µs	± 15	600	40	25 125 150		46,04 48,68 50,78		A
Reverse recovery time	t_{rr}					25 125 150		65,83 167,48 187,28		ns
Recovered charge	Q_r					25 125 150		1,04 2,11 2,56		µC
Reverse recovered energy	E_{rec}					25 125 150		0,225 0,626 0,781		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		3786,78 2453,85 2084,77		A/µs



Vincotech

10-FZ124PA040F2-P629F38
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-FZ124PA040F2-P629F38


datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 59 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,804 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
6,58E-02	1,87E+00
1,35E-01	3,17E-01
4,44E-01	7,98E-02
1,10E-01	1,68E-02
4,98E-02	1,72E-03



Vincotech

10-FZ124PA040F2-P629F38


datasheet

Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D =$ single pulse
 $T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 40$ A
 $T_j = 25$ °C



Vincotech

10-FZ124PA040F2-P629F38 datasheet

Inverter Diode Characteristics

figure 7.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	1,556	K/W
FWD thermal model values		
R (K/W)	τ (s)	
4,65E-02	4,86E+00	
1,06E-01	8,11E-01	
4,71E-01	1,09E-01	
4,83E-01	3,07E-02	
2,34E-01	7,03E-03	
1,81E-01	1,25E-03	
3,38E-02	3,28E-04	



Vincotech

10-FZ124PA040F2-P629F38
datasheet


Thermistor Characteristics

figure 9.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech


10-FZ124PA040F2-P629F38 datasheet

Inverter Switching Characteristics

figure 10. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$




With an inductive load at

$V_{CE} =$	600	V	$T_f:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{gon} =$	16	Ω		150 °C
$R_{goff} =$	16	Ω		

figure 12. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$




With an inductive load at

$V_{CE} =$	600	V	$T_f:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{gon} =$	16	Ω		150 °C

figure 11. IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$




With an inductive load at

$V_{CE} =$	600	V	$T_f:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_C =$	40	A		150 °C

figure 13. FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} =$	600	V	$T_f:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_C =$	40	A		150 °C



Vincotech


10-FZ124PA040F2-P629F38 datasheet

Inverter Switching Characteristics

figure 14.

IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 15.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 40$ A

figure 16.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω

T_j : 25 °C
125 °C
150 °C

figure 17.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 40$ A

T_j : 25 °C
125 °C
150 °C



Vincotech

10-FZ124PA040F2-P629F38
datasheet


Inverter Switching Characteristics

figure 18.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 20.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 19.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 40$ A


T_j : 25 °C
125 °C
150 °C

figure 21.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 40$ A

T_j : 25 °C
125 °C
150 °C




Vincotech

10-FZ124PA040F2-P629F38
datasheet

Inverter Switching Characteristics

figure 22. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 16 \text{ } \Omega$

$T_j = 25 \text{ } ^\circ\text{C}$
 $125 \text{ } ^\circ\text{C}$
 $150 \text{ } ^\circ\text{C}$

figure 24. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 16 \text{ } \Omega$
 $R_{goff} = 16 \text{ } \Omega$

figure 23. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 40 \text{ A}$

$T_j = 25 \text{ } ^\circ\text{C}$
 $125 \text{ } ^\circ\text{C}$
 $150 \text{ } ^\circ\text{C}$



Vincotech

10-FZ124PA040F2-P629F38 datasheet

Inverter Switching Definitions

figure 25. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 26. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 27. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 28. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Inverter Switching Definitions

figure 29.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 30.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)






Vincotech



10-FZ124PA040F2-P629F38

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-FZ124PA040F2-P629F38
With thermal paste (5,2 W/mK, PTM6000HV)	10-FZ124PA040F2-P629F38-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-FZ124PA040F2-P629F38-/3/

Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTV	WWYY	UL VIN	LLLLL	SSSS
Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTV	LLLLL	SSSS	WWYY		

Outline				
Pin table [mm]				
Pin	X	Y	Function	
1	0	22,5	G1	
2	2,9	22,5	S1	
3	8,3	22,5	DC-	
4	10,8	22,5	DC-	
5	19,6	22,5	DC+	
6	22,1	22,5	DC+	
7	29,1	22,5	S2	
8	32	22,5	G2	
9	33,5	17,8	OUT1	
10	33,5	15,3	OUT1	
11	33,5	7,2	OUT2	
12	33,5	4,7	OUT2	
13	32	0	G4	
14	29,1	0	S4	
15	22,1	0	DC+	
16	19,6	0	DC+	
17	10,8	0	DC-	
18	8,3	0	DC-	
19	2,9	0	S3	
20	0	0	G3	
21	0	8	Th1	
22	0	14,5	Th2	



Tolerance of pinpositions: ±0.5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance




Vincotech

10-FZ124PA040F2-P629F38

datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T1, T2, T3, T4	IGBT	1200 V	40 A	Inverter Switch	
D2, D1, D4, D3	FWD	1200 V	25 A	Inverter Diode	
NTC	Thermistor			Thermistor	



Vincotech

10-FZ124PA040F2-P629F38
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-FZ124PA040F2-P629F38-D1-14	12 Jul. 2022		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.