



Vincotech

10-EZ12B2A040MS-LQ17L73T

datasheet

flowBOOST E1 SiC

1200 V / 40 mΩ

Topology features

- Dual Booster
- Integrated DC capacitor
- Kelvin Emitter for improved switching performance
- Open Emitter configuration
- Temperature sensor

Component features

- High Blocking Voltage with low drain source on state resistance
- High speed SiC-MOSFET technology
- Resistant to Latch-up

Housing features

- Base isolation: Al₂O₃
- Convex shaped substrate for superior thermal contact
- Compact housing
- CTI600 housing material
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection

Target applications

- Charging Stations
- Energy Storage Systems
- Power Supply
- Solar Inverters
- UPS
- Welding & Cutting


Types

- 10-EZ12B2A040MS-LQ17L73T

flow E1 12 mm housing



Schematic





Vincotech

10-EZ12B2A040MS-LQ17L73T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

Boost Switch

| | | | | |
|------------------------------|------------|---------------------------------------|---------|----|
| Drain-source voltage | V_{DS} | | 1200 | V |
| Drain current (DC current) | I_D | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 43 | A |
| Peak drain current | I_{DM} | t_p limited by T_{jmax} | 120 | A |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 73 | W |
| Gate-source voltage | V_{GS} | static | 0 / 18 | V |
| | | dynamic | -5 / 22 | V |
| Maximum Junction Temperature | T_{jmax} | | 175 | °C |

Boost Diode

| | | | | |
|--|------------|---|------|----|
| Peak repetitive reverse voltage | V_{RRM} | | 1200 | V |
| Forward current (DC current) | I_F | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 27 | A |
| Surge (non-repetitive) forward current | I_{FSM} | Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 25\text{ °C}$ | 142 | A |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 73 | W |
| Maximum junction temperature | T_{jmax} | | 175 | °C |

Boost Sw. Protection Diode

| | | | | |
|--|------------|--|------|-----|
| Peak repetitive reverse voltage | V_{RRM} | | 1600 | V |
| Forward current (DC current) | I_F | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 45 | A |
| Surge (non-repetitive) forward current | I_{FSM} | Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$ | 270 | A |
| Surge current capability | I^2t | | 370 | A²s |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 53 | W |
| Maximum junction temperature | T_{jmax} | | 150 | °C |

Capacitor (DC)

| | | | | |
|-----------------------|-----------|--|-------------|----|
| Maximum DC voltage | V_{MAX} | | 1500 | V |
| Operation Temperature | T_{op} | | -55 ... 125 | °C |



Vincotech

10-EZ12B2A040MS-LQ17L73T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

Module Properties

Thermal Properties

| | | | | |
|---|------------------|--|----------------------------------|----|
| Storage temperature | T_{stg} | | -40...+125 | °C |
| Operation temperature under switching condition | T_{jop} | | -40...+(T_{jmax} - 25) | °C |

Isolation Properties

| | | | | |
|----------------------------|-------------------|-------------------------------------|-------|----|
| Isolation voltage | V_{isol} | DC Test Voltage* $t_p = 2\text{ s}$ | 6000 | V |
| Creepage distance | | | >12,7 | mm |
| Clearance | | | 9,02 | mm |
| Comparative Tracking Index | CTI | | ≥ 600 | |

*100 % tested in production



Vincotech

10-EZ12B2A040MS-LQ17L73T

datasheet

Characteristic Values

| Parameter | Symbol | Conditions | | | | | Values | | | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
| | | | V_{GE} [V] V_{GS} [V] | V_{CE} [V] V_{DS} [V] V_F [V] | I_C [A] I_D [A] I_F [A] | T_j [°C] | Min | Typ | Max | |

Boost Switch

Static

| | | | | | | | | | | |
|----------------------------------|--------------|---|------|------|-------|------------------|-----|----------------------|---------------------|----|
| Drain-source on-state resistance | $r_{DS(on)}$ | | 18 | | 30 | 25 125 150 | | 37,9 36,8 39,2 | 55,2 ⁽¹⁾ | mΩ |
| Gate-source threshold voltage | $V_{GS(th)}$ | | | | 0,003 | 25 | 3,6 | 4,6 | 5,6 | V |
| Gate to Source Leakage Current | I_{GSS} | | 22 | 0 | | 25 | | | 200 | nA |
| Zero Gate Voltage Drain Current | I_{DSS} | | 0 | 1200 | | 25 | | | 100 | μA |
| Internal gate resistance | r_g | | | | | | | 3 | | Ω |
| Gate charge | Q_g | | 0/18 | | 30 | 25 | | 185 | | nC |
| Short-circuit input capacitance | C_{iss} | 0 | 10 | 0 | 25 | | | 4000 | | pF |
| Short-circuit output capacitance | C_{oss} | | | | | | | 1300 | | |
| Reverse transfer capacitance | C_{rss} | | | | | | | 110 | | |

Thermal

| | | | | | | | | | | |
|--|---------------|---|--|--|--|--|--|-----|--|-----|
| Thermal resistance junction to sink ⁽²⁾ | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX) | | | | | | 1,3 | | K/W |
|--|---------------|---|--|--|--|--|--|-----|--|-----|

Dynamic

| | | | | | | | | | | |
|-----------------------------|--------------|---|------|-----|----|------------------|--|---------------------------|--|-----|
| Turn-on delay time | $t_{d(on)}$ | $R_{gon} = 16 \Omega$ $R_{goff} = 16 \Omega$ | 0/18 | 600 | 32 | 25 125 150 | | 42,39 32,24 30,72 | | ns |
| Rise time | t_r | | | | | 25 125 150 | | 28,08 19,47 18,56 | | ns |
| Turn-off delay time | $t_{d(off)}$ | | | | | 25 125 150 | | 96,82 122,35 129,28 | | ns |
| Fall time | t_f | | | | | 25 125 150 | | 7,78 8,1 8,02 | | ns |
| Turn-on energy (per pulse) | E_{on} | | | | | 25 125 150 | | 0,833 0,59 0,565 | | mWs |
| Turn-off energy (per pulse) | E_{off} | | | | | 25 125 150 | | 0,242 0,237 0,242 | | mWs |



Vincotech

10-EZ12B2A040MS-LQ17L73T

datasheet

Characteristic Values

| Parameter | Symbol | Conditions | | | | | Values | | | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
| | | | V_{GE} [V] V_{GS} [V] | V_{CE} [V] V_{DS} [V] V_F [V] | I_C [A] I_D [A] I_F [A] | T_j [°C] | Min | Typ | Max | |

Boost Diode

Static

| | | | | | | | | | | |
|-------------------------|-------|----------------|--|--|----|------------------|--|----------------------|--------------------|----|
| Forward voltage | V_F | | | | 20 | 25 125 150 | | 1,51 2,03 2,13 | 1,8 ⁽¹⁾ | V |
| Reverse leakage current | I_R | $V_i = 1200$ V | | | | 25 | | 60 | 500 | µA |

Thermal

| | | | | | | | | | | |
|--|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|
| Thermal resistance junction to sink ⁽²⁾ | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK (PSX) | | | | | | 1,3 | | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|

Dynamic

| | | | | | | | | | | |
|---------------------------------------|----------------------|---|------|-----|----|------------------|--|--|--|------|
| Peak recovery current | I_{RM} | $di/dt=1384$ A/µs $di/dt=1731$ A/µs $di/dt=2704$ A/µs | 0/18 | 600 | 32 | 25 125 150 | | 7,36 10,31 10,79 | | A |
| Reverse recovery time | t_{rr} | | | | | 25 125 150 | | 13,31 13,31 13,18 | | ns |
| Recovered charge | Q_r | | | | | 25 125 150 | | 0,058 0,079 0,083 | | µC |
| Reverse recovered energy | E_{rec} | | | | | 25 125 150 | | $2,511 \times 10^{-3}$ $4,147 \times 10^{-3}$ $4,525 \times 10^{-3}$ | | mWs |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ | | | | | 25 125 150 | | 1991,57 3178,45 3190,63 | | A/µs |



Vincotech

Characteristic Values

| Parameter | Symbol | Conditions | | | | | | Values | | | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--|--------|-----|-----|------|
| | | | V_{GE} [V] V_{GS} [V] | V_{CE} [V] V_{DS} [V] V_F [V] | I_C [A] I_D [A] I_F [A] | T_j [°C] | | Min | Typ | Max | |

Boost Sw. Protection Diode

Static

| | | | | | | | | | | | |
|-------------------------|-------|----------------|--|--|----|-----------|--|-------------|--------------------|--|----|
| Forward voltage | V_F | | | | 28 | 25 125 | | 1,1 1,04 | 1,5 ⁽¹⁾ | | V |
| Reverse leakage current | I_R | $V_r = 1600$ V | | | | 25 150 | | | 100 1000 | | μA |

Thermal

| | | | | | | | | | | | |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|--|-----|
| Thermal resistance junction to sink ⁽²⁾ | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK (PSX) | | | | | | 1,31 | | | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|--|-----|

Capacitor (DC)

Static

| | | | | | | | | | | | |
|--------------------|-----|--------------------------|--|--|--|----|-----|------|----|--|----|
| Capacitance | C | DC bias voltage = 0 V | | | | 25 | | 6,8 | | | nF |
| Tolerance | | | | | | | -10 | | 10 | | % |
| Dissipation factor | | $f = 1$ kHz | | | | 25 | | 0,15 | | | % |

Thermistor

Static

| | | | | | | | | | | | |
|--------------------------------|----------------|-------------------|--|--|--|-----|-----|------|-----|--|------|
| Rated resistance | R | | | | | 25 | | 5 | | | kΩ |
| Deviation of R100 | $\Delta_{R/R}$ | $R_{100} = 499$ Ω | | | | 100 | 3,2 | | 3,3 | | % |
| Power dissipation | P | | | | | 25 | | 130 | | | mW |
| Power dissipation constant | d | | | | | 25 | | 1,3 | | | mW/K |
| B-value | $B_{(25/50)}$ | Tol. ± 1 % | | | | | | 3380 | | | K |
| Vincotech Thermistor Reference | | | | | | | | | V | | |

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-EZ12B2A040MS-LQ17L73T

datasheet

Boost Switch Characteristics

figure 1. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




figure 2. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




figure 3. MOSFET

Typical transfer characteristics

$$I_D = f(V_{GS})$$





figure 4. MOSFET

Typical reverse current characteristics

$$I_{SD} = f(V_{SD})$$






Vincotech

Boost Switch Characteristics

figure 5. MOSFET

Transient thermal impedance as a function of pulse width

$Z_{th(j-a)} = f(t_p)$




| | |
|-----------------------------|------------|
| $D =$ | t_p / T |
| $R_{th(j-a)} =$ | 1,305 K/W |
| MOSFET thermal model values | |
| R (K/W) | τ (s) |
| 8,10E-02 | 2,89E+00 |
| 2,17E-01 | 2,87E-01 |
| 7,39E-01 | 5,99E-02 |
| 2,09E-01 | 6,28E-03 |
| 5,87E-02 | 3,95E-04 |

figure 6. MOSFET

Safe operating area

$I_D = f(V_{DS})$



| | |
|------------|--------------|
| $D =$ | single pulse |
| $T_s =$ | 80 °C |
| $V_{GS} =$ | 18 V |
| $T_j =$ | T_{jmax} |



Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet

Boost Diode Characteristics

figure 7. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



| | | |
|--------------------------|------------|-----|
| $D =$ | t_p / T | |
| $R_{th(j-s)} =$ | 1,296 | K/W |
| FWD thermal model values | | |
| R (K/W) | τ (s) | |
| 6,22E-02 | 4,27E+00 | |
| 2,36E-01 | 2,99E-01 | |
| 6,69E-01 | 4,31E-02 | |
| 2,88E-01 | 4,14E-03 | |
| 4,04E-02 | 1,25E-04 | |



Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet

Boost Sw. Protection Diode Characteristics

figure 9. Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 10. Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



| | | |
|--------------------------------|------------|-----|
| $D =$ | t_p / T | |
| $R_{th(j-s)} =$ | 1,314 | K/W |
| Rectifier thermal model values | | |
| R (K/W) | τ (s) | |
| 8,85E-02 | 1,99E+00 | |
| 2,65E-01 | 1,87E-01 | |
| 6,64E-01 | 4,96E-02 | |
| 2,12E-01 | 5,03E-03 | |
| 8,48E-02 | 4,58E-04 | |



Vincotech

10-EZ12B2A040MS-LQ17L73T
datasheet


Thermistor Characteristics

figure 11.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet


Boost Switching Characteristics

figure 12.

MOSFET

Typical switching energy losses as a function of drain current

$$E = f(I_D)$$



With an inductive load at


| | | | | |
|--------------|------|----------|--------|--------|
| $V_{DS} =$ | 600 | V | $T_j:$ | 25 °C |
| $V_{GS} =$ | 0/18 | V | | 125 °C |
| $R_{gon} =$ | 16 | Ω | | 150 °C |
| $R_{goff} =$ | 16 | Ω | | |

figure 14.

FWD

Typical reverse recovered energy loss as a function of drain current

$$E_{rec} = f(I_D)$$



With an inductive load at


| | | | | |
|-------------|------|----------|--------|--------|
| $V_{DS} =$ | 600 | V | $T_j:$ | 25 °C |
| $V_{GS} =$ | 0/18 | V | | 125 °C |
| $R_{gon} =$ | 16 | Ω | | 150 °C |

figure 13.

MOSFET

Typical switching energy losses as a function of MOSFET turn on gate resistor

$$E = f(R_g)$$



With an inductive load at


| | | | | |
|------------|------|---|--------|--------|
| $V_{DS} =$ | 600 | V | $T_j:$ | 25 °C |
| $V_{GS} =$ | 0/18 | V | | 125 °C |
| $I_D =$ | 32 | A | | 150 °C |

figure 15.

FWD

Typical reverse recovered energy loss as a function of MOSFET turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

| | | | | |
|------------|------|---|--------|--------|
| $V_{DS} =$ | 600 | V | $T_j:$ | 25 °C |
| $V_{GS} =$ | 0/18 | V | | 125 °C |
| $I_D =$ | 32 | A | | 150 °C |




Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet

Boost Switching Characteristics

figure 16. MOSFET

Typical switching times as a function of drain current
 $t = f(I_D)$




With an inductive load at

$T_j = 150$ °C
 $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 17. MOSFET

Typical switching times as a function of MOSFET turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $I_D = 32$ A

figure 18. FWD


Typical reverse recovery time as a function of drain current
 $t_{rr} = f(I_D)$



At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $R_{gon} = 16$ Ω
 $T_j: 25$ °C
 125 °C
 150 °C

figure 19. FWD

Typical reverse recovery time as a function of MOSFET turn on gate resistor
 $t_{rr} = f(R_{gon})$



At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $I_D = 32$ A
 $T_j: 25$ °C
 125 °C
 150 °C



Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet


Boost Switching Characteristics

figure 20.

FWD

Typical recovered charge as a function of drain current

$$Q_r = f(I_D)$$




At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $R_{gon} = 16$ Ω
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 21.

FWD

Typical recovered charge as a function of MOSFET turn on gate resistor

$$Q_r = f(R_{gon})$$




At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $I_D = 32$ A
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 22.

FWD

Typical peak reverse recovery current as a function of drain current

$$I_{RM} = f(I_D)$$




At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $R_{gon} = 16$ Ω
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 23.

FWD

Typical peak reverse recovery current as a function of MOSFET turn on gate resistor

$$I_{RM} = f(R_{gon})$$




At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $I_D = 32$ A
 T_j : 25 °C (blue), 125 °C (black), 150 °C (red)



Boost Switching Characteristics

figure 24. FWD

Typical rate of fall of forward and reverse recovery current as a function of drain current
 $di_f/dt, di_{rr}/dt = f(I_D)$




At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $R_{gon} = 16$ Ω
 $T_j = 25$ °C
125 °C
150 °C

figure 26. MOSFET

Reverse bias safe operating area


$I_D = f(V_{DS})$



At $T_j = 150$ °C
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 25. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{gon})$



At $V_{DS} = 600$ V
 $V_{GS} = 0/18$ V
 $I_D = 32$ A
 $T_j = 25$ °C
125 °C
150 °C



Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet

Boost Switching Definitions

figure 27. MOSFET

Turn-off Switching Waveforms & definition of t_{doff} t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 28. MOSFET

Turn-on Switching Waveforms & definition of t_{don} t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 29. MOSFET

Turn-off Switching Waveforms & definition of t_f





figure 30. MOSFET

Turn-on Switching Waveforms & definition of t_r





Vincotech

10-EZ12B2A040MS-LQ17L73T datasheet

Boost Switching Definitions

figure 31. FWD

Turn-off Switching Waveforms & definition of t_{rr}




figure 32. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





figure 33. FWD

Turn-on Switching Waveforms & definition of t_{Erec} (t_{Erec} = integrating time for E_{rec})





Vincotech

10-EZ12B2A040MS-LQ17L73T


datasheet


| Ordering Code | |
|--|------------------------------|
| Version | Ordering Code |
| Without thermal paste | 10-EZ12B2A040MS-LQ17L73T |
| With thermal paste (5,2 W/mK, PTM6000HV) | 10-EZ12B2A040MS-LQ17L73T-/7/ |

| Marking | | | | | | |
|---------|------------|-------------------------------|---------------------|----------------|-------------------|--------|
| | Text | Name | Date code | UL & VIN | Lot | Serial |
| | | NN-NNNNNNNNNNNNNNNN- TTTTTTVV | WWYY | UL VIN | LLLLL | SSSS |
| | Datamatrix | Type&Ver TTTTTTTVV | Lot number LLLLL | Serial SSSS | Date code WWYY | |

| Pin table [mm] | | | |
|----------------|---------------|------|----------|
| Pin | X | Y | Function |
| 1 | 32 | 3,2 | DC-2 |
| 2 | 32 | 0 | DC-2 |
| 3 | 28,8 | 3,2 | G4 |
| 4 | 28,8 | 0 | S4 |
| 5 | 12,8 | 0 | T2 |
| 6 | 9,6 | 0 | T1 |
| 7 | 0 | 0 | AC2 |
| 8 | 0 | 3,2 | AC2 |
| 9 | not assembled | | |
| 10 | not assembled | | |
| 11 | not assembled | | |
| 12 | not assembled | | |
| 13 | 0 | 22,4 | AC1 |
| 14 | 0 | 25,6 | AC1 |
| 15 | 28,8 | 25,6 | G2 |
| 16 | 28,8 | 22,4 | S2 |
| 17 | 32 | 25,6 | DC-1 |
| 18 | 32 | 22,4 | DC-1 |
| 19 | 22,4 | 12,8 | DC+ |
| 20 | 25,6 | 12,8 | DC+ |
| 21 | 28,8 | 12,8 | DC+ |
| 22 | 32 | 12,8 | DC+ |

center of press-fit pin head
pin head type "T": PCB plated through-hole $\Phi 1\text{mm} \pm 0.09 / -0.06$
for further PCB design rules refer to the latest handling instruction






Tolerance of pinposition: $\pm 0.4\text{mm}$ at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech

Pinout




Identification

| ID | Component | Voltage | Current | Function | Comment |
|----------|------------|---------|---------|----------------------------|---------|
| T25, T27 | MOSFET | 1200 V | 40 mΩ | Boost Switch | |
| D25, D27 | FWD | 1200 V | 20 A | Boost Diode | |
| D45, D47 | Rectifier | 1600 V | 28 A | Boost Sw. Protection Diode | |
| C25, C27 | Capacitor | 1500 V | | Capacitor (DC) | |
| Rt | Thermistor | | | Thermistor | |



Vincotech

10-EZ12B2A040MS-LQ17L73T
datasheet

| Packaging instruction | | | | |
|---|------|----------|------|---|
| Standard packaging quantity (SPQ) 100 | >SPQ | Standard | <SPQ | Sample |
| Handling instruction | | | | |
| Handling instructions for <i>flow</i> E1 packages see vincotech.com website. | | | | |
| Package data | | | | |
| Package data for <i>flow</i> E1 packages see vincotech.com website. | | | | |
| Vincotech thermistor reference | | | | |
| See Vincotech thermistor reference table at vincotech.com website. | | | | |
| UL recognition and file number | | | | |
| This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website. | | | |  |

| Document No.: | Date: | Modification: | Pages |
|--------------------------------|--------------|---|-------|
| 10-EZ12B2A040MS-LQ17L73T-D1-14 | 30 Jul. 2024 | Initial Release | |
| 10-EZ12B2A040MS-LQ17L73T-D2-14 | 16 Apr. 2026 | Correct Vgs of the Boost Switch Correct Outline drawing and Pintable | |

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.