



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

flowMNPC E3BP

1200 V / 400 A

## Topology features

- Kelvin Emitter for improved switching performance
- Mixed Voltage Neutral Point Clamped Topology (T-Type)
- Temperature sensor

## Component features

- High speed switching
- Low collector emitter saturation voltage
- Low turn-off losses
- Optimized for hard switching topologies
- Positive temperature coefficient

## Housing features

- Base isolation:  $\text{Al}_2\text{O}_3$
- Cu baseplate
- Convex shaped baseplate for superior thermal contact
- CTI600 housing material
- Baseplate with rough surface
- Thermo-mechanical push-and-pull force relief
- Solder pin


## Target applications

- Energy Storage Systems
- Solar Inverters
- UPS


## Types

- 30-E312NMA400H7-PM19F07Z

## flow E3BP 12 mm housing



## Schematic





Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter | Symbol | Conditions | Value | Unit |
|-----------|--------|------------|-------|------|
|-----------|--------|------------|-------|------|

### Buck Switch

|                                   |            |  |          |    |
|-----------------------------------|------------|--|----------|----|
| Collector-emitter voltage         | $V_{CES}$  |  | 1200     | V  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$            | 290      | A  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$                      | 1200     | A  |
| Turn off safe operating area      |            | $T_j = 150\text{ °C}$ , $V_{CE} = 1200\text{ V}$ | 1200     | A  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$            | 523      | W  |
| Gate-emitter voltage              | $V_{GES}$  |  | $\pm 20$ | V  |
| Maximum junction temperature      | $T_{jmax}$ |  | 175      | °C |

### Buck Diode

|                                 |            |                                       |      |    |
|---------------------------------|------------|---------------------------------------|------|----|
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 650  | V  |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 304  | A  |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 1200 | A  |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 429  | W  |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175  | °C |

### Boost Switch

|                                   |            |  |          |    |
|-----------------------------------|------------|--|----------|----|
| Collector-emitter voltage         | $V_{CES}$  |  | 650      | V  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$            | 282      | A  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$                      | 800      | A  |
| Turn off safe operating area      |            | $T_j = 150\text{ °C}$ , $V_{CE} = 1200\text{ V}$ | 800      | A  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$            | 457      | W  |
| Gate-emitter voltage              | $V_{GES}$  |  | $\pm 20$ | V  |
| Maximum junction temperature      | $T_{jmax}$ |  | 175      | °C |



Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                       | Symbol     | Conditions                            | Value | Unit |
|---------------------------------|------------|---------------------------------------|-------|------|
| <b>Boost Diode</b>              |            |                                       |       |      |
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 1200  | V    |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 197   | A    |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 1200  | A    |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 395   | W    |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175   | °C   |

## Module Properties

### Thermal Properties

|   |           |  |                            |    |
|---|-----------|--|----------------------------|----|
| Storage temperature                             | $T_{stg}$ |  | -40...+125                 | °C |
| Operation temperature under switching condition | $T_{jop}$ |  | -40...+( $T_{jmax} - 25$ ) | °C |

### Isolation Properties

|                            |            |                                     |       |    |
|----------------------------|------------|-------------------------------------|-------|----|
| Isolation voltage          | $V_{isol}$ | DC Test Voltage* $t_p = 2\text{ s}$ | 6000  | V  |
| Creepage distance          |            |                                     | >12,7 | mm |
| Clearance                  |            |                                     | >12,7 | mm |
| Comparative Tracking Index | CTI        |                                     | ≥ 600 |    |

\*100 % tested in production



Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Buck Switch

#### Static

|                                      |               |                          |      |      |        |                  |     |                      |                     |    |
|--------------------------------------|---------------|--------------------------|------|------|--------|------------------|-----|----------------------|---------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$  | $V_{CE} = V_{GE}$        |      |      | 0,0064 | 25               | 4,7 | 5,5                  | 6,2                 | V  |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ |                          | 15   |      | 400    | 25<br>125<br>150 |     | 1,78<br>1,94<br>1,98 | 2,15 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$     |                          | 0    | 1200 |        | 25               |     |                      | 16                  | μA |
| Gate-emitter leakage current         | $I_{GES}$     |                          | 20   | 0    |        | 25               |     |                      | 400                 | nA |
| Internal gate resistance             | $r_g$         |                          |      |      |        |                  |     | None                 |                     | Ω  |
| Input capacitance                    | $C_{ies}$     | $f = 100 \text{ kHz}$    | 0    | 25   |        | 25               |     | 52000                |                     | pF |
| Output capacitance                   | $C_{oes}$     |                          |      |      |        |                  |     | 960                  |                     | pF |
| Reverse transfer capacitance         | $C_{res}$     |                          |      |      |        |                  |     | 288                  |                     | pF |
| Gate charge                          | $Q_g$         | $V_{CC} = 960 \text{ V}$ | 0/15 |      | 400    | 25               |     | 2856                 |                     | nC |

#### Thermal

|  |               |   |  |  |  |  |  |      |  |     |
|--|---------------|---|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2 \text{ W/mK}$<br>(PTM) |  |  |  |  |  | 0,18 |  | K/W |
|--|---------------|---|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |  |          |     |     |                  |  |                            |  |     |
|-----------------------------|--------------|--|----------|-----|-----|------------------|--|----------------------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  | $R_{gon} = 2,13 \Omega$<br>$R_{goff} = 2 \Omega$ | $\pm 15$ | 350 | 400 | 25<br>125<br>150 |  | 163,54<br>166,53<br>167,08 |  | ns  |
| Rise time                   | $t_r$        |  |          |     |     | 25<br>125<br>150 |  | 23,35<br>25,4<br>26,18     |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |  |          |     |     | 25<br>125<br>150 |  | 150,59<br>175,22<br>181,85 |  | ns  |
| Fall time                   | $t_f$        |  |          |     |     | 25<br>125<br>150 |  | 35,83<br>59,96<br>65,61    |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     |  |          |     |     | 25<br>125<br>150 |  | 7,84<br>9,58<br>10,03      |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |  |          |     |     | 25<br>125<br>150 |  | 6,26<br>11,39<br>12,76     |  | mWs |





Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Buck Diode

#### Static

|                         |       |               |  |  |     |                  |  |                     |                     |    |
|-------------------------|-------|---------------|--|--|-----|------------------|--|---------------------|---------------------|----|
| Forward voltage         | $V_F$ |               |  |  | 400 | 25<br>125<br>150 |  | 1,65<br>1,6<br>1,58 | 1,92 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 650$ V |  |  |     | 25               |  |                     | 21,2                | µA |

#### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2$ W/mK<br>(PTM) |  |  |  |  |  | 0,22 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                                       |                      |  |          |     |     |                  |  |                              |  |      |
|---------------------------------------|----------------------|--|----------|-----|-----|------------------|--|------------------------------|--|------|
| Peak recovery current                 | $I_{RM}$             | $di/dt=14181$ A/µs<br>$di/dt=16927$ A/µs<br>$di/dt=16036$ A/µs | $\pm 15$ | 350 | 400 | 25<br>125<br>150 |  | 252,33<br>369,87<br>396,69   |  | A    |
| Reverse recovery time                 | $t_{rr}$             |  |          |     |     | 25<br>125<br>150 |  | 71,69<br>98,02<br>109,2      |  | ns   |
| Recovered charge                      | $Q_r$                |  |          |     |     | 25<br>125<br>150 |  | 9,33<br>20,18<br>23,36       |  | µC   |
| Reverse recovered energy              | $E_{rec}$            |  |          |     |     | 25<br>125<br>150 |  | 1,39<br>3,73<br>4,46         |  | mWs  |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ |  |          |     |     | 25<br>125<br>150 |  | 3908,85<br>4241,9<br>4306,97 |  | A/µs |



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            |     | Values |     |  | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|-----|--------|-----|--|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min | Typ    | Max |  |      |

### Boost Switch

#### Static

|                                      |              |                          |     |     |       |                  |      |                     |                    |    |
|--------------------------------------|--------------|--------------------------|-----|-----|-------|------------------|------|---------------------|--------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$ | $V_{CE} = V_{GE}$        |     |     | 0,004 | 25               | 3,25 | 4                   | 4,75               | V  |
| Collector-emitter saturation voltage | $V_{CEsat}$  |                          | 15  |     | 400   | 25<br>125<br>150 | 1,15 | 1,24<br>1,7<br>1,75 | 1,8 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$    |                          | 0   | 650 |       | 25               |      |                     | 100                | µA |
| Gate-emitter leakage current         | $I_{GES}$    |                          | 20  | 0   |       | 25               |      |                     | 400                | nA |
| Internal gate resistance             | $r_g$        |                          |     |     |       |                  |      | None                |                    | Ω  |
| Input capacitance                    | $C_{ies}$    | $f = 1 \text{ Mhz}$      | 0   | 25  |       | 25               |      | 22800               |                    | pF |
| Output capacitance                   | $C_{oes}$    |                          |     |     |       |                  |      | 660                 |                    | pF |
| Reverse transfer capacitance         | $C_{res}$    |                          |     |     |       |                  |      | 77,2                |                    | pF |
| Gate charge                          | $Q_g$        | $V_{CC} = 400 \text{ V}$ | ±15 |     | 400   | 25               |      | 1680                |                    | nC |

#### Thermal

|  |               |   |  |  |  |  |  |      |  |     |
|--|---------------|---|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2 \text{ W/mK}$<br>(PTM) |  |  |  |  |  | 0,21 |  | K/W |
|--|---------------|---|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |  |     |     |     |                  |  |                         |  |     |
|-----------------------------|--------------|--|-----|-----|-----|------------------|--|-------------------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  | $R_{gon} = 2,13 \Omega$<br>$R_{goff} = 2 \Omega$ | ±15 | 350 | 400 | 25<br>125<br>150 |  | 53,14<br>53,8<br>54,13  |  | ns  |
| Rise time                   | $t_r$        |  |     |     |     | 25<br>125<br>150 |  | 11,9<br>13,63<br>13,92  |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |  |     |     |     | 25<br>125<br>150 |  | 68,03<br>83,55<br>87,89 |  | ns  |
| Fall time                   | $t_f$        |  |     |     |     | 25<br>125<br>150 |  | 10,82<br>27,24<br>32,85 |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     |  |     |     |     | 25<br>125<br>150 |  | 2,59<br>4,02<br>4,42    |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |  |     |     |     | 25<br>125<br>150 |  | 3,49<br>5,92<br>6,65    |  | mWs |



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Boost Diode

#### Static

|                         |       |                |  |  |     |                  |  |                      |                  |    |
|-------------------------|-------|----------------|--|--|-----|------------------|--|----------------------|------------------|----|
| Forward voltage         | $V_F$ |                |  |  | 400 | 25<br>125<br>150 |  | 3,11<br>2,96<br>2,88 | 3 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 1200$ V |  |  |     | 25               |  |                      | 16               | µA |

#### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 5,2$ W/mK<br>(PTM) |  |  |  |  |  | 0,24 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                                       |                      |  |          |     |     |                  |  |                                  |  |      |
|---------------------------------------|----------------------|--|----------|-----|-----|------------------|--|----------------------------------|--|------|
| Peak recovery current                 | $I_{RM}$             | $di/dt=32542$ A/µs<br>$di/dt=27583$ A/µs<br>$di/dt=26872$ A/µs | $\pm 15$ | 350 | 400 | 25<br>125<br>150 |  | 533,44<br>639,85<br>663,43       |  | A    |
| Reverse recovery time                 | $t_{rr}$             |  |          |     |     | 25<br>125<br>150 |  | 30<br>96,31<br>102,03            |  | ns   |
| Recovered charge                      | $Q_r$                |  |          |     |     | 25<br>125<br>150 |  | 8,88<br>19,69<br>22,54           |  | µC   |
| Reverse recovered energy              | $E_{rec}$            |  |          |     |     | 25<br>125<br>150 |  | 1,49<br>4,19<br>4,82             |  | mWs  |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ |  |          |     |     | 25<br>125<br>150 |  | 71583,58<br>49801,89<br>43067,13 |  | A/µs |



Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |   |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|---|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Thermistor

#### Static

|                                |                |                         |  |  |  |     |    |      |   |      |
|--------------------------------|----------------|-------------------------|--|--|--|-----|----|------|---|------|
| Rated resistance               | $R$            |                         |  |  |  | 25  |    | 22   |   | kΩ   |
| Deviation of R100              | $\Delta_{R/R}$ | $R_{100} = 1484 \Omega$ |  |  |  | 100 | -5 |      | 5 | %    |
| Power dissipation              | $P$            |                         |  |  |  | 25  |    | 130  |   | mW   |
| Power dissipation constant     | $d$            |                         |  |  |  | 25  |    | 1,5  |   | mW/K |
| B-value                        | $B_{(25/50)}$  | Tol. $\pm 1 \%$         |  |  |  |     |    | 3962 |   | K    |
| B-value                        | $B_{(25/100)}$ | Tol. $\pm 1 \%$         |  |  |  |     |    | 4000 |   | K    |
| Vincotech Thermistor Reference |                |                         |  |  |  |     |    |      | I |      |

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$





figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



| IGBT thermal model values |            |
|---------------------------|------------|
| $R$ (K/W)                 | $\tau$ (s) |
| 1,41E-02                  | 9,72E+00   |
| 2,56E-02                  | 1,95E+00   |
| 8,76E-02                  | 1,03E-01   |
| 4,21E-02                  | 1,58E-02   |
| 1,24E-02                  | 4,42E-04   |



Vincotech


**30-E312NMA400H7-PM19F07Z**  
datasheet

## Buck Switch Characteristics

**figure 5.** IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D =$  single pulse  
 $T_s = 80 \text{ } ^\circ\text{C}$   
 $V_{GE} = 15 \text{ V}$   
 $T_j = T_{jmax}$

**figure 6.** IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 400 \text{ A}$   
 $T_j = 25 \text{ } ^\circ\text{C}$



Vincotech

## Buck Diode Characteristics

figure 7.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



|                          |            |
|--------------------------|------------|
| $D =$                    | $t_p / T$  |
| $R_{th(j-s)} =$          | 0,222 K/W  |
| FWD thermal model values |            |
| $R$ (K/W)                | $\tau$ (s) |
| 2,97E-02                 | 5,14E+00   |
| 3,36E-02                 | 3,91E-01   |
| 1,15E-01                 | 4,51E-02   |
| 3,29E-02                 | 5,21E-03   |
| 1,08E-02                 | 2,04E-04   |



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet


## Boost Switch Characteristics

figure 9.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$



$t_p = 250 \mu s$   
 $V_{GE} = 15 V$


$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

figure 10.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_j = 150 \text{ °C}$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

figure 11.

IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$



$t_p = 250 \mu s$   
 $V_{CE} = 10 V$


$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

figure 12.

IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0.208 \text{ K/W}$   
IGBT thermal model values  

| $R \text{ (K/W)}$ | $\tau \text{ (s)}$ |
|-------------------|--------------------|
| 1.97E-02          | 7.27E+00           |
| 2.56E-02          | 9.80E-01           |
| 1.18E-01          | 5.85E-02           |
| 3.10E-02          | 6.51E-03           |
| 1.44E-02          | 1.96E-04           |





Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet


## Boost Switch Characteristics

figure 13.

IGBT

Safe operating area

$I_C = f(V_{CE})$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$

$V_{GE} = 15 \text{ V}$

$T_j = T_{jmax}$



Vincotech

## Boost Diode Characteristics

figure 14.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 15.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



|                          |            |     |
|--------------------------|------------|-----|
| $D =$                    | $t_p / T$  |     |
| $R_{th(j-s)} =$          | 0,24       | K/W |
| FWD thermal model values |            |     |
| $R$ (K/W)                | $\tau$ (s) |     |
| 2,57E-02                 | 6,18E+00   |     |
| 3,31E-02                 | 7,29E-01   |     |
| 1,25E-01                 | 6,10E-02   |     |
| 3,91E-02                 | 7,17E-03   |     |
| 1,76E-02                 | 3,66E-04   |     |



Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet


## Thermistor Characteristics

figure 16.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet


## Buck Switching Characteristics

figure 17.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$   
 $R_{goff} = 2$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 19.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 18.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A


$T_j$ : 25 °C  
125 °C  
150 °C

figure 20.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

$T_j$ : 25 °C  
125 °C  
150 °C



Vincotech


30-E312NMA400H7-PM19F07Z  
datasheet

## Buck Switching Characteristics

figure 21.

IGBT

Typical switching times as a function of collector current  
 $t = f(I_C)$




With an inductive load at

$T_j = 150$  °C  
 $V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$   
 $R_{goff} = 2$   $\Omega$

figure 22.

IGBT

Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 150$  °C  
 $V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

figure 23.

FWD

Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

figure 24.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



Vincotech

30-E312NMA400H7-PM19F07Z  
datasheet


## Buck Switching Characteristics

figure 25.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 27.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 26.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 400$  A


$T_j$ : 25 °C  
125 °C  
150 °C

figure 28.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 400$  A

$T_j$ : 25 °C  
125 °C  
150 °C




Vincotech

30-E312NMA400H7-PM19F07Z  
datasheet

## Buck Switching Characteristics

figure 29. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$

$T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 30. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

$T_j$ : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 31. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At  $T_j = 150$  °C  
 $R_{gon} = 2,13$   $\Omega$   
 $R_{goff} = 2$   $\Omega$



Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet


## Boost Switching Characteristics

figure 32.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at


|              |      |   |        |        |
|--------------|------|---|--------|--------|
| $V_{CE} =$   | 350  | V | $T_j:$ | 25 °C  |
| $V_{GE} =$   | ±15  | V |        | 125 °C |
| $R_{gon} =$  | 2,13 | Ω |        | 150 °C |
| $R_{goff} =$ | 2    | Ω |        |        |

figure 34.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at


|             |      |   |        |        |
|-------------|------|---|--------|--------|
| $V_{CE} =$  | 350  | V | $T_j:$ | 25 °C  |
| $V_{GE} =$  | ±15  | V |        | 125 °C |
| $R_{gon} =$ | 2,13 | Ω |        | 150 °C |

figure 33.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at


|            |     |   |        |        |
|------------|-----|---|--------|--------|
| $V_{CE} =$ | 350 | V | $T_j:$ | 25 °C  |
| $V_{GE} =$ | ±15 | V |        | 125 °C |
| $I_C =$    | 400 | A |        | 150 °C |

figure 35.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

|            |     |   |        |        |
|------------|-----|---|--------|--------|
| $V_{CE} =$ | 350 | V | $T_j:$ | 25 °C  |
| $V_{GE} =$ | ±15 | V |        | 125 °C |
| $I_C =$    | 400 | A |        | 150 °C |





Vincotech

30-E312NMA400H7-PM19F07Z  
datasheet


## Boost Switching Characteristics

figure 36.

IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$



With an inductive load at


$T_j = 150$  °C  
 $V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$   
 $R_{goff} = 2$   $\Omega$

figure 37.

IGBT

Typical switching times as a function of IGBT turn on gate resistor

$$t = f(R_g)$$



With an inductive load at


$T_j = 150$  °C  
 $V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

figure 38.

FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 39.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

$T_j$ : 25 °C  
125 °C  
150 °C



Vincotech

30-E312NMA400H7-PM19F07Z  
datasheet


## Boost Switching Characteristics

figure 40.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 42.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$


$T_j$ : 25 °C  
125 °C  
150 °C

figure 41.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 400$  A


$T_j$ : 25 °C  
125 °C  
150 °C

figure 43.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 400$  A

$T_j$ : 25 °C  
125 °C  
150 °C



Vincotech


# 30-E312NMA400H7-PM19F07Z

datasheet

## Boost Switching Characteristics

figure 44. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 2,13$   $\Omega$

$T_j$ : 25 °C  
125 °C  
150 °C

figure 45. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 350$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 400$  A

$T_j$ : 25 °C  
125 °C  
150 °C

figure 46. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At  $T_j = 150$  °C  
 $R_{gon} = 2,13$   $\Omega$   
 $R_{goff} = 2$   $\Omega$



Vincotech

# 30-E312NMA400H7-PM19F07Z datasheet

## Switching Definitions

figure 47. IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 48. IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 49. IGBT

Turn-off Switching Waveforms & definition of  $t_f$





figure 50. IGBT

Turn-on Switching Waveforms & definition of  $t_r$





Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Switching Definitions

figure 51.

FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$





figure 52.

FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )





Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

| Ordering Code                            |                              |
|--|------------------------------|
| Version                                  | Ordering Code                |
| Without thermal paste                    | 30-E312NMA400H7-PM19F07Z     |
| With thermal paste (5,2 W/mK, PTM6000HV) | 30-E312NMA400H7-PM19F07Z-/7/ |

| Marking |            |                               |            |           |           |        |
|---------|------------|-------------------------------|------------|-----------|-----------|--------|
|         | Text       | Name                          |            | Date code | UL & VIN  | Lot    |
|         |            | NN-NNNNNNNNNNNNNNNN- TTTTWWYY |            | WWYY      | UL VIN    | LLLL   |
|         | Datamatrix | Type&Ver                      | Lot number | Serial    | Date code | Serial |
|         |            | TTTTTTTV                      | LLLLL      | SSSS      | WWYY      | SSSS   |

| Outline        |       |     |          |    |       |      |        |
|----------------|-------|-----|----------|----|-------|------|--------|
| Pin table [mm] |       |     |          |    |       |      |        |
| Pin            | X     | Y   | Function | 39 | 40,16 | 48   | Ph2    |
| 1              | 0     | 0   | DC-1     | 40 | 43,36 | 48   | Ph2    |
| 2              | 0     | 3,2 | DC-1     | 41 | 46,56 | 48   | Ph2    |
| 3              | 0     | 6,4 | DC-1     | 42 | 49,76 | 48   | Ph2    |
| 4              | 32    | 0   | DC-1     | 43 | 52,96 | 48   | Ph2    |
| 5              | 32    | 3,2 | DC-1     | 44 | 56,16 | 48   | Ph2    |
| 6              | 32    | 6,4 | DC-1     | 45 | 59,36 | 48   | Ph2    |
| 7              | 40,16 | 0   | DC-2     | 46 | 62,56 | 48   | Ph2    |
| 8              | 40,16 | 3,2 | DC-2     | 47 | 16    | 41,6 | G11-1  |
| 9              | 40,16 | 6,4 | DC-2     | 48 | 56,16 | 41,6 | G11-2  |
| 10             | 72,16 | 0   | DC-2     | 49 | 16    | 44,8 | S11-1  |
| 11             | 72,16 | 3,2 | DC-2     | 50 | 56,16 | 44,8 | S11-2  |
| 12             | 72,16 | 6,4 | DC-2     | 51 | 6,4   | 35,2 | G12-11 |
| 13             | 6,4   | 0   | GND1     | 52 | 25,6  | 35,2 | G12-12 |
| 14             | 6,4   | 3,2 | GND1     | 53 | 46,56 | 35,2 | G12-21 |
| 15             | 25,6  | 0   | GND1     | 54 | 65,76 | 35,2 | G12-22 |
| 16             | 25,6  | 3,2 | GND1     | 55 | 3,2   | 35,2 | S12-1  |
| 17             | 46,56 | 0   | GND2     | 56 | 28,8  | 35,2 | S12-1  |
| 18             | 46,56 | 3,2 | GND2     | 57 | 43,36 | 35,2 | S12-2  |
| 19             | 65,76 | 0   | GND2     | 58 | 68,96 | 35,2 | S12-2  |
| 20             | 65,76 | 3,2 | GND2     | 59 | 6,4   | 6,4  | G13-11 |
| 21             | 12,8  | 0   | DC+1     | 60 | 25,6  | 6,4  | G13-12 |
| 22             | 16    | 0   | DC+1     | 61 | 46,56 | 6,4  | G13-21 |
| 23             | 19,2  | 0   | DC+1     | 62 | 65,76 | 6,4  | G13-22 |
| 24             | 16    | 3,2 | DC+1     | 63 | 9,6   | 6,4  | S13-1  |
| 25             | 16    | 6,4 | DC+1     | 64 | 22,4  | 6,4  | S13-1  |
| 26             | 52,96 | 0   | DC+2     | 65 | 49,76 | 6,4  | S13-2  |
| 27             | 56,16 | 0   | DC+2     | 66 | 62,56 | 6,4  | S13-2  |
| 28             | 59,36 | 0   | DC+2     | 67 | 9,6   | 25,6 | G14-11 |
| 29             | 56,16 | 3,2 | DC+2     | 68 | 22,4  | 25,6 | G14-12 |
| 30             | 56,16 | 6,4 | DC+2     | 69 | 49,76 | 25,6 | G14-21 |
| 31             | 9,6   | 48  | Ph1      | 70 | 62,56 | 25,6 | G14-22 |
| 32             | 12,8  | 48  | Ph1      | 71 | 12,8  | 25,6 | S14-1  |
| 33             | 16    | 48  | Ph1      | 72 | 19,2  | 25,6 | S14-1  |
| 34             | 19,2  | 48  | Ph1      | 73 | 52,96 | 25,6 | S14-2  |
| 35             | 22,4  | 48  | Ph1      | 74 | 59,36 | 25,6 | S14-2  |
| 36             | 25,6  | 48  | Ph1      | 75 | 72,16 | 48   | Therm1 |
| 37             | 28,8  | 48  | Ph1      | 76 | 72,16 | 44,8 | Therm2 |
| 38             | 32    | 48  | Ph1      |    |       |      |        |




Vincotech

# 30-E312NMA400H7-PM19F07Z

datasheet

## Pinout



$n=1,2$

$m=11,12,21,22$

See exact Pin numbers and Pin functions on Outline


## Identification

| ID       | Component  | Voltage | Current | Function     | Comment  |
|----------|------------|---------|---------|--------------|--|
| T11, T12 | IGBT       | 1200 V  | 400 A   | Buck Switch  | Parallel devices with separate control. Values apply to complete device. |
| D11, D12 | FWD        | 650 V   | 400 A   | Buck Diode   | Parallel devices. Values apply to complete device.                       |
| T13, T14 | IGBT       | 650 V   | 400 A   | Boost Switch | Parallel devices with separate control. Values apply to complete device. |
| D13, D14 | FWD        | 1200 V  | 400 A   | Boost Diode  | Parallel devices. Values apply to complete device.                       |
| Rt       | Thermistor |         |         | Thermistor   |  |



Vincotech

**30-E312NMA400H7-PM19F07Z**  
datasheet

| Packaging instruction   |      |          |      |   |
|---|------|----------|------|---|
| Standard packaging quantity (SPQ) 24  | >SPQ | Standard | <SPQ | Sample  |
| Handling instruction  |      |          |      |   |
| Handling instructions for <i>flow</i> E3BP packages see vincotech.com website.  |      |          |      |   |
| Package data  |      |          |      |   |
| Package data for <i>flow</i> E3BP packages see vincotech.com website.   |      |          |      |   |
| Vincotech thermistor reference  |      |          |      |   |
| See Vincotech thermistor reference table at vincotech.com website.  |      |          |      |   |
| UL recognition and file number  |      |          |      |   |
| This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website. |      |          |      |  |

| Document No.:                  | Date:        | Modification:                                    | Pages |
|--------------------------------|--------------|--|-------|
| 30-E312NMA400H7-PM19F07Z-D2-14 | 12 Nov. 2025 | Change Outline drawing according to PCN-2025-026 |       |

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.