



Vincotech

B0-EP122PA002MS-PG88F78T

target datasheet

flowDUAL E3 SiC

1200 V / 2 m Ω

Topology features

- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- High Blocking Voltage with low drain source on state resistance
- High speed SiC-MOSFET technology
- Resistant to Latch-up

Housing features

- Base isolation: Al₂O₃
- CTI600 housing material
- Compact, baseplate-less housing
- VINcoPress Technology
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection


Target applications

- Charging Stations
- Energy Storage Systems
- General
- Industrial Drives
- Power Supply
- Servo Drives
- Solar Inverters
- UPS


Types

- B0-EP122PA002MS-PG88F78T

flow E3 12 mm housing



Schematic





Vincotech

B0-EP122PA002MS-PG88F78T
target datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Half-Bridge Switch				
Drain-source voltage	V_{DS}		1200	V
Drain current (DC current)	I_D	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	1036	A
Peak drain current	I_{DM}	t_p limited by T_{jmax}	2272	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	424	W
Gate-source voltage	V_{GSS}		-5 / 18	V
		dynamic	-10 / 22	
Maximum Junction Temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage $t_p = 2\text{ s}$	6800	V
Creepage distance			>12,7	mm
Clearance			10,01	mm
Comparative Tracking Index	CTI		≥ 600	



Vincotech

B0-EP122PA002MS-PG88F78T
target datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Half-Bridge Switch

Static

Drain-source on-state resistance	$r_{DS(on)}$		18		568	25		2,12	3,12	mΩ
Gate-source threshold voltage	$V_{GS(th)}$				0,0568	25	1,7	2,25	2,75	V
Gate to Source Leakage Current	I_{GSS}		22	0		25			800	nA
Zero Gate Voltage Drain Current	I_{DSS}		0	1200		25			80	μA
Internal gate resistance	r_g							0,125		Ω
Gate charge	Q_g		-5/18	800	568	25		1504		nC
Short-circuit input capacitance	C_{iss}	$f = 500 \text{ kHz}$	0	800	0	25		37440		pF
Short-circuit output capacitance	C_{oss}							1880		
Reverse transfer capacitance	C_{rss}							64		
Diode forward voltage	V_{SD}		0		568	25		4,1		V

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						0,22		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Thermistor



Static

Rated resistance	R					25		5		kΩ
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 493 \text{ Ω}$				100	-5		5	%
Power dissipation	P							245		mW
Power dissipation constant	d					25		1,4		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 2 \%$						3375		K
B-value	$B_{(25/100)}$	Tol. $\pm 2 \%$						3437		K
Vincotech Thermistor Reference									K	



target datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	B0-EP122PA002MS-PG88F78T
With thermal paste (5,2 W/mK, PTM6000HV)	B0-EP122PA002MS-PG88F78T-/7/

Marking							
	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNN- TTTTTIVV		WWYY	UL VIN	LLLLL	SSSS
		Datamatrix	Type&Ver	Lot number	Serial	Date code	
TTTTTIVV			LLLLL	SSSS	WWYY		

Outline							
Pin table [mm]							
Pin	X	Y	Function	31	32	19,2	DC-
1	0	6,4	S11-2	32	28,8	19,2	DC-
2	0	9,6	G11-2	33	32	0	DC-
3	0	38,4	G11-1	34	28,8	0	DC-
4	0	41,6	S11-1	35	32	3,2	DC-
5	16	3,2	Ph	36	28,8	3,2	DC-
6	12,8	3,2	Ph	37	46,56	3,2	DC+
7	16	6,4	Ph	38	46,56	6,4	DC+
8	12,8	6,4	Ph	39	46,56	9,6	DC+
9	16	19,2	Ph	40	46,56	12,8	DC+
10	12,8	19,2	Ph	41	46,56	16	DC+
11	3,2	19,2	Ph	42	43,36	16	DC+
12	0	22,4	Ph	43	46,56	19,2	DC+
13	0	25,6	Ph	44	43,36	19,2	DC+
14	3,2	28,8	Ph	45	46,56	28,8	DC+
15	12,8	28,8	Ph	46	43,36	28,8	DC+
16	16	28,8	Ph	47	46,56	32	DC+
17	16	41,6	Ph	48	43,36	32	DC+
18	12,8	41,6	Ph	49	46,56	35,2	DC+
19	16	44,8	Ph	50	46,56	38,4	DC+
20	12,8	44,8	Ph	51	46,56	41,6	DC+
21	32	44,8	DC-	52	46,56	44,8	DC+
22	28,8	44,8	DC-	53	72,16	6,4	S12-2
23	32	48	DC-	54	72,16	9,6	G12-2
24	28,8	48	DC-	55	72,16	38,4	G12-1
25	32	28,8	DC-	56	72,16	41,6	S12-1
26	28,8	28,8	DC-	57	72,16	25,6	Therm1
27	32	32	DC-	58	72,16	22,4	Therm2
28	28,8	32	DC-	59	not assembled		
29	32	16	DC-	60	not assembled		
30	28,8	16	DC-				


center of press-fit pin head
pin head type 1: Pits pattern through-hole Ø1mm ±0,09-0,06
for further PCB design rules refer to the latest handling instruction

36,00
28
12
X
Y

Tolerance of position: column of the end of the pins
Tolerance of coordinate axis is only used without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T13, T12, T14	MOSFET	1200 V	2,12 mΩ	Half-Bridge Switch	
Rt	Thermistor			Thermistor	



Vincotech

B0-EP122PA002MS-PG88F78T
target datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 40	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> E3 packages see vincotech.com website.

Package data
Package data for <i>flow</i> E3 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,op}=150^{\circ}\text{C}$ and up to 4000VAC/1min isolation voltage. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
B0-EP122PA002MS-PG88F78T-T1-14	19 Mar. 2025	Initial Release	

Product status definition		
Datasheet Status	Product Status	Definition
Target	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. The data contained is exclusively intended for technically trained staff.

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.