



Vincotech

10-FY07HVA075S503-L985F15

datasheet

flowPACK 1 H6.5

650 V / 75 A

Topology features

- H6.5
- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- High speed and smooth switching
- Low gate charge
- Very low collector emitter saturation voltage

Housing features

- Base isolation: Al_2O_3
- Convex shaped substrate for superior thermal contact
- Thermo-mechanical push-and-pull force relief
- Solder pin


Target applications

- Solar Inverters
- Energy Storage Systems


Types

- 10-FY07HVA075S503-L985F15

flow 1 12 mm housing



Schematic





Vincotech

10-FY07HVA075S503-L985F15
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Low Buck Switch

Collector-emitter voltage	V_{CES}		650	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	56	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	80	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

High Buck Switch

Collector-emitter voltage	V_{CES}		650	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	56	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	80	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Buck Diode

Peak repetitive reverse voltage	V_{RRM}		650	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	46	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	208	A
Surge current capability	I^2_t		216	A²s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	70	W
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Boost Switch

Collector-emitter voltage	V_{CES}		650	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	56	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	80	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Low Boost Diode

Peak repetitive reverse voltage	V_{RRM}		650	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	46	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	208	A
Surge current capability	I^2t		216	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	70	W
Maximum junction temperature	T_{jmax}		175	°C

High Boost Diode

Peak repetitive reverse voltage	V_{RRM}		650	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	46	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	208	A
Surge current capability	I^2t		216	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	70	W
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

10-FY07HVA075S503-L985F15
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+(T_{jmax} - 25)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			>12,7	mm
Clearance			7,85	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Low Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,00075	25	3,2	4	4,8	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		75	25 125 150		1,41 1,52 1,55	1,75 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	650		25			50	µA
Gate-emitter leakage current	I_{GES}		20	0		25			100	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		4500		pF
Output capacitance	C_{oes}							130		pF
Reverse transfer capacitance	C_{res}							17		pF
Gate charge	Q_g	$V_{CC} = 520 \text{ V}$	15		75	25		164		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						1,19		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \text{ } \Omega$ $R_{goff} = 4 \text{ } \Omega$	-5/15	350	75	25 125 150		33,96 34,39 34,07		ns
Rise time	t_r					25 125 150		10,38 11,04 11,61		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		98,78 116,81 121,6		ns
Fall time	t_f					25 125 150		15,86 33,45 37,64		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=0,255 \text{ } \mu\text{C}$ $Q_{tFWD}=0,29 \text{ } \mu\text{C}$ $Q_{tFWD}=0,297 \text{ } \mu\text{C}$				25 125 150		0,197 0,319 0,382		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,731 1,16 1,31		mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

High Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,00075	25	3,2	4	4,8	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		75	25 125 150		1,41 1,52 1,55	1,75 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	650		25			50	µA
Gate-emitter leakage current	I_{GES}		20	0		25			100	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		4500		pF
Output capacitance	C_{oes}							130		pF
Reverse transfer capacitance	C_{res}							17		pF
Gate charge	Q_g	$V_{CC} = 520 \text{ V}$	15		75	25		164		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						1,19		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \text{ } \Omega$ $R_{goff} = 4 \text{ } \Omega$	-5/15	350	75	25 125 150		33,96 34,39 34,07		ns
Rise time	t_r					25 125 150		10,38 11,04 11,61		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		98,78 116,81 121,6		ns
Fall time	t_f					25 125 150		15,86 33,45 37,64		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		0,197 0,319 0,382		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,731 1,16 1,31		mWs



Vincotech

10-FY07HVA075S503-L985F15
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Buck Diode

Static

Forward voltage	V_F				40	25 125 150		1,33 1,4 1,43	1,5 ⁽¹⁾ 1,71 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 650$ V				25 150		0,12 8	200 800	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						1,35		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=3430$ A/µs $di/dt=6261$ A/µs $di/dt=6798$ A/µs	-5/15	350	75	25 125 150		31,31 36,04 35,91		A
Reverse recovery time	t_{rr}					25 125 150		13,7 13,34 13,47		ns
Recovered charge	Q_r					25 125 150		0,255 0,29 0,297		µC
Reverse recovered energy	E_{rec}					25 125 150		0,043 0,049 0,051		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		5700,41 7509,67 7172,52		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,00075	25	3,2	4	4,8	V
Collector-emitter saturation voltage	V_{CEsat}		15		75	25 125 150		1,41 1,52 1,55	1,75 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	650		25			50	µA
Gate-emitter leakage current	I_{GES}		20	0		25			100	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		4500		pF
Output capacitance	C_{oes}							130		pF
Reverse transfer capacitance	C_{res}							17		pF
Gate charge	Q_g	$V_{CC} = 520 \text{ V}$	15		75	25		164		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						1,19		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4 \text{ Ω}$ $R_{goff} = 4 \text{ Ω}$	-5/15	350	75	25 125 150		34,23 34,8 34,86		ns
Rise time	t_r					25 125 150		12,21 13,06 12,47		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		99,72 117,22 122,8		ns
Fall time	t_f					25 125 150		15,71 30,6 37,85		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		0,198 0,306 0,368		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		0,746 1,17 1,29		mWs



Vincotech

10-FY07HVA075S503-L985F15
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Low Boost Diode

Static

Forward voltage	V_F			40	25 125 150		1,33 1,4 1,43	1,5 ⁽¹⁾ 1,71 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 650$ V			25 150		0,12 8	200 800	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)					1,35		K/W
--	---------------	---------------------------------------	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=6204$ A/µs $di/dt=4479$ A/µs $di/dt=3208$ A/µs	-5/15	350	75	25 125 150		26,49 24,29 21,91		A
Reverse recovery time	t_{rr}					25 125 150		13,24 13,2 13,47		ns
Recovered charge	Q_r					25 125 150		0,213 0,196 0,179		µC
Reverse recovered energy	E_{rec}					25 125 150		0,032 0,027 0,024		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		5420,33 5013,77 3929,24		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

High Boost Diode

Static

Forward voltage	V_F			40	25 125 150		1,33 1,4 1,43	1,5 ⁽¹⁾ 1,71 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 650$ V			25 150		0,12 8	200 800	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)					1,35		K/W
--	---------------	---------------------------------------	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=6204$ A/µs $di/dt=4479$ A/µs $di/dt=3208$ A/µs	-5/15	350	75	25 125 150		26,49 24,29 21,91		A
Reverse recovery time	t_{rr}					25 125 150		13,24 13,2 13,47		ns
Recovered charge	Q_r					25 125 150		0,213 0,196 0,179		µC
Reverse recovered energy	E_{rec}					25 125 150		0,032 0,027 0,024		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		5420,33 5013,77 3929,24		A/µs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

10-FY07HVA075S503-L985F15

datasheet

Low Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$





figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



IGBT thermal model values	
R (K/W)	τ (s)
4,48E-02	6,76E+00
1,96E-01	8,22E-01
7,16E-01	6,95E-02
1,70E-01	1,03E-02
6,03E-02	1,14E-03




Vincotech

Low Buck Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D = \text{single pulse}$
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 75 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$



Vincotech

10-FY07HVA075S503-L985F15


datasheet

High Buck Switch Characteristics

figure 7. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 9. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 14 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 10. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,187 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
4,48E-02	6,76E+00
1,96E-01	8,22E-01
7,16E-01	6,95E-02
1,70E-01	1,03E-02
6,03E-02	1,14E-03



Vincotech


High Buck Switch Characteristics

figure 11.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D = \text{single pulse}$
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$

figure 12.

IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 75 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$



Vincotech


Buck Diode Characteristics

figure 13.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$



$t_p = 250 \mu s$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 14.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,355 \text{ K/W}$
FWD thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
2,60E-02	7,41E+00
1,46E-01	7,76E-01
8,02E-01	7,00E-02
2,77E-01	7,44E-03
1,10E-01	9,71E-04



Vincotech

10-FY07HVA075S503-L985F15


datasheet

Boost Switch Characteristics

figure 15. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 16. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 17. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 14 V$

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 18. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,187 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
4,48E-02	6,76E+00
1,96E-01	8,22E-01
7,16E-01	6,95E-02
1,70E-01	1,03E-02
6,03E-02	1,14E-03



Vincotech


Boost Switch Characteristics

figure 19.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D = \text{single pulse}$
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$

figure 20.

IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 75 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$



Vincotech

Low Boost Diode Characteristics

figure 21.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 22.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	1,355 K/W
FWD thermal model values	
R (K/W)	τ (s)
2,60E-02	7,41E+00
1,46E-01	7,76E-01
8,02E-01	7,00E-02
2,77E-01	7,44E-03
1,10E-01	9,71E-04



Vincotech

10-FY07HVA075S503-L985F15
datasheet

High Boost Diode Characteristics

figure 23.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 24.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech


10-FY07HVA075S503-L985F15
datasheet

Thermistor Characteristics

figure 25. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

10-FY07HVA075S503-L985F15 datasheet


Low Buck Switching Characteristics

figure 26.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 27.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $I_c = 75 \text{ A}$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 28.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$


T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)

figure 29.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $I_c = 75 \text{ A}$

T_j : $25 \text{ } ^\circ\text{C}$ (blue)
 $125 \text{ } ^\circ\text{C}$ (black)
 $150 \text{ } ^\circ\text{C}$ (red)



Vincotech


10-FY07HVA075S503-L985F15 datasheet

Low Buck Switching Characteristics

figure 30.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 31.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

figure 32.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω

T_j : 25 °C
125 °C
150 °C

figure 33.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C



Vincotech

10-FY07HVA075S503-L985F15
datasheet


Low Buck Switching Characteristics

figure 34.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 36.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 35.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 37.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C




Vincotech

10-FY07HVA075S503-L985F15
datasheet

Low Buck Switching Characteristics

figure 38. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 39. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_C = 75$ A

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 40. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Vincotech

10-FY07HVA075S503-L985F15
datasheet


High Buck Switching Characteristics

figure 41.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 42.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 43.

IGBT

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 44.

IGBT

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C



Vincotech


10-FY07HVA075S503-L985F15
datasheet

High Buck Switching Characteristics

figure 45.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 46.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

figure 47.

IGBT

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω

T_j : 25 °C (blue)
125 °C (black)
150 °C (red)

figure 48.

IGBT

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C (blue)
125 °C (black)
150 °C (red)



Vincotech

10-FY07HVA075S503-L985F15
datasheet


High Buck Switching Characteristics

figure 49.

IGBT

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 51.

IGBT

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 50.

IGBT

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 52.

IGBT

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C




Vincotech

10-FY07HVA075S503-L985F15
datasheet

High Buck Switching Characteristics

figure 53. IGBT

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω

T_j : 25 °C
125 °C
150 °C

figure 54. IGBT

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_C = 75$ A

T_j : 25 °C
125 °C
150 °C

figure 55. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Vincotech

10-FY07HVA075S503-L985F15

datasheet


Boost Switching Characteristics

figure 56.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 57.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 58.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $R_{gon} = 4$ Ω


T_j : 25 °C
125 °C
150 °C

figure 59.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = -5/15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C



Vincotech

10-FY07HVA075S503-L985F15 datasheet

Boost Switching Characteristics

figure 60.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




figure 61.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




figure 62.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$





figure 63.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$





Vincotech

10-FY07HVA075S503-L985F15
datasheet


Boost Switching Characteristics

figure 64.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 350 \text{ V} \\ V_{GE} &= -5/15 \text{ V} \\ R_{gon} &= 4 \text{ } \Omega \end{aligned}$$


$$T_j: \begin{aligned} & \text{— } 25 \text{ } ^\circ\text{C} \\ & \text{— } 125 \text{ } ^\circ\text{C} \\ & \text{— } 150 \text{ } ^\circ\text{C} \end{aligned}$$

figure 66.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 350 \text{ V} \\ V_{GE} &= -5/15 \text{ V} \\ R_{gon} &= 4 \text{ } \Omega \end{aligned}$$


$$T_j: \begin{aligned} & \text{— } 25 \text{ } ^\circ\text{C} \\ & \text{— } 125 \text{ } ^\circ\text{C} \\ & \text{— } 150 \text{ } ^\circ\text{C} \end{aligned}$$

figure 65.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 350 \text{ V} \\ V_{GE} &= -5/15 \text{ V} \\ I_c &= 75 \text{ A} \end{aligned}$$


$$T_j: \begin{aligned} & \text{— } 25 \text{ } ^\circ\text{C} \\ & \text{— } 125 \text{ } ^\circ\text{C} \\ & \text{— } 150 \text{ } ^\circ\text{C} \end{aligned}$$

figure 67.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$$\begin{aligned} V_{CE} &= 350 \text{ V} \\ V_{GE} &= -5/15 \text{ V} \\ I_c &= 75 \text{ A} \end{aligned}$$

$$T_j: \begin{aligned} & \text{— } 25 \text{ } ^\circ\text{C} \\ & \text{— } 125 \text{ } ^\circ\text{C} \\ & \text{— } 150 \text{ } ^\circ\text{C} \end{aligned}$$




Vincotech

10-FY07HVA075S503-L985F15
datasheet

Boost Switching Characteristics

figure 68. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$

T_j : 25 °C
125 °C
150 °C

figure 70. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$

figure 69. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = -5/15 \text{ V}$
 $I_C = 75 \text{ A}$

T_j : 25 °C
125 °C
150 °C



Vincotech

Switching Definitions

figure 71. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 72. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 73. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 74. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 75.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 76.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





datasheet

Pin table [mm]			
Pin	X	Y	Function
1	52,2	0	G14
2	49,2	0	S14
3	not assembled		
4	26,1	0	Therm2
5	23,1	0	Therm1
6	3	0	S12
7	0	0	G12
8	0	8	DC+
9	0	10,5	DC+
10	0	17,7	DC-1
11	0	20,2	DC-1
12	0	28,2	G11
13	3	28,2	S11
14	10	28,2	G21
15	13	28,2	S21
16	20,35	28,2	Ph2
17	22,85	28,2	Ph2
18	29,35	28,2	Ph1
19	31,85	28,2	Ph1
20	39,2	28,2	S22
21	42,2	28,2	G22
22	49,2	28,2	S13
23	52,2	28,2	G13
24	52,2	20,2	DC-2
25	52,2	17,7	DC-2
26	52,2	10,5	DC+
27	52,2	8	DC+
28	26,1	22,1	A20

Outline


Tolerance of pinpositions: ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech

10-FY07HVA075S503-L985F15
datasheet

Pinout




Identification

ID	Component	Voltage	Current	Function	Comment
T11, T13	IGBT	650 V	75 A	Low Buck Switch	
T12, T14	IGBT	650 V	75 A	High Buck Switch	
D22, D21	FWD	650 V	40 A	Buck Diode	
T21, T22	IGBT	650 V	75 A	Boost Switch	
D12, D14	FWD	650 V	40 A	Low Boost Diode	
D20	FWD	650 V	40 A	High Boost Diode	
Rt	Thermistor			Thermistor	



Vincotech

10-FY07HVA075S503-L985F15
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow</i> 1 packages see vincotech.com website.				
Package data				
Package data for <i>flow</i> 1 packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
10-FY07HVA075S503-L985F15-D1-14	27 Mar. 2026	Initial Release	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.