



Vincotech

80-M3126PB100M703-K817F70

datasheet

MiniSKiiP® PACK 3

1200 V / 100 A

Topology features

- Inverter
- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current
- Switching optimized for EMC

Housing features

- Base isolation: Al_2O_3
- Easy assembly in one mounting step
- Flexible PCB design w/o pin holes
- Rugged solderless spring contacts


Target applications

- Servo Drives


Types

- 80-M3126PB100M703-K817F70

MiniSKiiP® 3 16 mm housing



Schematic





Vincotech

80-M3126PB100M703-K817F70
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	114	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	240	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	9,5	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	81	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	149	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	$^{\circ}\text{C}$
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	$^{\circ}\text{C}$

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	5500	V
Creepage distance		With std lid For more informations see handling instructions	6,3	mm
Clearance		With std lid For more informations see handling instructions	6,3	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

80-M3126PB100M703-K817F70
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,01	25	5,4	6	6,6	V
Collector-emitter saturation voltage	V_{CEsat}		15		100	25 125 150		1,61 1,82 1,91	1,85 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			100	μA
Gate-emitter leakage current	I_{GES}		20	0		25			200	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	0	10		25			21000		pF
Output capacitance	C_{oes}							700		pF
Reverse transfer capacitance	C_{res}							280		pF
Gate charge	Q_g	$V_{CC} = 600$ V	0/15		100	25		700		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)						0,4		K/W
--	---------------	--	--	--	--	--	--	-----	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω	±15	600	100	25 125 150		177,56 176,41 176,65		ns
Rise time	t_r					25 125 150		30,89 35,89 36,76		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		194,99 223,67 229,73		ns
Fall time	t_f					25 125 150		89,83 117,95 132,29		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=8,01$ μC $Q_{tFWD}=12,51$ μC $Q_{tFWD}=13,78$ μC				25 125 150		7,13 9,19 9,86		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		7,66 10,63 11,57		mWs



Vincotech

80-M3126PB100M703-K817F70

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	
Inverter Diode										
Static										
Forward voltage	V_F				100	25 125 150		1,82 1,96 1,97	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			40	µA
Thermal										
Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)						0,64		K/W
Dynamic										
Peak recovery current	I_{RM}	$di/dt=3160$ A/µs $di/dt=3016$ A/µs $di/dt=2912$ A/µs	± 15	600	100	25 125 150		92,97 93,99 94,81		A
Reverse recovery time	t_{rr}					25 125 150		233,75 371,71 405,11		ns
Recovered charge	Q_r					25 125 150		8,01 12,51 13,78		µC
Reverse recovered energy	E_{rec}					25 125 150		2,72 4,6 5,09		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		1232,29 931,37 832,71		A/µs



Vincotech

80-M3126PB100M703-K817F70
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		1		k Ω
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 1670 \Omega$				100	-2		2	%
Maximum Current	I_{max}							3		mA
Power dissipation constant	d					25		0,76		mW/K
A-value	A							$7,635 \times 10^{-3}$		1/K
B-value	B							$1,73 \times 10^{-5}$		1/K ²
Vincotech Thermistor Reference									E	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

80-M3126PB100M703-K817F70

datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$





figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech

80-M3126PB100M703-K817F70

datasheet


Inverter Switch Characteristics

figure 5.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D =$ single pulse
 $T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$

figure 6.

IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 100$ A
 $T_j = 25$ °C



Vincotech

80-M3126PB100M703-K817F70 datasheet

Inverter Diode Characteristics

figure 7. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	0,638 K/W
FWD thermal model values	
R (K/W)	τ (s)
5,39E-02	2,66E+00
1,18E-01	3,25E-01
3,25E-01	4,92E-02
8,49E-02	7,32E-03
5,61E-02	5,21E-04



Vincotech


80-M3126PB100M703-K817F70
datasheet

Thermistor Characteristics

figure 9. Thermistor

Typical PTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

80-M3126PB100M703-K817F70 datasheet


Inverter Switching Characteristics

figure 10.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 12.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 11.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 100 \text{ A}$


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 13.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 100 \text{ A}$

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech


80-M3126PB100M703-K817F70
datasheet

Inverter Switching Characteristics

figure 14.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 15.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A

figure 16.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 17.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

80-M3126PB100M703-K817F70
datasheet


Inverter Switching Characteristics

figure 18.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 20.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 19.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 21.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 100$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

80-M3126PB100M703-K817F70
datasheet

Inverter Switching Characteristics

figure 22. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C

figure 24. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

figure 23. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 100$ A
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C



Vincotech

80-M3126PB100M703-K817F70 datasheet

Inverter Switching Definitions

figure 25. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 26. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 27. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 28. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Inverter Switching Definitions

figure 29.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 30.

FWD


Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





datasheet

Ordering Code	
Version	Ordering Code
With std lid (6.5mm height) + no thermal grease	80-M3126PB100M703-K817F70-/0A/
With thin lid (2.8mm height) + no thermal grease	80-M3126PB100M703-K817F70-/0B/
With std lid (6.5mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M3126PB100M703-K817F70-/1A/
With thin lid (2.8mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M3126PB100M703-K817F70-/1B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M3126PB100M703-K817F70-/4A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M3126PB100M703-K817F70-/4B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M3126PB100M703-K817F70-/5A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M3126PB100M703-K817F70-/5B/

Marking							
	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTIVV		WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver TTTTTIVV	Lot number LLLLL	Serial SSSS	Date code WWYY		

Outline							
Pin table [mm]							
Pin	X	Y	Function	45	-25,9	2,2	S14
1	15,83	-25,3	DC+	46	not assembled		
2	15,83	-6,4	G16	47	not assembled		
3	15,83	-3,2	S16	48	not assembled		
4	not assembled			49	not assembled		
5	not assembled			50	-35,68	22,1	DC-
6	not assembled			51	-35,68	25,3	DC-
7	not assembled			52	-36,58	-25,3	DC+
8	not assembled			53	not assembled		
9	15,83	22,1	DC-	54	-36,58	-15,7	Ph1
10	15,83	25,3	Therm2	55	-36,58	-12,5	Ph1
11	8,13	-25,3	DC+	56	-36,58	-9,3	Ph1
12	not assembled			57	-36,58	-6,1	Ph1
13	8,13	22,1	DC-	58	not assembled		
14	8,13	25,3	Therm1	59	not assembled		
15	1,82	-15,38	Ph3	60	-39,32	22,1	DC-
16	1,82	-12,18	Ph3	61	-39,32	25,3	DC-
17	1,82	-8,98	Ph3	62	-40,22	-25,3	DC+
18	1,82	-5,79	Ph3	63	not assembled		
19	0,43	22,1	S15	64	-40,22	-15,7	Ph1
20	0,43	25,3	G15	65	-40,22	-12,5	Ph1
21	-1,07	-25,3	DC+	66	-40,22	-9,3	Ph1
22	-1,82	-15,38	Ph3	67	-40,22	-6,09	Ph1
23	-1,82	-12,18	Ph3	68	-50,18	-25,3	DC+
24	-1,82	-8,98	Ph3	69	-50,18	-22,1	DC+
25	-1,82	-5,79	Ph3	70	not assembled		
26	not assembled			71	not assembled		
27	-7,27	22,1	DC-	72	not assembled		
28	-7,27	25,3	DC-	73	not assembled		
29	-14,97	22,1	S13	74	not assembled		
30	-14,97	25,3	G13	75	not assembled		
31	-16,05	-15,02	Ph2	76	-50,18	22,1	S11
32	-16,05	-11,82	Ph2	77	-50,18	25,3	G11
33	-16,05	-8,63	Ph2	78	-53,82	-25,3	DC+
34	-16,05	-5,42	Ph2	79	-53,82	-22,1	DC+
35	-19,22	-25,3	DC+	80	not assembled		
36	-19,7	-15,02	Ph2	81	not assembled		
37	-19,7	-11,82	Ph2	82	not assembled		
38	-19,7	-8,62	Ph2	83	not assembled		
39	-19,7	-5,42	Ph2	84	-53,82	3,1	S12
40	not assembled			85	-53,82	6,3	G12
41	not assembled			86	not assembled		
42	-22,67	22,1	DC-	87	not assembled		
43	-22,67	25,3	DC-	88	not assembled		
44	-25,9	-1	G14				


Pad positions refers to center point. For more informations on pad design please see package data



Vincotech

80-M3126PB100M703-K817F70
datasheet

Pinout




Identification

ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	100 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	100 A	Inverter Diode	
Rt	Thermistor			Thermistor	



Vincotech

80-M3126PB100M703-K817F70
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 48	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for MiniSKiiP® 3 packages see vincotech.com website.				
Package data				
Package data for MiniSKiiP® 3 packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,op}=150^{\circ}\text{C}$ and up to 2500VAC/1min isolation voltage. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
80-M3126PB100M703-K817F70-D1-14	9 Dec. 2025		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.