





Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
 target datasheet

<i>flow</i> PHASE 0	1200 V / 100 A
<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><b>Features</b></p> <ul style="list-style-type: none"> <li>High efficiency IGBT4 half-bridge</li> <li>Full current FWD</li> <li>Thermistor</li> </ul> </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><b>Target applications</b></p> <ul style="list-style-type: none"> <li>Industrial Drives</li> <li>Power Supply</li> <li>Solar</li> <li>UPS</li> <li>Welding</li> </ul> </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><b>Types</b></p> <ul style="list-style-type: none"> <li>10-FZ122PB100SC02-M819F08</li> <li>10-F0122PB100SC02-M819F09</li> <li>10-PZ122PB100SC02-M819F08Y</li> </ul> </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><i>flow</i> 0 housing</p>  <p style="display: flex; justify-content: space-around; font-size: small;"> <span>12 mm housing</span> <span>17 mm housing</span> <span>Press-fit pins</span> </p> </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><b>Schematic</b></p>  </div>

## Maximum Ratings

$T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
<b>Half-bridge Switch</b>				
Collector-emitter voltage	$V_{CES}$		1200	V
Collector current	$I_C$	$T_j = T_{jmax}$ $T_s = 80^\circ\text{C}$	90	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{jmax}$	300	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80^\circ\text{C}$	207	W
Gate-emitter voltage	$V_{GES}$		$\pm 20$	V
Short circuit ratings	$t_{SC}$	$T_j \leq 150^\circ\text{C}$	10	$\mu\text{s}$
	$V_{CC}$	$V_{GE} = 15\text{V}$	800	V
Maximum Junction Temperature	$T_{jmax}$		175	$^\circ\text{C}$



Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
target datasheet

Parameter	Symbol	Conditions	Value	Unit
<b>Half-bridge Diode</b>				
Peak Repetitive Reverse Voltage	$V_{RRM}$		1200	V
Continuous (direct) forward current	$I_F$	$T_j = T_{jmax}$ $T_s = 80^\circ\text{C}$	84	A
Repetitive peak forward current	$I_{FRM}$		200	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80^\circ\text{C}$	144	W
Maximum Junction Temperature	$T_{jmax}$		175	$^\circ\text{C}$

## Module Properties

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

### Thermal Properties

Storage temperature	$T_{stg}$		-40...+125	$^\circ\text{C}$
Operation Junction Temperature	$T_{jop}$		-40...+( $T_{jmax} - 25$ )	$^\circ\text{C}$

### Isolation Properties

Isolation voltage	$V_{isol}$	DC voltage	4000	V
Creepage distance			min 12,7	mm
Clearance		for 12 mm housing	9,12	mm
Clearance		for 17 mm housing	min 12,7	mm
Clearance		for Press-fit pins	9,54	mm
Comparative Tracking Index	CTI		>200	



## Characteristic Values

### Half-bridge Switch

Parameter	Symbol	Conditions					Value			Unit
		$V_{GE}$ [V]	$V_{CE}$ [V]	$I_C$ [A]	$T_j$ [°C]	Min	Typ	Max		

#### Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}$			0,0038	25 125	5,1	5,8	6,4	V
Collector-emitter saturation voltage	$V_{CEsat}$		15		100	25 125 150	1,53	1,90	2,1	V
Collector-emitter cut-off current	$I_{CES}$		0	1200		25 125			10	μA
Gate-emitter leakage current	$I_{GES}$		20	0		25 125			120	nA
Internal gate resistance	$r_g$							7,5		Ω
Input capacitance	$C_{ies}$	f=1 MHz	0	25		25		6300		pF
Reverse transfer capacitance	$C_{res}$							270		

#### Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material $\lambda=3,4W/mK$						0,46		K/W
-------------------------------------	---------------	--	--	--	--	--	--	------	--	-----

### Half-bridge Diode

Parameter	Symbol	Conditions					Value			Unit
		$V_r$ [V]	$I_F$ [A]	$T_j$ [°C]	Min	Typ	Max			

#### Static

Forward voltage	$V_F$				100	25 125	1,35	1,83 1,86	2,05	V
Reverse leakage current	$I_r$			1200		25 150			18	μA

#### Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material $\lambda=3,4W/mK$						0,66		K/W
-------------------------------------	---------------	--	--	--	--	--	--	------	--	-----



Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
target datasheet

## Thermistor

Parameter	Symbol	Conditions					Value			Unit
		$V_{GE}$ [V]	$V_{CE}$ [V]	$I_C$ [A]	$T_j$ [°C]	Min	Typ	Max		
Rated resistance	$R$				25		21,5		kΩ	
Deviation of R100	$\Delta_{R/R}$	R100=1486 Ω			100	-4,5		+4,5	%	
Power dissipation	$P$				25		210		mW	
Power dissipation constant					25		3,5		mW/K	
B-value	$B_{(25/50)}$				25		3884		K	
B-value	$B_{(25/100)}$				25		3964		K	
Vincotech NTC Reference								F		



Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
 target datasheet

Ordering Code & Marking							
Version	Ordering Code	in DataMatrix as		in packaging barcode as			
without thermal paste 12mm housing	10-FZ122PB100SC02-M819F08	M819F08		M819F08			
without thermal paste 17mm housing	10-F0122PB100SC02-M819F09	M819F09		M819F09			
NN-NNNNNNNNNNNNNN NNNNNNNN WWYY UL Vinco LLLLL SSSS		<b>Text</b>	<b>Name</b>	<b>Date code</b>	<b>UL &amp; Vinco</b>	<b>Lot</b>	<b>Serial</b>
			NN-NNNNNNNNNNNNNN-NNNNNNNN	WWYY	UL Vinco	LLLLL	SSSS
		<b>Datamatrix</b>	<b>Type&amp;Ver</b>	<b>Lot number</b>	<b>Serial</b>	<b>Date code</b>	
		TTTTTTTV	LLLLL	SSSS	WWYY		

Pin table [mm]				Outline	
Pin	X	Y	Function		
1	0	0	DC-		12 mm housing
2	0	2,3	DC-		
3	0	4,6	DC-		
4	0	6,9	DC-		
5	0	15,6	DC+		
6	0	17,9	DC+		
7	0	20,2	DC+		
8	0	22,5	DC+		
9	13,85	16,45	G12		17 mm housing
10	16,75	16,45	S12		
11	33,5	11,5	Ph		
12	33,5	9,2	Ph		
13	33,5	6,9	Ph		
14	33,5	4,6	Ph		
15	33,5	2,3	Ph		
16	33,5	0	Ph		
17	13,85	13,55	Ph		
18	19,55	4,95	S11		
19	19,55	7,85	G11		
20	33,5	22,5	Therm1		Tolerance of positions: $\pm 0,5$ mm of the end of pins Dimension of coordinate axis is only offset without tolerance
21	26,1	22,5	Therm2		



Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
 target datasheet

Ordering Code & Marking								
Version	Ordering Code	in DataMatrix as		in packaging barcode as				
without thermal paste Press-Fit pins	10-PZ122PB100SC02-M819F08Y	M819F08Y		M819F08Y				
NN-NNNNNNNNNNNNNN NNNNNNNN WWYY UL Vinco LLLLL SSSS		Text	Name		Date code	UL & Vinco	Lot	Serial
			NN-NNNNNNNNNNNNNN-NNNNNNNN		WWYY	UL Vinco	LLLLL	SSSS
		Datamatrix	Type&Ver	Lot number	Serial	Date code		
		TTTTTTTV	LLLLL	SSSS	WWYY			

Pin table [mm]			
Pin	X	Y	Function
1	0	0	DC-
2	0	2,3	DC-
3	0	4,6	DC-
4	0	6,9	DC-
5	0	15,6	DC+
6	0	17,9	DC+
7	0	20,2	DC+
8	0	22,5	DC+
9	13,85	16,45	G12
10	16,75	16,45	S12
11	33,5	11,5	Ph
12	33,5	9,2	Ph
13	33,5	6,9	Ph
14	33,5	4,6	Ph
15	33,5	2,3	Ph
16	33,5	0	Ph
17	13,85	13,55	Ph
18	19,55	4,95	S11
19	19,55	7,85	G11
20	33,5	22,5	Therm1
21	26,1	22,5	Therm2


Tolerance of pinpositions: ±0,5mm at the end of pins  
 Dimension of coordinate axis is only offset without tolerance



Vincotech

**10-FZ122PB100SC02-M819F08**  
**10-F0122PB100SC02-M819F09**  
**10-PZ122PB100SC02-M819F08Y**  
 target datasheet

**Pinout**



**Identification**

ID	Component	Voltage	Current	Function	Comment
T11, T12	IGBT	1200V	100A	Half-bridge Switch	
D11, D12	FWD	1200V	100A	Half-bridge Diode	
Rt	NTC	-	-	Thermistor	



Packaging instruction			
Standard packaging quantity (SPQ)	135	>SPQ	Standard
		<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> 0 packages see vincotech.com website.

Package data
Package data for <i>flow</i> 0 packages see vincotech.com website.

Document No.:	Date:	Modification:	Pages
10-Fx122PB100SC02-M819F0x-T2-14	25 Feb. 2017		

Product status definition		
Datasheet Status	Product Status	Definition
Target	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. The data contained is exclusively intended for technically trained staff.

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.