





| <i>flow</i> IPM 1B-CI | 1200 V / 8 A |
|--|---|
| <div style="background-color: #eee; padding: 2px; margin-bottom: 5px;">Features</div> <p>Power</p> <ul style="list-style-type: none"> • 3 Phase Inverter • 3 Phase Input Rectifier • Open emitter or Emitter Shunt <p>Gate Driver</p> <ul style="list-style-type: none"> • Booststrap circuit • Overcurrent protection • Undervoltage lockout <p>NTC</p> <ul style="list-style-type: none"> • Temperature sensor | <div style="background-color: #eee; padding: 2px; margin-bottom: 5px;">flow 1B 17 mm and 12 mm housing</div> <div style="text-align: center;">  </div> <p style="font-size: small; text-align: center;">with solder pins 17 mm with Press-fit pins 12mm</p> |
| <div style="background-color: #eee; padding: 2px; margin-bottom: 5px;">Target applications</div> <ul style="list-style-type: none"> • Embedded Drives • Industrial Drives | <div style="background-color: #eee; padding: 2px; margin-bottom: 5px;">Schematic</div>  |
| <div style="background-color: #eee; padding: 2px; margin-bottom: 5px;">Types</div> <ul style="list-style-type: none"> • 20-1B12IPA008SC-L239C09 • 20-FB12IPA008SC-L239C08Y | |

Maximum Ratings

$T_j = 25\text{ }^\circ\text{C}$, unless otherwise specified

| Parameter | Symbol | Condition | Value | Unit |
|--|------------|--|-------|----------------------|
| Rectifier Diode | | | | |
| Peak Repetitive Reverse Voltage | V_{RRM} | | 1600 | V |
| Continuous (direct) forward current | I_F | $T_j = T_{jmax}$ $T_s = 80\text{ }^\circ\text{C}$ | 13 | A |
| Surge (non-repetitive) forward current | I_{FSM} | 50 Hz Single Half Sine Wave $t_p = 10\text{ ms}$ $T_j = 45\text{ }^\circ\text{C}$ | 150 | A |
| Surge current capability | I^2t | | 110 | A^2s |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ }^\circ\text{C}$ | 15 | W |
| Maximum Junction Temperature | T_{jmax} | | 150 | $^\circ\text{C}$ |



Vincotech

20-1B12IPA008SC-L239C09
20-FB12IPA008SC-L239C08Y
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Condition | Value | Unit |
|-------------------------------------|------------|--|---------------------------|-------------|
| Inverter Switch | | | | |
| Collector-emitter voltage | V_{CES} | | 1200 | V |
| Collector current | I_C | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 9 | A |
| Repetitive peak collector current | I_{CRM} | t_p limited by T_{jmax} | 24 | A |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 23 | W |
| Gate-emitter voltage | V_{GES} | | ± 20 | V |
| Short circuit ratings | t_{SC} | $T_j \leq 150\text{ °C}$ | 10 | μs |
| | V_{CC} | $V_{GE} = 15\text{ V}$ | 800 | V |
| Maximum Junction Temperature | T_{jmax} | | 175 | $^{\circ}C$ |
| Inverter Diode | | | | |
| Peak Repetitive Reverse Voltage | V_{RRM} | | 1200 | V |
| Continuous (direct) forward current | I_F | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 8 | A |
| Repetitive peak forward current | I_{FRM} | | 15 | A |
| Total power dissipation | P_{tot} | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 12 | W |
| Maximum Junction Temperature | T_{jmax} | | 150 | $^{\circ}C$ |
| Gate Driver | | | | |
| Supply voltage | V_{CC} | | 24 | V |
| Logic input voltage | V_{in} | U-Hin, U-Lin, V-Hin, V-Lin, W-Hin, W-Lin FAULT, RESET | $-0,5 \dots V_{cc} + 0,5$ | V |
| Internal current limit | I_{MAX} | | 5 | A |
| Junction Temperature | T_{jmax} | | 125 | $^{\circ}C$ |



Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

| Parameter | Symbol | Condition | Value | Unit |
|-----------|--------|-----------|-------|------|
|-----------|--------|-----------|-------|------|

Inverter Shunt

| | | | | |
|--------------------|-----------|--|------|---|
| DC forward current | I_F | | 9 | A |
| Power dissipation | P_{tot} | | 2,43 | W |

Module Properties

Thermal Properties

| | | | | |
|---|-----------|--|---------------------------|----|
| Storage temperature | T_{stg} | | -40...+125 | °C |
| Operation temperature under switching condition | T_{jop} | | -40...($T_{jmax} - 25$) | °C |

Isolation Properties

| | | | | |
|----------------------------|------------|------------------------------------|-------------------|----|
| Isolation voltage | V_{isol} | DC Test Voltage $t_p = 2\text{ s}$ | 4000 | V |
| Creepage distance | | | min. 12,7 | mm |
| Clearance | | Press-fit pins / solder pins | min. 12,7 / 12,69 | mm |
| Comparative Tracking Index | CTI | | > 200 | |



Characteristic Values

| Parameter | Symbol | Conditions | | | | | Value | | | Unit |
|-----------|--------|--------------|--------------|--------------|-----------|------------|-------|-----|-----|------|
| | | V_{GS} [V] | V_{GE} [V] | V_{DS} [V] | I_D [A] | T_j [°C] | Min | Typ | Max | |

Rectifier Diode

Static

| | | | | | | | | | | |
|-------------------------|-------|--|--|------|---|-----------|--|--------------|------|----|
| Forward voltage | V_F | | | | 7 | 25 125 | | 1,04 0,97 | 1,11 | V |
| Reverse leakage current | I_r | | | 1600 | | 25 | | | 10 | μA |

Thermal

| | | | | | | | | | | |
|-------------------------------------|---------------|---|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink | $R_{th(j-s)}$ | phase-change material $\lambda = 3,4$ W/mK | | | | | | 4,56 | | K/W |
|-------------------------------------|---------------|---|--|--|--|--|--|------|--|-----|

Inverter Switch

Static

| | | | | | | | | | | | |
|--------------------------------------|--------------|-------------------|----|------|---------|-----------|--|------|--------------|------|----|
| Gate-emitter threshold voltage | $V_{GE(th)}$ | $V_{GE} = V_{CE}$ | | | 0,00015 | 25 | | 5,3 | 5,8 | 6,3 | V |
| Collector-emitter saturation voltage | V_{CEsat} | | 15 | | 8 | 25 150 | | 1,58 | 1,85 2,25 | 2,07 | V |
| Collector-emitter cut-off current | I_{CES} | | 0 | 1200 | | 25 | | | | 1 | μA |
| Gate-emitter leakage current | I_{GES} | | 20 | 0 | | 25 | | | | 120 | nA |
| Internal gate resistance | r_g | | | | | | | | none | | Ω |
| Input capacitance | C_{ies} | | | | | | | | 490 | | pF |
| Reverse transfer capacitance | C_{res} | $f = 1$ MHz | 0 | 25 | | 25 | | | 30 | | |

Thermal

| | | | | | | | | | | | |
|-------------------------------------|---------------|---|--|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink | $R_{th(j-s)}$ | phase-change material $\lambda = 3,4$ W/mK | | | | | | | 4,22 | | K/W |
|-------------------------------------|---------------|---|--|--|--|--|--|--|------|--|-----|

Dynamic

| | | | | | | | | | | | |
|-----------------------------|--------------|----------------------|-----|---|-----|------|--|-------|------|-----|--|
| Turn-on delay time* | $t_{d(on)}$ | $V_{CC} = 15$ V | 600 | 8 | 25 | | | 1484 | | ns | |
| | | | | | 125 | | | | 1909 | | |
| Rise time | t_r | | | | 25 | | | | 12 | | |
| | | | | | 125 | | | | 16 | | |
| Turn-off delay time* | $t_{d(off)}$ | | | | 25 | | | | 1436 | | |
| | | 125 | | | | 1916 | | | | | |
| Fall time | t_f | 25 | | | | 77 | | | | | |
| | | 125 | | | | 136 | | | | | |
| Turn-on energy (per pulse) | E_{on} | $Q_{t-FWD} = 1$ μC | | | | 25 | | 0,399 | | mWs | |
| | | $Q_{t-FWD} = 1,7$ μC | | | | 125 | | 0,630 | | | |
| Turn-off energy (per pulse) | E_{off} | | | | | 25 | | 0,520 | | | |
| | | | | | | 125 | | 0,844 | | | |

* times include gate driver deadtime



Characteristic Values

| Parameter | Symbol | Conditions | | | | | Value | | | Unit |
|-----------|--------|--------------|--------------|-----------|------------|-----|-------|-----|--|------|
| | | V_{GE} [V] | V_{CE} [V] | I_C [A] | T_j [°C] | Min | Typ | Max | | |

Inverter Diode

Static

| Parameter | Symbol | V_{GS} [V] | V_{DS} [V] | I_D [A] | T_j [°C] | Min | Typ | Max | Unit |
|-------------------------|--------|--------------|--------------|-----------|------------|-----|--------------|-----|------|
| Forward voltage | V_F | | | 7,5 | 25 125 | | 1,65 1,61 | | V |
| Reverse leakage current | I_r | | 1200 | | 25 | | | 250 | μA |

Thermal

| Parameter | Symbol | Conditions | Value | Unit |
|-------------------------------------|---------------|---|-------|------|
| Thermal resistance junction to sink | $R_{th(j-s)}$ | phase-change material $\lambda = 3,4$ W/mK | 5,69 | K/W |

Dynamic

| Parameter | Symbol | V_{GS} [V] | V_{DS} [V] | I_D [A] | T_j [°C] | Min | Typ | Max | Unit |
|---------------------------------------|----------------------|--------------|--------------|-----------|------------|-----|----------------|-----|------|
| Peak recovery current | I_{RRM} | | | | 25 125 | | 8 8 | | A |
| Reverse recovery time | t_{rr} | | | | 25 125 | | 320 514 | | ns |
| Recovered charge | Q_r | | | | 25 125 | | 0,975 1,748 | | μC |
| Reverse recovered energy | E_{rec} | | | | 25 125 | | 0,433 0,785 | | mWs |
| Peak rate of fall of recovery current | $(di_{rf}/dt)_{max}$ | | | | 25 125 | | 56 37 | | A/μs |

Inverter Shunt

| Parameter | Symbol | Value | Unit |
|------------|--------|-------|------|
| Resistance | R | 30 | mΩ |



Characteristic Values

| Parameter | Symbol | Conditions | | | | | Value | | | Unit |
|-----------|--------|--------------|--------------|-----------|------------|-----|-------|-----|--|------|
| | | V_{GE} [V] | V_{CE} [V] | I_C [A] | T_j [°C] | Min | Typ | Max | | |

Gate Driver

Static

| | | | | | | | | | |
|--|--------------------|--|--|--|--|------|------|------|---------------|
| Recommended supply voltage | V_{CC} | | | | | 13,5 | 15 | 20 | V |
| Power on reset trip voltage | V_{POR} | | | | | 4 | 5,5 | 7,5 | V |
| Internal current limit | I_{MAX} | | | | | 13,3 | 16,7 | 20 | A |
| Quiescent supply current | I_q | | | | | | 3 | 4,5 | mA |
| Logic "1" input voltage | V_{inH} | U-Hin, U-Lin, V-Hin, V-Lin, W-Hin, W-Lin, RESET | | | | 2,2 | 3 | 4 | V |
| Logic "0" input voltage | V_{inL} | | | | | 0,6 | 1,5 | 2,1 | V |
| Logic "1" input current | I_{inH} | $V_{in} = 5\text{ V}$ | | | | 0,6 | 1 | 1,4 | mA |
| Logic "0" input current | I_{inL} | $V_{in} = 0\text{ V}$ | | | | 0 | 0 | 0,01 | mA |
| Input signal filter time | t_{Filt} | U-Hin, U-Lin, V-Hin, V-Lin, W-Hin, W-Lin, FAULT(in), RESET(pulse) | | | | 80 | 200 | 500 | ns |
| Logic "1" FAULT output* | $V_{outFAULTH}$ | $I_{FAULT} = 1\text{ mA}$ | | | | | | 0,95 | V |
| Logic "1" FAULT input threshold voltage* | $V_{inFAULTH}$ | | | | | 0,6 | 1,5 | 2,1 | V |
| Logic "0" FAULT input threshold voltage* | $V_{inFAULTL}$ | | | | | 2,2 | 3 | 4 | V |
| Under voltage reset voltage | $V_{UVreset}$ | | | | | 10 | 10,8 | 11,6 | V |
| Under voltage trip voltage | V_{UVtrip} | | | | | 10,5 | 11,3 | 12,1 | V |
| Under voltage hysteresis voltage | $V_{UVhysteresis}$ | | | | | 0,2 | 0,5 | 0,8 | V |
| Under voltage filter time | t_{UVfilt} | | | | | 4 | 8 | 16 | μs |
| Internal dead time | $t_{UV\bar{it}}$ | Delay matching, high side turn-on and low side turn off | | | | -100 | 80 | 300 | ns |
| Internal dead time | t_{UVit} | Delay matching, high side turn-on and low side turn off | | | | -20 | 180 | 400 | ns |

*FAULT pin is inverse logic with open drain output
 for more information see Mitsubishi's M81738FP preliminary (Jan 2012) datasheet



Vincotech

20-1B12IPA008SC-L239C09
20-FB12IPA008SC-L239C08Y
 datasheet

Characteristic Values

| Parameter | Symbol | Conditions | | | | | Value | | | Unit |
|-----------|--------|------------------------------|---|-------------------------------------|------------|-----|-------|-----|--|------|
| | | V_{GE} [V] V_{GS} [V] | V_{CE} [V] V_{DS} [V] V_F [V] | I_C [A] I_D [A] I_F [A] | T_j [°C] | Min | Typ | Max | | |

Thermistor

| | | | | | | | | | |
|----------------------------|----------------|-------------------------|--|--|-----|-----|------|-----|------|
| Rated resistance | R | | | | 25 | | 22 | | kΩ |
| Deviation of R_{100} | $\Delta_{R/R}$ | $R_{100} = 1486 \Omega$ | | | 100 | -12 | | +14 | % |
| Power dissipation | P | | | | 25 | | 200 | | mW |
| Power dissipation constant | | | | | 25 | | 2 | | mW/K |
| B-value | $B_{(25/50)}$ | Tol. $\pm 3\%$ | | | 25 | | 3950 | | K |
| B-value | $B_{(25/100)}$ | Tol. $\pm 3\%$ | | | 25 | | 3998 | | K |
| Vincotech NTC Reference | | | | | | | | B | |



Rectifier Diode Characteristics

figure 1. Rectifier Diode
Typical forward characteristics





figure 2. Rectifier Diode
Transient thermal impedance as a function of pulse width



Diode thermal model values

| R (K/W) | τ (s) |
|------------|------------|
| 1,1300E-01 | 8,9590E+00 |
| 2,5930E-01 | 8,4330E-01 |
| 1,9540E+00 | 1,0960E-01 |
| 1,7280E+00 | 3,6370E-02 |
| 5,0510E-01 | 3,4450E-03 |




Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$I_C = f(V_{CE})$




$t_p = 250 \mu s$ $T_j: 25 \text{ }^\circ C$ $\dots\dots\dots$
 $V_{GE} = 15 \text{ V}$ $T_j: 150 \text{ }^\circ C$ $-\cdot-\cdot-\cdot-$

figure 2. IGBT

Typical output characteristics

$I_C = f(V_{CE})$




$t_p = 250 \mu s$
 $T_j = 150 \text{ }^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$I_C = f(V_{GE})$




$t_p = 100 \mu s$ $T_j: 25 \text{ }^\circ C$ $\dots\dots\dots$
 $V_{CE} = 10 \text{ V}$ $T_j: 150 \text{ }^\circ C$ $-\cdot-\cdot-\cdot-$

figure 4. IGBT

Transient Thermal Impedance as function of Pulse duration

$Z_{th(j-s)} = f(t_p)$



$D = t_p / T$
 $R_{th(j-s)} = 4,22 \text{ K/W}$
 IGBT thermal model values

| $R \text{ (K/W)}$ | $\tau \text{ (s)}$ |
|-------------------|--------------------|
| 2,57E+00 | 6,96E-02 |
| 7,15E-01 | 1,68E-02 |
| 5,14E-01 | 3,47E-03 |
| 9,91E-02 | 7,30E-04 |




Inverter Diode Characteristics

figure 1. FWD

Typical forward characteristics

$I_F = f(V_F)$




$t_p = 250 \mu s$ $T_j: 25 \text{ }^\circ C$
 $125 \text{ }^\circ C$ ————

figure 2. FWD

Transient thermal impedance as a function of pulse width

$Z_{th(j-s)} = f(t_p)$



$D = t_p / T$
 $R_{th(j-s)} = 5,69 \text{ K/W}$

FWD thermal model values


| $R \text{ (K/W)}$ | $\tau \text{ (s)}$ |
|-------------------|--------------------|
| 1,733E-01 | 2,116E+00 |
| 1,301E+00 | 1,400E-01 |
| 2,883E+00 | 4,111E-02 |
| 9,535E-01 | 5,372E-03 |
| 3,778E-01 | 1,029E-03 |

Thermistor Characteristics

figure 1. Thermistor

Typical NTC characteristic as a function of temperature

$R = f(T)$






Inverter Switching Characteristics

figure 1. IGBT


Typical switching energy losses as a function of collector current



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{CC} = 15 \text{ V}$
 $V_{IN} = 5 \text{ V}$
 $T_j = 25 \text{ }^\circ\text{C}$ (dotted blue line)
 $T_j = 125 \text{ }^\circ\text{C}$ (solid black line)

figure 2. FWD


Typical reverse recovered energy loss as a function of collector current



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{CC} = 15 \text{ V}$
 $V_{IN} = 5 \text{ V}$
 $T_j = 25 \text{ }^\circ\text{C}$ (dotted blue line)
 $T_j = 125 \text{ }^\circ\text{C}$ (solid black line)

figure 3. IGBT


Typical switching times as a function of collector current



With an inductive load at
 $T_j = 125 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{CC} = 15 \text{ V}$
 $V_{IN} = 5 \text{ V}$

figure 4. FWD

Typical reverse recovery time as a function of collector current



At
 $V_{CE} = 600 \text{ V}$
 $V_{CC} = 15 \text{ V}$
 $V_{IN} = 5 \text{ V}$
 $I_C = 8 \text{ A}$
 $T_j = 25 \text{ }^\circ\text{C}$ (dotted blue line)
 $T_j = 125 \text{ }^\circ\text{C}$ (solid black line)




Inverter Switching Characteristics

figure 5. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




At $V_{CE} = 600$ V $T_j = 25$ °C
 $V_{CC} = 15$ V $T_j = 125$ °C ———
 $V_{IN} = 5$ V

figure 6. FWD

Typical peak reverse recovery current current as a function of collector current

$$I_{RM} = f(I_c)$$




At $V_{CE} = 600$ V $T_j = 25$ °C
 $V_{CC} = 15$ V $T_j = 125$ °C ———
 $V_{IN} = 5$ V
 $V_{GE} = 15$ V
 $I_c = 8$ A

figure 7. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current


$$di_f/dt, di_{rr}/dt = f(I_c)$$



At $V_{CE} = 600$ V $T_j = 25$ °C
 $V_{CC} = 15$ V $T_j = 125$ °C ———
 $V_{IN} = 5$ V

figure 8. IGBT

Reverse bias safe operating area



At $T_j = 175$ °C



Vincotech


Inverter Switching Characteristics

General conditions

| | | |
|----------|---|--------|
| T_j | = | 125 °C |
| V_{CC} | = | 15 V |

Figure 1. IGBT


Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})



| | | |
|-------------------|-------|---------|
| $V_{IN}(0\%) =$ | 0 | V |
| $V_{IN}(100\%) =$ | 15 | V |
| $V_C(100\%) =$ | 600 | V |
| $I_C(100\%) =$ | 8 | A |
| $t_{doff} =$ | 1,916 | μ s |
| $t_{Eoff} =$ | 2,308 | μ s |

Figure 2. IGBT


Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})



| | | |
|-------------------|-------|---------|
| $V_{IN}(0\%) =$ | 0 | V |
| $V_{IN}(100\%) =$ | 15 | V |
| $V_C(100\%) =$ | 600 | V |
| $I_C(100\%) =$ | 8 | A |
| $t_{don} =$ | 1,909 | μ s |
| $t_{Eon} =$ | 2,116 | μ s |

Figure 3. IGBT


Turn-off Switching Waveforms & definition of t_f



| | | |
|----------------|-------|---------|
| $V_C(100\%) =$ | 600 | V |
| $I_C(100\%) =$ | 8 | A |
| $t_f =$ | 0,136 | μ s |

Figure 4. IGBT

Turn-on Switching Waveforms & definition of t_r




| | | |
|----------------|-------|---------|
| $V_C(100\%) =$ | 600 | V |
| $I_C(100\%) =$ | 8 | A |
| $t_r =$ | 0,016 | μ s |



Vincotech


Inverter Switching Characteristics

Figure 5. IGBT




$P_{off}(100\%) = 4,85$ kW
 $E_{off}(100\%) = 0,84$ mJ
 $t_{Eoff} = 2,31$ μs

Figure 6. IGBT



$P_{on}(100\%) = 4,85$ kW
 $E_{on}(100\%) = 0,63$ mJ
 $t_{Eon} = 2,12$ μs

Figure 7. FWD




$V_d(100\%) = 600$ V
 $I_d(100\%) = 8$ A
 $I_{RRM}(100\%) = -8$ A
 $t_{rr} = 0,514$ μs




Inverter Switching Characteristics

Figure 8. FWD



| | | |
|-------------------|------|---------------|
| I_d (100%) = | 8 | A |
| Q_{rr} (100%) = | 1,75 | μC |
| t_{Qrr} = | 1,13 | μs |

Figure 9. FWD



| | | |
|--------------------|------|---------------|
| P_{rec} (100%) = | 4,85 | kW |
| E_{rec} (100%) = | 0,79 | mJ |
| t_{Erec} = | 1,13 | μs |



Vincotech

20-1B12IPA008SC-L239C09
20-FB12IPA008SC-L239C08Y
 datasheet


| Ordering Code & Marking | | | | | | |
|---|------------|--|--|---------------------------------|-------------------------|---------------|
| Version | | | Ordering Code | | | |
| without thermal paste 17 mm housing with solder pins | | | 20-1B12IPA008SC-L239C09 | | | |
| without thermal paste 12 mm housing with press-fit pins | | | 20-FB12IPA008SC-L239C08Y | | | |
| with thermal paste 17 mm housing with solder pins | | | 20-1B12IPA008SC-L239C09-/3/ | | | |
| with thermal paste 12 mm housing with press-fit pins | | | 20-FB12IPA008SC-L239C08Y-/3/ | | | |
| | Text | Name | Date code | UL & VIN | Lot | Serial |
| | | NN-NNNNNNNNNNNNNN TTTTTVV WWYY UL VIN LLLLL SSSS | NN-NNNNNNNNNNNNNN-TTTTTVV WWYY UL VIN LLLLL SSSS | WWYY UL VIN LLLLL SSSS | UL VIN LLLLL SSSS | LLLLL SSSS |
| | Datamatrix | Type&Ver | Lot number | Serial | Date code | |
| | | TTTTTTVV | LLLLL | SSSS | WWYY | |

| Pin table [mm] | | | | Outline | |
|----------------|------|------|----------|--|--|
| Pin | X | Y | Function | | |
| 1 | 45,1 | 0 | WH | 17 mm Solder pin | |
| 2 | 42,4 | 0 | WL | | |
| 3 | 39,7 | 0 | RW+ | | |
| 4 | 37 | 0 | RW- | | |
| 5 | 34,3 | 0 | GND | | |
| 6 | 31,6 | 0 | VCC | | |
| 7 | 28,9 | 0 | VH | | |
| 8 | 26,2 | 0 | VL | | |
| 9 | 23,5 | 0 | RV+ | | |
| 10 | 20,8 | 0 | RV- | | |
| 11 | 18,1 | 0 | UH | | |
| 12 | 15,4 | 0 | UL | | |
| 13 | 12,7 | 0 | RU+ | | |
| 14 | 10 | 0 | RU- | | |
| 15 | 7,3 | 0 | RST | | |
| 16 | 4,6 | 0 | FO | | |
| 17 | 1,9 | 0 | NTC | | |
| 18 | 0 | 8,8 | L3 | 12 mm Press-fit | |
| 19 | 0 | 17,8 | L2 | | |
| 20 | 3,8 | 26,1 | L1 | | |
| 21 | 7,8 | 13,3 | EU | | |
| 22 | 9 | 18,7 | DC1- | | |
| 23 | 14,2 | 26,1 | DC1+ | | |
| 24 | 20,6 | 17,8 | EV | | |
| 25 | 24,7 | 26,1 | U | | |
| 26 | 28,7 | 21,6 | DC2+ | | |
| 27 | 36,2 | 16,7 | EW | | |
| 28 | 37,5 | 26,1 | V | | |
| 29 | 45,1 | 21,9 | W | | |
| | | | | <p>Tolerance of pinpositions: ±0.5mm at the end of pins Dimension of coordinate axis is only offset without tolerance</p> | |

| Pin Descriptions | | | Power pin descriptions | | |
|------------------|----------|---|------------------------|----------|----------------------|
| Pin | Function | Description | Pin | Function | Description |
| 1 | W-HIN | Signal input for high-side W phase | 18 | L3 | Rectifier input L3 |
| 2 | W-LIN | Signal input for low-side W phase | 19 | L2 | Rectifier input L2 |
| 3 | RW+ | W phase shunt + | 20 | L1 | Rectifier input L1 |
| 4 | RW- | W phase shunt - | 21 | EU | Open emitter U phase |
| 5 | GND | Signal ground | 22 | DC1- | Rectifier output DC- |
| 6 | VCC | Driver circuit supply voltage | 23 | DC1+ | Rectifier output DC+ |
| 7 | V-HIN | Signal input for high-side V phase | 24 | EV | Open emitter V phase |
| 8 | V-LIN | Signal input for low-side V phase | 25 | U | Output U phase |
| 9 | RV+ | V phase shunt + | 26 | DC2+ | Inverter input DC+ |
| 10 | RV- | V phase shunt - | 27 | EW | Open emitter W phase |
| 11 | U-HIN | Signal input for high-side U phase | 28 | V | Output V phase |
| 12 | U-LIN | Signal input for low-side U phase | 29 | W | Output W phase |
| 13 | RU+ | U phase shunt + | | | |
| 14 | RU- | U phase shunt - | | | |
| 15 | RESET | Fault latch reset (min. 500ns pulse) | | | |
| 16 | ~FAULT | Fault latch input/output (negative logic, open drain) | | | |
| 17 | NTC | Temperature sensor connector | | | |



Vincotech




| Identification | | | | | |
|----------------|------------|---------|---------|-----------------|---------|
| ID | Component | Voltage | Current | Function | Comment |
| D7-D12 | FWD | 1600 V | 12 A | Rectifier Diode | |
| T1-T6 | IGBT | 1200 V | 8 A | Inverter Switch | |
| D1-D6 | FWD | 1200 V | 7,5 A | Inverter Diode | |
| R1-R3 | Resistor | | | Inverter Shunt | |
| NTC | Thermistor | | | Thermistor | |



| Packaging instruction | | | |
|---------------------------------------|------|----------|-------------|
| Standard packaging quantity (SPQ) 100 | >SPQ | Standard | <SPQ Sample |

| Handling instruction |
|--|
| Handling instructions for <i>flow</i> 1B packages see vincotech.com website. |

| Package data |
|---|
| Package data for <i>flow</i> 1B packages see vincotech.com website. |

| UL recognition and file number |
|---|
| This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.  |

| Document No.: | Date: | Modification: | Pages |
|--------------------------------|--------------|---------------|-------|
| 20-xB12IPA008SC-L239C0xx-D1-14 | 11 Feb. 2017 | | |

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.