



**fastPACK E2 SiC**

**2300 V / 10 mΩ**

**Topology features**

- Kelvin Emitter for improved switching performance
- Open Emitter configuration
- Temperature sensor

**Component features**

- Fast intrinsic diode with low reverse recovery
- High blocking voltage with low on-resistance
- High speed switching with low capacitance

**Housing features**

- Base isolation: AlN
- Convex shaped substrate for superior thermal contact
- Compact housing
- CTI600 housing material
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection

**Target applications**

- Charging Stations
- Power Supply
- Solar Inverters
- UPS


**Types**

- 10-EY234PB010ME01-PR39F08T

**flow E2 12 mm housing**



**Schematic**





Vincotech

10-EY234PB010ME01-PR39F08T  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>Inverter Switch</b>				
Drain-source voltage	$V_{DS}$		2300	V
Drain current (DC current)	$I_D$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	115	A
Peak drain current	$I_{DM}$	$t_p$ limited by $T_{jmax}$	498	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	384	W
Gate-source voltage	$V_{GS}$	static	-4 / 15	V
		dynamic	-8 / 19	V
Maximum Junction Temperature	$T_{jmax}$		175	°C

## Module Properties

### Thermal Properties

Storage temperature	$T_{stg}$		-40...+125	°C
Operation temperature under switching condition	$T_{jop}$		-40...+( $T_{jmax} - 25$ )	°C

### Isolation Properties

Isolation voltage	$V_{isol}$	DC Test Voltage* $t_p = 2\text{ s}$	6800	V
Creepage distance			>12,7	mm
Clearance			9,28	mm
Comparative Tracking Index	CTI		≥ 600	

\*100 % tested in production



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		

#### Inverter Switch

##### Static

Drain-source on-state resistance	$r_{DS(on)}$		15		207	25 125 150		11,7 23,2 27,6	13 <sup>(1)</sup>	mΩ
Gate-source threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$			0,057	25	1,8	2,5	3,6	V
Gate to Source Leakage Current	$I_{GSS}$		15	0		25		30	300	nA
Zero Gate Voltage Drain Current	$I_{DSS}$		0	2300		25		3	30	μA
Internal gate resistance	$r_g$							3,33		Ω
Gate charge	$Q_g$		-4/15	1500	207	25		441		nC
Short-circuit input capacitance	$C_{iss}$	$f = 100$ kHz	0	1500	0	25		18000		pF
Short-circuit output capacitance	$C_{oss}$						306			
Reverse transfer capacitance	$C_{rss}$						30			
Diode forward voltage	$V_{SD}$		0		105	25		5,5		V

##### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,25		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----



Vincotech

10-EY234PB010ME01-PR39F08T  
datasheet

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		
<b>Dynamic</b>										
Turn-on delay time	$t_{d(on)}$					25 125 150		42,03 38,86 38,68		ns
Rise time	$t_r$	$R_{gon} = 1 \Omega$ $R_{goff} = 1 \Omega$				25 125 150		50,31 48,34 47,9		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		163,4 183,85 189,96		ns
Fall time	$t_f$					25 125 150		20,87 27,48 29,11		ns
Turn-on energy (per pulse)	$E_{on}$	$Q_{rFWD}=0,943 \mu C$ $Q_{rFWD}=3,44 \mu C$ $Q_{rFWD}=5,48 \mu C$				25 125 150		14,69 16,61 18,66		mWs
Turn-off energy (per pulse)	$E_{off}$		-4/15	1200	210	25 125 150		8,38 9,67 10,07		mWs
Peak recovery current	$I_{RRM}$					25 125 150		42,22 80,6 106,03		A
Reverse recovery time	$t_{rr}$					25 125 150		48,72 72,11 83,37		ns
Recovered charge	$Q_r$	$di/dt=4336 A/\mu s$ $di/dt=3477 A/\mu s$ $di/dt=3631 A/\mu s$				25 125 150		0,943 3,44 5,48		$\mu C$
Reverse recovered energy	$E_{rec}$					25 125 150		0,438 2,6 4,22		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		4666,77 4137,12 5735,85		A/ $\mu s$



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GS}$ [V]	$V_{GE}$ [V]	$V_{DS}$ [V]	$V_{CE}$ [V]	$T_j$ [°C]	Min	Typ	Max	

### Thermistor

#### Static

Rated resistance	$R$					25		5		k $\Omega$
Deviation of R100	$A_{R/R}$	$R_{100} = 499 \Omega$				100	3,2		3,3	%
Power dissipation	$P$					25		130		mW
Power dissipation constant	$d$					25		1,3		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3380		K
Vincotech Thermistor Reference									V	

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.




## Inverter Switch Characteristics

figure 1. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




$t_p = 250 \mu s$   
 $V_{GS} = 15 V$   
 $T_j:$  25 °C (blue), 125 °C (black), 150 °C (red)

figure 2. MOSFET

Typical output characteristics

$$I_D = f(V_{DS})$$




$t_p = 250 \mu s$   
 $T_j = 150 \text{ } ^\circ C$   
 $V_{GS}$  from -4 V to 15 V in steps of 2 V

figure 3. MOSFET

Typical transfer characteristics

$$I_D = f(V_{GS})$$




$t_p = 250 \mu s$   
 $V_{DS} = 10 V$   
 $T_j:$  25 °C (blue), 125 °C (black), 150 °C (red)

figure 4. MOSFET

Typical reverse drain current characteristics

$$I_{SD} = f(V_{SD})$$



$t_p = 250 \mu s$   
 $V_{GS} = 15 V$   
 $T_j:$  25 °C (blue), 125 °C (black), 150 °C (red)




## Inverter Switch Characteristics

figure 5. MOSFET

Transient thermal impedance as a function of pulse width

$$Z_{th(j-c)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-c)} = 0,248 \text{ K/W}$


MOSFET thermal model values

R (K/W)	$\tau$ (s)
1,15E-02	8,20E+00
5,13E-02	1,34E+00
1,17E-01	9,67E-02
5,09E-02	8,78E-03
1,98E-02	1,16E-03

figure 6. MOSFET

Gate voltage vs gate charge

$$V_{GS} = f(Q_g)$$



$I_b = 150 \text{ A}$	$T_j = 25 \text{ }^\circ\text{C}$
-----------------------	-----------------------------------




## Thermistor Characteristics

figure 7. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






## Inverter Switching Characteristics

figure 8. MOSFET

Typical switching energy losses as a function of drain current  
 $E = f(I_D)$




With an inductive load at  
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $R_{gon} = 1 \ \Omega$   
 $R_{goff} = 1 \ \Omega$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

figure 9. MOSFET

Typical switching energy losses as a function of MOSFET turn on gate resistor  
 $E = f(R_g)$




With an inductive load at  
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $I_D = 210 \text{ A}$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

figure 10. MOSFET

Typical reverse recovered energy loss as a function of drain current  
 $E_{rec} = f(I_D)$




With an inductive load at  
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $R_{gon} = 1 \ \Omega$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

figure 11. MOSFET

Typical reverse recovered energy loss as a function of MOSFET turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at  
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $I_D = 210 \text{ A}$


$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C



## Inverter Switching Characteristics

**figure 12.** MOSFET


Typical switching times as a function of drain current  
 $t = f(I_D)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $R_{gon} = 1 \text{ } \Omega$   
 $R_{goff} = 1 \text{ } \Omega$

**figure 13.** MOSFET


Typical switching times as a function of MOSFET turn on gate resistor  
 $t = f(R_g)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $I_D = 210 \text{ A}$

**figure 14.** MOSFET


Typical reverse recovery time as a function of drain current  
 $t_{rr} = f(I_D)$



At  $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $R_{gon} = 1 \text{ } \Omega$   
 $T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 15.** MOSFET

Typical reverse recovery time as a function of MOSFET turn on gate resistor  
 $t_{rr} = f(R_{gon})$



At  $V_{DS} = 1200 \text{ V}$   
 $V_{GS} = -4/15 \text{ V}$   
 $I_D = 210 \text{ A}$   
 $T_j$ : — 25 °C  
— 125 °C  
— 150 °C




## Inverter Switching Characteristics

**figure 16.** MOSFET

Typical recovered charge as a function of drain current

$$Q_r = f(I_D)$$




At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 1$   $\Omega$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

**figure 17.** MOSFET

Typical recovered charge as a function of MOSFET turn on gate resistor

$$Q_r = f(R_{gon})$$




At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 210$  A

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

**figure 18.** MOSFET

Typical peak reverse recovery current as a function of drain current

$$I_{RM} = f(I_D)$$




At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $R_{gon} = 1$   $\Omega$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

**figure 19.** MOSFET

Typical peak reverse recovery current as a function of MOSFET turn on gate resistor

$$I_{RM} = f(R_{gon})$$



At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 210$  A


$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C



## Inverter Switching Characteristics

**figure 20.** MOSFET

Typical rate of fall of forward and reverse recovery current as a function of drain current  
 $di_f/dt, di_{rr}/dt = f(I_D)$




At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $R_{g(on)} = 1$  Ω

$T_j$ : 25 °C (blue)  
 125 °C (black)  
 150 °C (red)

**figure 21.** MOSFET

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_{rr}/dt = f(R_{g(on)})$




At  $V_{DS} = 1200$  V  
 $V_{GS} = -4/15$  V  
 $I_D = 210$  A

$T_j$ : 25 °C (blue)  
 125 °C (black)  
 150 °C (red)

**figure 22.** MOSFET

Reverse bias safe operating area

$I_D = f(V_{DS})$




At  $T_j = 150$  °C  
 $R_{g(on)} = 1$  Ω  
 $R_{g(off)} = 1$  Ω



## Inverter Switching Definitions


**figure 23.** MOSFET

Turn-off Switching Waveforms & definition of  $t_{doff}$   $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




**figure 24.** MOSFET

Turn-on Switching Waveforms & definition of  $t_{don}$   $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




**figure 25.** MOSFET

Turn-off Switching Waveforms & definition of  $t_f$



**figure 26.** MOSFET

Turn-on Switching Waveforms & definition of  $t_r$





### Inverter Switching Definitions

figure 27. FWD

Turn-off Switching Waveforms & definition of  $t_{tr}$




figure 28. FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )





figure 29. FWD


Turn-on Switching Waveforms & definition of  $t_{Erec}$  ( $t_{Erec}$  = integrating time for  $E_{rec}$ )







Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14	MOSFET	2300 V	10 mΩ	Inverter Switch	
Rt	Thermistor			Thermistor	



Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> E2 packages see vincotech.com website.

Package data
Package data for <i>flow</i> E2 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,op}=175^{\circ}\text{C}$ and up to 4000VAC/1min isolation voltage. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
10-EY234PB010ME01-PR39F08T-D1-14	5 Jun. 2025	Initial Release	
10-EY234PB010ME01-PR39F08T-D2-14	15 Aug. 2025	Add low current measurements to Dynamic Characteristics	

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.