



<i>flowPACK E2</i>	1200 V / 50 A
<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Features</p> <ul style="list-style-type: none"> IGBT M7 with low V_{CEsat} and improved EMC behavior Standard industrial housing Optimized $R_{th(j-s)}$ with Phase Change Material Built-in NTC </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Target applications</p> <ul style="list-style-type: none"> Industrial Drives </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Types</p> <ul style="list-style-type: none"> 10-EY126PA050M7-L196F78T 10-E2126PA050M7-L196F78Z </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><i>flow E2 12 mm housing</i></p> <div style="display: flex; justify-content: space-around; align-items: center;"> </div> <div style="display: flex; justify-content: space-around; margin-top: 5px;"> Press-fit pin Solder pin </div> </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Schematic</p> </div>

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C		50	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	124	W
Gate-emitter voltage	V_{GES}		±20	V
Maximum junction temperature	T_{jmax}		175	°C



Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	49	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	87	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance			8,91	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Parameter	Symbol	$V_{GE} = V_{CE}$	V_{GS} [V]	V_{CE} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Gate-emitter threshold voltage	$V_{GE(th)}$				0,005	25	5,4	6	6,6	V
Collector-emitter saturation voltage	V_{CESat}		15		50	25 125 150		1,55 1,77 1,83	1,9	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			90	μA
Gate-emitter leakage current	I_{GES}		15	0		25			500	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}							10000		pF
Output capacitance	C_{oes}		0	10		25		350		
Reverse transfer capacitance	C_{res}							130		
Gate charge	Q_g		15	600	50	25		410		nC

Thermal

Parameter	Symbol	Value	Unit
Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)	K/W

Dynamic

Parameter	Symbol	$R_{gon} = 16$ Ω $R_{goff} = 16$ Ω	V_{GS} [V]	V_{CE} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Turn-on delay time	$t_{d(on)}$	±15	600	50	25	25		343		ns
Rise time	t_r						125		337	
							150		349	
							25		84	
Turn-off delay time	$t_{d(off)}$						125		94	
		150		96						
		25		274						
Fall time	t_f	125		297						
		150		308						
		25		97						
Turn-on energy (per pulse)*	E_{on}	$Q_{iFWD} = 4,5$ μC $Q_{iFWD} = 8$ μC $Q_{iFWD} = 8,1$ μC	25	600	50	25		5,83		mWs
							125		7,88	
							150		7,98	
Turn-off energy (per pulse)*	E_{off}		25	600	50	25		2,97		
							125		4,12	
							150		5,04	

* $L_s = 12$ nH



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max		

Inverter Diode

Static

Parameter	Symbol	V_{GS} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Forward voltage	V_F			50	25 125 150		1,66 1,78 1,79	2,1	V
Reverse leakage current	I_R		1200		25			40	μA

Thermal

Parameter	Symbol	Conditions	Value	Unit
Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)	1,09	K/W

Dynamic

Parameter	Symbol	dI/dt [A/μs]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit	
Peak recovery current	I_{RRM}			25 125 150		23 28 28		A	
Reverse recovery time	t_{rr}			25 125 150		320 502 543		ns	
Recovered charge	Q_r	$dI/dt = 488$ A/μs $dI/dt = 364$ A/μs $dI/dt = 416$ A/μs	±15	600	50	25 125 150	4,51 7,96 8,10		μC
Reverse recovered energy	E_{rec}			25 125 150		1,48 2,90 3,16		mWs	
Peak rate of fall of recovery current	$(di_{rf}/dt)_{max}$			25 125 150		150 121 83		A/μs	

Thermistor

Parameter	Symbol	Conditions	Value	Unit
Rated resistance	R		25	kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 493$ Ω	100	%
Power dissipation	P		25	mW
Power dissipation constant			25	mW/K
B-value	$B_{(25/50)}$	Tol. ±2 %	25	K
B-value	$B_{(25/100)}$	Tol. ±2 %	25	K
Vincotech NTC Reference				K




Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu\text{s}$ $T_j: 25 \text{ }^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$ $T_j: 125 \text{ }^\circ\text{C}$ ———
 $T_j: 150 \text{ }^\circ\text{C}$ - - - -

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu\text{s}$ $T_j = 150 \text{ }^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 100 \mu\text{s}$ $T_j: 25 \text{ }^\circ\text{C}$
 $V_{CE} = 10 \text{ V}$ $T_j: 125 \text{ }^\circ\text{C}$ ———
 $T_j: 150 \text{ }^\circ\text{C}$ - - - -

figure 4. IGBT

Transient thermal impedance as function of pulse duration

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,77 \text{ K/W}$

IGBT thermal model values

R (K/W)	τ (s)
4,42E-02	4,45E+00
9,11E-02	9,15E-01
2,73E-01	1,28E-01
2,59E-01	4,34E-02
6,73E-02	6,94E-03
3,15E-02	6,91E-04




Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



- $D =$ single pulse
- $T_s =$ 80 °C
- $V_{GE} =$ ±15 V
- $T_j =$ T_{jmax}




Inverter Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$
 T_j : 25 °C (blue dotted line)
 125 °C (black solid line)
 150 °C (red dashed line)

figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,09 \text{ K/W}$
 FWD thermal model values


R (K/W)	τ (s)
4,05E-02	7,09E+00
8,82E-02	9,93E-01
2,80E-01	1,18E-01
4,48E-01	3,26E-02
1,45E-01	5,44E-03
9,23E-02	5,22E-04

Thermistor Characteristics

figure 1. Thermistor

Typical NTC characteristic as a function of temperature


$$R = f(T)$$





Inverter Switching Characteristics


figure 1. IGBT



With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C	————
$R_{g\text{on}} = 16$ Ω	$T_j = 150$ °C	-----
$R_{g\text{off}} = 16$ Ω		


figure 2. IGBT



With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C	————
$I_c = 50$ A	$T_j = 150$ °C	-----


figure 3. FWD



With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C	————
$R_{g\text{on}} = 16$ Ω	$T_j = 150$ °C	-----

figure 4. FWD



With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C	————
$I_c = 50$ A	$T_j = 150$ °C	-----




Inverter Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_c)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{g(on)} =$	16	Ω
$R_{g(off)} =$	16	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_c =$	50	A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_c)$$




At	$V_{CE} =$	600	V	$T_j =$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$R_{g(on)} =$	16	Ω		150 °C	-----

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{g(on)})$$



At	$V_{CE} =$	600	V	$T_j =$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$I_c =$	50	A		150 °C	-----




Inverter Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




At $V_{CE} = 600$ V $T_j = 25$ °C $I_c = 50$ A
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $R_{gdn} = 16$ Ω $T_j = 150$ °C

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gdn})$$




At $V_{CE} = 600$ V $T_j = 25$ °C $I_c = 50$ A
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $I_c = 50$ A $T_j = 150$ °C

figure 11. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$




At $V_{CE} = 600$ V $T_j = 25$ °C $I_c = 50$ A
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $R_{gdn} = 16$ Ω $T_j = 150$ °C

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gdn})$$




At $V_{CE} = 600$ V $T_j = 25$ °C $I_c = 50$ A
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $I_c = 50$ A $T_j = 150$ °C



Inverter Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_c)$



At $V_{CE} = 600$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $R_{g0n} = 16$ Ω $T_j = 150$ °C

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{g0n})$



At $V_{CE} = 600$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C
 $I_c = 50$ A $T_j = 150$ °C

figure 15. IGBT

Reverse bias safe operating area
 $I_c = f(V_{CE})$



At $T_j = 175$ °C
 $R_{g0n} = 16$ Ω
 $R_{g0ff} = 16$ Ω




Inverter Switching Definitions

General conditions		
T_j	=	125 °C
R_{gon}	=	16 Ω
R_{goff}	=	16 Ω

figure 1. IGBT


Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_{doff} =$	297	ns

figure 2. IGBT


Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_{don} =$	337	ns

figure 3. IGBT


Turn-off Switching Waveforms & definition of t_f



$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_f =$	106	ns

figure 4. IGBT

Turn-on Switching Waveforms & definition of t_r



$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_r =$	94	ns




Vincotech

10-EY126PA050M7-L196F78T
10-E2126PA050M7-L196F78Z
 datasheet


Inverter Switching Characteristics

figure 5. FWD
 Turn-off Switching Waveforms & definition of t_{rr}



$V_F(100\%) =$	600	V
$I_F(100\%) =$	50	A
$I_{RRM}(100\%) =$	28	A
$t_{rr} =$	502	ns

figure 6. FWD
 Turn-on Switching Waveforms & definition of t_{qr} (t_{qr} = integrating time for Q_r)



$I_F(100\%) =$	50	A
$Q_r(100\%) =$	7,96	μC



Ordering Code & Marking								
Version			Ordering Code					
without thermal paste 12 mm housing with press-fit pins			10-EY126PA050M7-L196F78T					
with thermal paste 12 mm housing with press-fit pins			10-EY126PA050M7-L196F78T-/3/					
without thermal paste 12 mm housing with Solder pins			10-E2126PA050M7-L196F78Z					
with thermal paste 12 mm housing with Solder pins			10-E2126PA050M7-L196F78Z-/3/					
NN-NNNNNNNNNNNN TTTTIV WWYY UL VIN LLLL SSSS			Text	Name	Date code	UL & VIN	Lot	Serial
				NN-NNNNNNNNNNNN-TTTTIV	WWYY	UL VIN	LLLLL	SSSS
			Datamatrix	Type&Ver	Lot number	Serial	Date code	
			TTTTTIV	LLLLL	SSSS	WWYY		

Pin table			
Pin	X	Y	Function
1	32	3,2	G16
2	32	0	Ph3
3	28,8	0	Ph3
4	25,6	0	Ph3
5	19,2	0	Ph2
6	16	0	Ph2
7	12,8	0	Ph2
8	12,8	3,2	G14
9	6,4	0	Ph1
10	3,2	0	Ph1
11	0	0	Ph1
12	0	3,2	G12
13	0	19,2	Therm1
14	0	28,8	Therm2
15	0	44,8	G11
16	0	48	DC-1
17	3,2	48	DC-1
18	6,4	48	DC-1
19	9,6	48	DC-1
20	12,8	48	DC-2
21	12,8	44,8	G13
22	16	48	DC-2
23	19,2	48	DC-2
24	22,4	48	DC-2
25	22,4	44,8	G15
26	25,6	48	DC-3
27	28,8	48	DC-3
28	32	48	DC-3
29	32	44,8	DC-3
30	12,8	25,6	DC+
31	12,8	22,4	DC+
32	12,8	19,2	DC+
33	12,8	16	DC+


Outline

center of press-fit pinhead
for connection parameter see the handling instruction

Tolerance of pinpositions: ±0,4mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	50 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	50 A	Inverter Diode	
Rt	NTC			Thermistor	




Vincotech

10-EY126PA050M7-L196F78T
10-E2126PA050M7-L196F78Z
datasheet

Packaging instruction			
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow</i> E2 packages see vincotech.com website.

Package data
Package data for <i>flow</i> E2 packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-Ex126PA050M7-L196F78x-D2-14	04 Dec. 2018	Added Z option to ordering code	1, 14

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.