





Vincotech

10-EZ12PMA015M7-L928A78T 10-E112PMA015M7-L928A78Z

datasheet

flowPIM E1		1200 V / 15 A
Features • IGBT M7 with low V_{CEsat} and improved EMC behavior • Standard industrial housing • Optimized $R_{th(j-s)}$ with Phase Change Material • Built-in NTC		flow E1 12 mm housing  Press-fit pin Solder pin
Target applications • Industrial Drives		Schematic 
Types • 10-EZ12PMA015M7-L928A78T • 10-E112PMA015M7-L928A78Z		

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	21	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	30	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	64	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
-----------	--------	-----------	-------	------

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	21	A
Repetitive peak forward current	I_{FRM}	T_j limited by T_{jmax}	30	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	51	W
Maximum junction temperature	T_{jmax}		175	°C

Brake Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	21	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	30	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	64	W
Gate-emitter voltage	V_{GES}		±20	V
Maximum junction temperature	T_{jmax}		175	°C

Brake Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	14	A
Repetitive peak forward current	I_{FRM}	T_j limited by T_{jmax}	20	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	43	W
Maximum junction temperature	T_{jmax}		175	°C

Rectifier Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	47	A
Surge (non-repetitive) forward current	I_{FSM}	50 Hz Single Half Sine Wave $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	270	A
Surge current capability	I^2t		370	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	58	W
Maximum junction temperature	T_{jmax}		150	°C



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
-----------	--------	-----------	-------	------

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{top}		-40...(T_{jmax} - 25)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance			min. 12,7	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,0015	25	5,4	6,0	6,6	V
Collector-emitter saturation voltage	V_{CEsat}		15		15	25 125 150		1,70 1,95 2,01	2,15	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			60	µA
Gate-emitter leakage current	I_{GES}		20	0		25			500	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}	0	10	25				2900		pF
Output capacitance	C_{oes}							120		
Reverse transfer capacitance	C_{res}							34		
Gate charge	Q_g		15	600	15	25		110		nC

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						1,49		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 32 \Omega$ $R_{goff} = 32 \Omega$	± 15	600	15	25 125 150		196 191 190		ns
Rise time	t_r					25 125 150		60 63 64		
Turn-off delay time	$t_{d(off)}$					25 125 150		181 206 211		
Fall time	t_f					25 125 150		95 113 114		
Turn-on energy (per pulse)*	E_{on}	$Q_{iFWD} = 1,5 \mu\text{C}$ $Q_{iFWD} = 2,5 \mu\text{C}$ $Q_{iFWD} = 2,7 \mu\text{C}$	± 15	600	15	25 125 150		1,69 2,11 2,21		mWs
Turn-off energy (per pulse)*	E_{off}					25 125 150		0,987 1,33 1,41		

* $L_s = 14 \text{ nH}$



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				15	25 125 150		1,63 1,74 1,73	2,1	V
Reverse leakage current	I_R			1200		25			30	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						1,88		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt = 181 \text{ A/}\mu\text{s}$ $di/dt = 205 \text{ A/}\mu\text{s}$ $di/dt = 175 \text{ A/}\mu\text{s}$	± 15	600	15	25 125 150		9 11 11		A
Reverse recovery time	t_{rr}					25 125 150		286 422 471		ns
Recovered charge	Q_r					25 125 150		1,50 2,46 2,68		μC
Reverse recovered energy	E_{rec}					25 125 150		0,497 0,913 1,00		mWs
Peak rate of fall of recovery current	$(di_{rf}/dt)_{max}$					25 125 150		77 49 44		A/μs



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,0015	25	5,4	6,0	6,6	V
Collector-emitter saturation voltage	V_{CEsat}		15		15	25 125 150		1,70 1,95 2,01	2,15	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			60	µA
Gate-emitter leakage current	I_{GES}		20	0		25			500	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}	0	10	25				2900		pF
Output capacitance	C_{oes}							120		
Reverse transfer capacitance	C_{res}							34		
Gate charge	Q_g		15	600	15	25		110		nC

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						1,49		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 32 \Omega$ $R_{goff} = 32 \Omega$	0 / 15	600	15	25 125 150		300 262 253		ns
Rise time	t_r					25 125 150		194 205 209		
Turn-off delay time	$t_{d(off)}$					25 125 150		388 428 438		
Fall time	t_f					25 125 150		67 87 89		
Turn-on energy (per pulse)	E_{on}					25 125 150		2,50 3,01 3,19		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		1,12 1,44 1,54		



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Diode

Static

Forward voltage	V_F				10	25 125 150		1,61 1,69 1,69	2,1	V
Reverse leakage current	I_R			1200		25			25	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK (PSX)}$						2,19		K/W
-------------------------------------	---------------	--	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt = 74 \text{ A/}\mu\text{s}$ $di/dt = 65 \text{ A/}\mu\text{s}$ $di/dt = 62 \text{ A/}\mu\text{s}$	0 / 15	600	15	25 125 150		6 7 7		A
Reverse recovery time	t_{rr}					25 125 150		317 473 542		ns
Recovered charge	Q_r					25 125 150		1,11 1,78 2,04		μC
Reverse recovered energy	E_{rec}					25 125 150		0,368 0,644 0,753		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		40 28 24		A/μs

Rectifier Diode

Static

Forward voltage	V_F				35	25 125		1,17 1,13		V
Reverse leakage current	I_R			1600		25			50	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK (PSX)}$						1,20		K/W
-------------------------------------	---------------	--	--	--	--	--	--	------	--	-----



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Rated resistance	R					25		5		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 493 \Omega$				100	-5		+5	%
Power dissipation	P					25		245		mW
Power dissipation constant						25		1,4		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 2 \%$				25		3375		K
B-value	$B_{(25/100)}$	Tol. $\pm 2 \%$				25		3437		K
Vincotech NTC Reference									K	



Vincotech


10-EZ12PMA015M7-L928A78T 10-E112PMA015M7-L928A78Z datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted)
 $125 \text{ } ^\circ C$ (black solid)
 $150 \text{ } ^\circ C$ (red dashed)

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 100 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted)
 $125 \text{ } ^\circ C$ (black solid)
 $150 \text{ } ^\circ C$ (red dashed)

figure 4. IGBT

Transient thermal impedance as function of pulse duration

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,49 \text{ K/W}$

IGBT thermal model values


$R \text{ (K/W)}$	$\tau \text{ (s)}$
4,90E-02	3,61E+00
1,10E-01	6,54E-01
4,70E-01	1,09E-01
4,98E-01	2,97E-02
2,21E-01	4,73E-03
1,37E-01	5,51E-04



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Inverter Switch Characteristics





Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Inverter Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech


10-EZ12PMA015M7-L928A78T 10-E112PMA015M7-L928A78Z datasheet

Brake Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted)
 $125 \text{ } ^\circ C$ (black solid)
 $150 \text{ } ^\circ C$ (red dashed)

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 100 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (blue dotted)
 $125 \text{ } ^\circ C$ (black solid)
 $150 \text{ } ^\circ C$ (red dashed)

figure 4. IGBT

Transient thermal impedance as function of pulse duration

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,49 \text{ K/W}$

IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
4,90E-02	3,61E+00
1,10E-01	6,54E-01
4,70E-01	1,09E-01
4,98E-01	2,97E-02
2,21E-01	4,73E-03
1,37E-01	5,51E-04



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Brake Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse
 $T_s =$ 80 °C
 $V_{GE} =$ ±15 V
 $T_j =$ T_{jmax}



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Brake Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$$D = \frac{t_p}{T}$$
$$R_{th(j-s)} = 2,19 \text{ K/W}$$

FWD thermal model values

R (K/W)	τ (s)
8,09E-02	3,20E+00
2,08E-01	2,82E-01
6,85E-01	4,41E-02
5,92E-01	1,02E-02
3,27E-01	2,02E-03
2,95E-01	3,64E-04



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Rectifier Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$$D = t_p / T$$

$$R_{th(j-s)} = 1,20 \text{ K/W}$$

FWD thermal model values


$R \text{ (K/W)}$	$\tau \text{ (s)}$
3,54E-02	9,31E+00
8,09E-02	9,99E-01
2,12E-01	1,71E-01
6,76E-01	4,85E-02
1,19E-01	5,88E-03
7,98E-02	8,33E-04

Thermistor Characteristics

figure 1. Thermistor

Typical NTC characteristic
 as a function of temperature

$$R = f(T)$$





Vincotech


10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Inverter Switching Characteristics

figure 1. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{g(on)} = 32$ Ω
 $R_{g(off)} = 32$ Ω

T_j :

25 °C


125 °C

150 °C

figure 2. IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 15$ A

T_j :

25 °C


125 °C

150 °C

figure 3. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{g(on)} = 32$ Ω

T_j :

25 °C


125 °C

150 °C

figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 15$ A

T_j :

25 °C

125 °C

150 °C



Vincotech


10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Inverter Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	32	Ω
$R_{goff} =$	32	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	15	A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$




At	$V_{CE} =$	600	V	$T_j:$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$R_{gon} =$	32	Ω		150 °C	-----

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



At	$V_{CE} =$	600	V	$T_j:$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	15	A		150 °C	-----



Vincotech


10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Inverter Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$




At	$V_{CE} =$	600	V	$T_j =$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$R_{gon} =$	32	Ω		150 °C	-----

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$




At	$V_{CE} =$	600	V	$T_j =$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	15	A		150 °C	-----

figure 11. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$




At	$V_{CE} =$	600	V	$T_j =$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$R_{gon} =$	32	Ω		150 °C	-----

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



At	$V_{CE} =$	600	V	$T_j =$	25 °C	
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	15	A		150 °C	-----




Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Inverter Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_F/dt, di_{rr}/dt = f(I_C)$



At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 32$ Ω
 $T_j = 25$ °C
 125 °C
 150 °C

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_F/dt, di_{rr}/dt = f(R_{gon})$



At $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 15$ A
 $T_j = 25$ °C
 125 °C
 150 °C

figure 15. IGBT

Reverse bias safe operating area
 $I_C = f(V_{CE})$



At $T_j = 175$ °C
 $R_{gon} = 32$ Ω
 $R_{goff} = 32$ Ω



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Inverter Switching Definitions

General conditions

T_j	=	125 °C
R_{gon}	=	32 Ω
R_{goff}	=	32 Ω

figure 1. IGBT




figure 2. IGBT




figure 3. IGBT





figure 4. IGBT





Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Inverter Switching Characteristics

figure 5. FWD





figure 6. FWD





Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Brake Switching Characteristics

figure 1. IGBT

Typical switching energy losses as a function of collector current




figure 2. IGBT

Typical switching energy losses as a function of gate resistor




figure 3. FWD

Typical reverse recovered energy loss as a function of collector current





figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor





Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Brake Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$





figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$





Vincotech


10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Brake Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$




At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $R_{gon} = 32$ Ω
 T_j : 25 °C (blue dotted), 125 °C (black solid), 150 °C (red dashed)

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$




At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $I_C = 15$ A
 T_j : 25 °C (blue dotted), 125 °C (black solid), 150 °C (red dashed)

figure 11. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$




At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $R_{gon} = 32$ Ω
 T_j : 25 °C (blue dotted), 125 °C (black solid), 150 °C (red dashed)

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $I_C = 15$ A
 T_j : 25 °C (blue dotted), 125 °C (black solid), 150 °C (red dashed)




Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Brake Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_F/dt, di_{rr}/dt = f(I_C)$



At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $R_{gon} = 32$ Ω
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_F/dt, di_{rr}/dt = f(R_{gon})$



At $V_{CE} = 600$ V
 $V_{GE} = 0 / 15$ V
 $I_C = 15$ A
 $T_j = 25$ °C
 $T_j = 125$ °C
 $T_j = 150$ °C

figure 15. IGBT

Reverse bias safe operating area
 $I_C = f(V_{CE})$



At $T_j = 125$ °C
 $R_{gon} = 32$ Ω
 $R_{goff} = 32$ Ω



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Brake Switching Definitions

General conditions

T_j	=	125 °C
R_{gon}	=	32 Ω
R_{goff}	=	32 Ω

figure 1. IGBT




figure 2. IGBT




figure 3. IGBT





figure 4. IGBT





Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
 datasheet

Brake Switching Characteristics

figure 5. FWD





figure 6. FWD








Vincotech

10-EZ12PMA015M7-L928A78T 10-E112PMA015M7-L928A78Z

datasheet

Ordering Code & Marking							
Version			Ordering Code				
without thermal paste 12 mm housing with press-fit pins			10-EZ12PMA015M7-L928A78T				
with thermal paste 12 mm housing with press-fit pins			10-EZ12PMA015M7-L928A78T-/3/				
without thermal paste 12 mm housing with Solder pins			10-E112PMA015M7-L928A78Z				
with thermal paste 12 mm housing with Solder pins			10-E112PMA015M7-L928A78Z-/3/				
NN-NNNNNNNNNNNNNN TTTTTUV WWYY UL VIN LLLLL SSSS 	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN-TTTTTUV		WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTUV	LLLLL	SSSS	WWYY			


Pin table				Outline			
Pin	X	Y	Function				
1	32	0	Br	 Solder pin 0.64 ±0.03 15.9 ±0.1			
2	25,6	0	DC-Br				
3	22,4	0	G27				
4	19,2	0	DC-Rect				
5	16	0	G15				
6	12,8	0	DC-3				
7	9,6	0	G13				
8	6,4	0	DC-2				
9	3,2	0	G11				
10	0	0	DC-1				
11	0	25,6	Ph1	 Press-fit pin center of press-fit pinhead for connection parameter see the handling instruction 13.08 ±0.1 16.4 ±0.5			
12	3,2	25,6	G12				
13	9,6	25,6	Ph2				
14	12,8	25,6	G14				
15	19,2	25,6	Ph3				
16	22,4	25,6	G16				
17	32	25,6	ACIn1				
18	25,6	19,2	ACIn2				
19	19,2	16	Therm1				
20	16	16	Therm2				
21	25,6	12,8	ACIn3	 12.8 16 X Y			
22	22,4	6,4	DC+Inv				
23	25,6	6,4	DC+Rect				
				Tolerance of pinpositions: ±0.4mm at the end of pins Dimension of coordinate axis is only offset without tolerance			



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	15 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	15 A	Inverter Diode	
T27	IGBT	1200 V	15 A	Brake Switch	
D27	FWD	1200 V	10 A	Brake Diode	
D31, D32, D33, D34, D35, D36	Rectifier	1600 V	35 A	Rectifier Diode	
Rt	NTC			Thermistor	



Vincotech

10-EZ12PMA015M7-L928A78T
10-E112PMA015M7-L928A78Z
datasheet

Packaging instruction			
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow</i> E1 packages see vincotech.com website.

Package data
Package data for <i>flow</i> E1 packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-Ex12PMA015M7-L928A78T-D4-14	30 May. 2019	Correction of I_G/I_f values Outline updated	1,2 28

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.