



Vincotech

# 10-FZ127PA008SC-L156E08

datasheet

flow7PACK 0

1200 V / 8 A

## Topology features

- Open Emitter configuration
- Temperature sensor
- Brake+Inverter

## Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current

## Housing features

- Base isolation:  $\text{Al}_2\text{O}_3$
- Clip-in, reliable mechanical connection, qualified for wave soldering
- Convex shaped substrate for superior thermal contact
- Thermo-mechanical push-and-pull force relief
- Solder pin


## Target applications

- Motor Drives
- Power Generation


## Types

- 10-FZ127PA008SC-L156E08

## flow 0 12 mm housing



## Schematic





Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                         | Symbol     | Conditions                                                             | Value    | Unit               |
|-----------------------------------|------------|------------------------------------------------------------------------|----------|--------------------|
| <b>Inverter Switch</b>            |            |                                                                        |          |                    |
| Collector-emitter voltage         | $V_{CES}$  |                                                                        | 1200     | V                  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 16       | A                  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$                                            | 24       | A                  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 61       | W                  |
| Gate-emitter voltage              | $V_{GES}$  |                                                                        | $\pm 20$ | V                  |
| Short circuit ratings             | $t_{SC}$   | $V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$ | 10       | $\mu s$            |
| Maximum junction temperature      | $T_{jmax}$ |                                                                        | 175      | $^{\circ}\text{C}$ |

## Inverter Diode

|                                 |            |                                       |      |                    |
|---------------------------------|------------|---------------------------------------|------|--------------------|
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 1200 | V                  |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 20   | A                  |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 20   | A                  |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 46   | W                  |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175  | $^{\circ}\text{C}$ |

## Brake Switch

|                                   |            |                                                                        |          |                    |
|-----------------------------------|------------|------------------------------------------------------------------------|----------|--------------------|
| Collector-emitter voltage         | $V_{CES}$  |                                                                        | 1200     | V                  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 16       | A                  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$                                            | 24       | A                  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 61       | W                  |
| Gate-emitter voltage              | $V_{GES}$  |                                                                        | $\pm 20$ | V                  |
| Short circuit ratings             | $t_{SC}$   | $V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$ | 10       | $\mu s$            |
| Maximum junction temperature      | $T_{jmax}$ |                                                                        | 175      | $^{\circ}\text{C}$ |



Vincotech

10-FZ127PA008SC-L156E08  
datasheet

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                       | Symbol     | Conditions                            | Value | Unit |
|---------------------------------|------------|---------------------------------------|-------|------|
| <b>Brake Diode</b>              |            |                                       |       |      |
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 1200  | V    |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 20    | A    |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 20    | A    |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 46    | W    |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175   | °C   |

## Brake Sw. Protection Diode

|                                 |            |                                       |      |    |
|---------------------------------|------------|---------------------------------------|------|----|
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 1200 | V  |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 10   | A  |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 6    | A  |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 25   | W  |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 150  | °C |

## Module Properties

### Thermal Properties

|                                                 |           |  |                            |    |
|-------------------------------------------------|-----------|--|----------------------------|----|
| Storage temperature                             | $T_{stg}$ |  | -40...+125                 | °C |
| Operation temperature under switching condition | $T_{jop}$ |  | -40...+( $T_{jmax} - 25$ ) | °C |

### Isolation Properties

|                            |            |                                     |       |    |
|----------------------------|------------|-------------------------------------|-------|----|
| Isolation voltage          | $V_{isol}$ | DC Test Voltage* $t_p = 2\text{ s}$ | 6000  | V  |
| Isolation voltage          | $V_{isol}$ | AC Voltage $t_p = 1\text{ min}$     | 2500  | V  |
| Creepage distance          |            |                                     | >12,7 | mm |
| Clearance                  |            |                                     | 9,1   | mm |
| Comparative Tracking Index | CTI        |                                     | ≥ 200 |    |

\*100 % tested in production



Vincotech

## Characteristic Values

| Parameter | Symbol | Conditions |                              |                                           |                                     |            |     | Values |     |  | Unit |
|-----------|--------|------------|------------------------------|-------------------------------------------|-------------------------------------|------------|-----|--------|-----|--|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min | Typ    | Max |  |      |

### Inverter Switch

#### Static

|                                      |              |                     |    |      |         |           |      |              |                     |    |
|--------------------------------------|--------------|---------------------|----|------|---------|-----------|------|--------------|---------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$ | $V_{CE} = V_{GE}$   |    |      | 0,00015 | 25        | 5,3  | 5,8          | 6,3                 | V  |
| Collector-emitter saturation voltage | $V_{CEsat}$  |                     | 15 |      | 8       | 25<br>150 | 1,58 | 1,86<br>2,24 | 2,07 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$    |                     | 0  | 1200 |         | 25        |      |              | 1                   | µA |
| Gate-emitter leakage current         | $I_{GES}$    |                     | 20 | 0    |         | 25        |      |              | 120                 | nA |
| Internal gate resistance             | $r_g$        |                     |    |      |         |           |      | None         |                     | Ω  |
| Input capacitance                    | $C_{ies}$    | $f = 1 \text{ Mhz}$ | 0  | 25   |         | 25        |      | 490          |                     | pF |
| Reverse transfer capacitance         | $C_{res}$    |                     |    |      |         |           |      | 30           |                     | pF |

#### Thermal

|                                                    |               |                                               |  |  |  |  |  |      |  |     |
|----------------------------------------------------|---------------|-----------------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4 \text{ W/mK}$<br>(PSX) |  |  |  |  |  | 1,57 |  | K/W |
|----------------------------------------------------|---------------|-----------------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |                                                                 |          |     |   |           |  |                 |  |     |
|-----------------------------|--------------|-----------------------------------------------------------------|----------|-----|---|-----------|--|-----------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  | $R_{gon} = 32 \Omega$<br>$R_{goff} = 32 \Omega$                 | $\pm 15$ | 600 | 8 | 25<br>125 |  | 71,4<br>70,6    |  | ns  |
| Rise time                   | $t_r$        |                                                                 |          |     |   | 25<br>125 |  | 18,6<br>22,8    |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |                                                                 |          |     |   | 25<br>125 |  | 194,4<br>236,4  |  | ns  |
| Fall time                   | $t_f$        |                                                                 |          |     |   | 25<br>125 |  | 78,46<br>108,16 |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     | $Q_{tFWD} = 0,885 \mu\text{C}$<br>$Q_{tFWD} = 1,57 \mu\text{C}$ |          |     |   | 25<br>125 |  | 0,499<br>0,748  |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |                                                                 |          |     |   | 25<br>125 |  | 0,435<br>0,624  |  | mWs |





Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |                                           |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|-------------------------------------------|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Inverter Diode

#### Static

|                         |       |                |  |  |    |           |      |              |                     |    |
|-------------------------|-------|----------------|--|--|----|-----------|------|--------------|---------------------|----|
| Forward voltage         | $V_F$ |                |  |  | 10 | 25<br>150 | 1,35 | 1,77<br>1,69 | 2,05 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 1200$ V |  |  |    | 25        |      |              | 2,7                 | μA |

#### Thermal

|                                                    |               |                                       |  |  |  |  |  |      |  |     |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 2,07 |  | K/W |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                                       |                      |                                      |          |     |   |           |  |                  |  |      |
|---------------------------------------|----------------------|--------------------------------------|----------|-----|---|-----------|--|------------------|--|------|
| Peak recovery current                 | $I_{RRM}$            | $di/dt=452$ A/μs<br>$di/dt=399$ A/μs | $\pm 15$ | 600 | 8 | 25<br>125 |  | 8,46<br>9,88     |  | A    |
| Reverse recovery time                 | $t_{rr}$             |                                      |          |     |   | 25<br>125 |  | 250,51<br>382,73 |  | ns   |
| Recovered charge                      | $Q_r$                |                                      |          |     |   | 25<br>125 |  | 0,885<br>1,57    |  | μC   |
| Reverse recovered energy              | $E_{rec}$            |                                      |          |     |   | 25<br>125 |  | 0,345<br>0,634   |  | mWs  |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ |                                      |          |     |   | 25<br>125 |  | 83,99<br>69,05   |  | A/μs |



Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |                                           |                                     |            |  | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|-------------------------------------------|-------------------------------------|------------|--|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] |  | Min    | Typ | Max |      |

### Brake Switch

#### Static

|                                      |              |                     |    |      |         |           |  |      |              |                     |    |
|--------------------------------------|--------------|---------------------|----|------|---------|-----------|--|------|--------------|---------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$ | $V_{CE} = V_{GE}$   |    |      | 0,00015 | 25        |  | 5,3  | 5,8          | 6,3                 | V  |
| Collector-emitter saturation voltage | $V_{CEsat}$  |                     | 15 |      | 8       | 25<br>150 |  | 1,58 | 1,86<br>2,24 | 2,07 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$    |                     | 0  | 1200 |         | 25        |  |      |              | 1                   | µA |
| Gate-emitter leakage current         | $I_{GES}$    |                     | 20 | 0    |         | 25        |  |      |              | 120                 | nA |
| Internal gate resistance             | $r_g$        |                     |    |      |         |           |  |      | None         |                     | Ω  |
| Input capacitance                    | $C_{ies}$    | $f = 1 \text{ Mhz}$ | 0  | 25   |         | 25        |  |      | 490          |                     | pF |
| Reverse transfer capacitance         | $C_{res}$    |                     |    |      |         |           |  |      | 30           |                     | pF |

#### Thermal

|                                                    |               |                                               |  |  |  |  |  |  |      |  |     |
|----------------------------------------------------|---------------|-----------------------------------------------|--|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4 \text{ W/mK}$<br>(PSX) |  |  |  |  |  |  | 1,57 |  | K/W |
|----------------------------------------------------|---------------|-----------------------------------------------|--|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |                                                     |          |     |   |           |  |                 |  |     |
|-----------------------------|--------------|-----------------------------------------------------|----------|-----|---|-----------|--|-----------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  | $R_{gon} = 32 \Omega$<br>$R_{goff} = 32 \Omega$     | $\pm 15$ | 600 | 8 | 25<br>125 |  | 71,4<br>70,6    |  | ns  |
| Rise time                   | $t_r$        |                                                     |          |     |   | 25<br>125 |  | 18,6<br>22,8    |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |                                                     |          |     |   | 25<br>125 |  | 194,4<br>236,4  |  | ns  |
| Fall time                   | $t_f$        |                                                     |          |     |   | 25<br>125 |  | 78,46<br>108,16 |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     | $Q_{tFWD} = 0,885 \mu C$<br>$Q_{tFWD} = 1,57 \mu C$ |          |     |   | 25<br>125 |  | 0,499<br>0,748  |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |                                                     |          |     |   | 25<br>125 |  | 0,435<br>0,624  |  | mWs |



Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

## Characteristic Values

| Parameter | Symbol | Conditions |                              |                                           |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|-------------------------------------------|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Brake Diode

#### Static

|                         |       |                |  |  |    |           |      |              |                     |    |
|-------------------------|-------|----------------|--|--|----|-----------|------|--------------|---------------------|----|
| Forward voltage         | $V_F$ |                |  |  | 10 | 25<br>150 | 1,35 | 1,77<br>1,69 | 2,05 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 1200$ V |  |  |    | 25        |      |              | 2,7                 | μA |

#### Thermal

|                                                    |               |                                       |  |  |  |  |  |      |  |     |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 2,07 |  | K/W |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                                       |                      |                                      |          |     |   |           |  |                  |  |      |
|---------------------------------------|----------------------|--------------------------------------|----------|-----|---|-----------|--|------------------|--|------|
| Peak recovery current                 | $I_{RRM}$            | $di/dt=452$ A/μs<br>$di/dt=399$ A/μs | $\pm 15$ | 600 | 8 | 25<br>125 |  | 8,46<br>9,88     |  | A    |
| Reverse recovery time                 | $t_{rr}$             |                                      |          |     |   | 25<br>125 |  | 250,51<br>382,73 |  | ns   |
| Recovered charge                      | $Q_r$                |                                      |          |     |   | 25<br>125 |  | 0,885<br>1,57    |  | μC   |
| Reverse recovered energy              | $E_{rec}$            |                                      |          |     |   | 25<br>125 |  | 0,345<br>0,634   |  | mWs  |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ |                                      |          |     |   | 25<br>125 |  | 83,99<br>69,05   |  | A/μs |

### Brake Sw. Protection Diode

#### Static

|                         |       |                |  |  |   |           |      |              |                     |    |
|-------------------------|-------|----------------|--|--|---|-----------|------|--------------|---------------------|----|
| Forward voltage         | $V_F$ |                |  |  | 3 | 25<br>150 | 1,23 | 1,65<br>1,52 | 1,97 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_r = 1200$ V |  |  |   | 25        |      |              | 27                  | μA |

#### Thermal

|                                                    |               |                                       |  |  |  |  |  |     |  |     |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 2,8 |  | K/W |
|----------------------------------------------------|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|



Vincotech

## Characteristic Values

| Parameter | Symbol | Conditions |                              |                                           |                                     |            | Values |     |     | Unit |
|-----------|--------|------------|------------------------------|-------------------------------------------|-------------------------------------|------------|--------|-----|-----|------|
|           |        |            | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min    | Typ | Max |      |

### Thermistor

#### Static

|                                |                |                         |  |  |  |     |    |      |   |      |
|--------------------------------|----------------|-------------------------|--|--|--|-----|----|------|---|------|
| Rated resistance               | $R$            |                         |  |  |  | 25  |    | 22   |   | kΩ   |
| Deviation of $R_{100}$         | $\Delta_{R/R}$ | $R_{100} = 1484 \Omega$ |  |  |  | 100 | -5 |      | 5 | %    |
| Power dissipation              | $P$            |                         |  |  |  | 25  |    | 130  |   | mW   |
| Power dissipation constant     | $d$            |                         |  |  |  | 25  |    | 1,5  |   | mW/K |
| B-value                        | $B_{(25/50)}$  | Tol. $\pm 1 \%$         |  |  |  |     |    | 3962 |   | K    |
| B-value                        | $B_{(25/100)}$ | Tol. $\pm 1 \%$         |  |  |  |     |    | 4000 |   | K    |
| Vincotech Thermistor Reference |                |                         |  |  |  |     |    |      | I |      |

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.



Vincotech


# 10-FZ127PA008SC-L156E08 datasheet

## Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_J: 25 ^\circ C$   
 $150 ^\circ C$

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_J = 150 ^\circ C$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_J: 25 ^\circ C$   
 $150 ^\circ C$

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 1,566 K/W$   
IGBT thermal model values  

| $R (K/W)$ | $\tau (s)$ |
|-----------|------------|
| 1,42E-01  | 5,98E-01   |
| 6,32E-01  | 7,71E-02   |
| 3,98E-01  | 2,43E-02   |
| 2,86E-01  | 6,16E-03   |
| 1,08E-01  | 1,44E-03   |



Vincotech


**10-FZ127PA008SC-L156E08**  
datasheet

## Inverter Switch Characteristics

**figure 5.** IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D$  = single pulse

$T_s = 80$  °C

$V_{GE} = 15$  V

$T_j = T_{jmax}$



Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

## Inverter Diode Characteristics

figure 6.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



|                          |            |     |
|--------------------------|------------|-----|
| $D =$                    | $t_p / T$  |     |
| $R_{th(j-s)} =$          | 2,066      | K/W |
| FWD thermal model values |            |     |
| $R$ (K/W)                | $\tau$ (s) |     |
| 5,09E-02                 | 4,26E+00   |     |
| 1,55E-01                 | 5,03E-01   |     |
| 7,75E-01                 | 7,89E-02   |     |
| 5,33E-01                 | 2,68E-02   |     |
| 3,54E-01                 | 5,03E-03   |     |
| 1,97E-01                 | 9,09E-04   |     |



Vincotech

# 10-FZ127PA008SC-L156E08 datasheet

## Brake Switch Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$





figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$







Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet


## Brake Switch Characteristics

figure 12.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$



D = single pulse

T<sub>s</sub> = 80 °C

V<sub>GE</sub> = 15 V

T<sub>j</sub> = T<sub>jmax</sub>



Vincotech

## Brake Diode Characteristics

figure 13.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 14.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



|                          |            |     |
|--------------------------|------------|-----|
| $D =$                    | $t_p / T$  |     |
| $R_{th(j-s)} =$          | 2,066      | K/W |
| FWD thermal model values |            |     |
| $R$ (K/W)                | $\tau$ (s) |     |
| 5,09E-02                 | 4,26E+00   |     |
| 1,55E-01                 | 5,03E-01   |     |
| 7,75E-01                 | 7,89E-02   |     |
| 5,33E-01                 | 2,68E-02   |     |
| 3,54E-01                 | 5,03E-03   |     |
| 1,97E-01                 | 9,09E-04   |     |



Vincotech

## Brake Sw. Protection Diode Characteristics

figure 15.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 16.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



|                          |            |     |
|--------------------------|------------|-----|
| $D =$                    | $t_p / T$  |     |
| $R_{th(j-s)} =$          | 2,796      | K/W |
| FWD thermal model values |            |     |
| $R$ (K/W)                | $\tau$ (s) |     |
| 7,82E-02                 | 2,45E+00   |     |
| 1,95E-01                 | 2,65E-01   |     |
| 9,84E-01                 | 4,77E-02   |     |
| 6,58E-01                 | 1,23E-02   |     |
| 5,09E-01                 | 2,70E-03   |     |
| 3,71E-01                 | 5,98E-04   |     |



Vincotech


**10-FZ127PA008SC-L156E08**  
datasheet

## Thermistor Characteristics

**figure 17.** Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

# 10-FZ127PA008SC-L156E08 datasheet


## Inverter Switching Characteristics

figure 18.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$   
 $R_{goff} = 32$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 19.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A


$T_j$ : — 25 °C  
— 125 °C

figure 20.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 21.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

$T_j$ : — 25 °C  
— 125 °C



Vincotech


# 10-FZ127PA008SC-L156E08 datasheet

## Inverter Switching Characteristics

figure 22.

IGBT

Typical switching times as a function of collector current  
 $t = f(I_C)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω  
 $R_{goff} = 32$  Ω

figure 23.

IGBT

Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

figure 24.

FWD

Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω

$T_j$ : — 25 °C  
— 125 °C

figure 25.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

$T_j$ : — 25 °C  
— 125 °C



Vincotech

10-FZ127PA008SC-L156E08  
datasheet


## Inverter Switching Characteristics

figure 26.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω


$T_j$ : — 25 °C  
— 125 °C

figure 28.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω


$T_j$ : — 25 °C  
— 125 °C

figure 27.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 8$  A


$T_j$ : — 25 °C  
— 125 °C

figure 29.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 8$  A

$T_j$ : — 25 °C  
— 125 °C




Vincotech

10-FZ127PA008SC-L156E08  
datasheet

## Inverter Switching Characteristics

figure 30. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 32 \text{ } \Omega$

$T_j$ : — 25 °C  
— 125 °C

figure 31. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_C = 8 \text{ A}$

$T_j$ : — 25 °C  
— 125 °C

figure 32. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At  $T_j = 125 \text{ } ^\circ\text{C}$   
 $R_{gon} = 32 \text{ } \Omega$   
 $R_{goff} = 32 \text{ } \Omega$





Vincotech

# 10-FZ127PA008SC-L156E08 datasheet


## Brake Switching Characteristics

figure 33.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$   
 $R_{goff} = 32$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 34.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A


$T_j$ : — 25 °C  
— 125 °C

figure 35.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$


$T_j$ : — 25 °C  
— 125 °C

figure 36.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

$T_j$ : — 25 °C  
— 125 °C



Vincotech


# 10-FZ127PA008SC-L156E08 datasheet

## Brake Switching Characteristics

figure 37.

IGBT

Typical switching times as a function of collector current  
 $t = f(I_C)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$   
 $R_{goff} = 32$   $\Omega$

figure 38.

IGBT

Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 125$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

figure 39.

FWD

Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$

$T_j$ : — 25 °C  
— 125 °C

figure 40.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

$T_j$ : — 25 °C  
— 125 °C




## Brake Switching Characteristics

figure 41.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω


$T_j$ : — 25 °C  
— 125 °C

figure 43.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$  Ω


$T_j$ : — 25 °C  
— 125 °C

figure 42.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 8$  A


$T_j$ : — 25 °C  
— 125 °C

figure 44.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 8$  A

$T_j$ : — 25 °C  
— 125 °C




Vincotech

10-FZ127PA008SC-L156E08  
datasheet

## Brake Switching Characteristics

figure 45. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 32$   $\Omega$

$T_j$ : 25 °C  
125 °C

figure 46. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_C = 8$  A

$T_j$ : 25 °C  
125 °C

figure 47. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At  $T_j = 125$  °C  
 $R_{gon} = 32$   $\Omega$   
 $R_{goff} = 32$   $\Omega$



Vincotech

## Switching Definitions

figure 48. IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 49. IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 50. IGBT

Turn-off Switching Waveforms & definition of  $t_f$





figure 51. IGBT

Turn-on Switching Waveforms & definition of  $t_r$





Vincotech

## Switching Definitions

figure 52.

FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$





figure 53.

FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )






Vincotech

# 10-FZ127PA008SC-L156E08

datasheet

| Ordering Code                            |                             |
|------------------------------------------|-----------------------------|
| Version                                  | Ordering Code               |
| Without thermal paste                    | 10-FZ127PA008SC-L156E08     |
| With thermal paste (5,2 W/mK, PTM6000HV) | 10-FZ127PA008SC-L156E08-/7/ |
| With thermal paste (3,4 W/mK, PSX-P7)    | 10-FZ127PA008SC-L156E08-/3/ |

| Marking    |                               |            |           |           |       |        |
|------------|-------------------------------|------------|-----------|-----------|-------|--------|
| Text       | Name                          |            | Date code | UL & VIN  | Lot   | Serial |
|            | NN-NNNNNNNNNNNNNN-<br>TTTTTVV |            | WWYY      | UL VIN    | LLLLL | SSSS   |
| Datamatrix | Type&Ver                      | Lot number | Serial    | Date code |       |        |
|            | TTTTTVV                       | LLLLL      | SSSS      | WWYY      |       |        |

| Outline                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |      |      |          |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|----------|-----|---|---|----------|---|---|------|------|---|---|------|------|---|------|------|-----|---|------|------|-----|---|------|------|-----|---|------|------|-----|---|------|------|-----|---|------|------|-----|---|------|----|------|----|------|---|-----|----|------|---|---|----|----|---|-----|----|----|---|---|----|------|---|-----|----|------|---|---|----|---|---|------|----|---|---|------|----|-----|-----|------|----|---|----|------|
| <p>Pin table [mm]</p> <table><tr><th>Pin</th><th>X</th><th>Y</th><th>Function</th></tr><tr><td>1</td><td>0</td><td>22,5</td><td>BRCE</td></tr><tr><td>2</td><td>3</td><td>22,5</td><td>BRCG</td></tr><tr><td>3</td><td>13,5</td><td>19,5</td><td>GI6</td></tr><tr><td>4</td><td>13,5</td><td>22,5</td><td>EI6</td></tr><tr><td>5</td><td>23,5</td><td>19,5</td><td>GI5</td></tr><tr><td>6</td><td>23,5</td><td>22,5</td><td>EI5</td></tr><tr><td>7</td><td>33,5</td><td>19,5</td><td>GI4</td></tr><tr><td>8</td><td>33,5</td><td>22,5</td><td>EI4</td></tr><tr><td>9</td><td>33,5</td><td>11</td><td>INV+</td></tr><tr><td>10</td><td>33,5</td><td>3</td><td>GI1</td></tr><tr><td>11</td><td>33,5</td><td>0</td><td>U</td></tr><tr><td>12</td><td>25</td><td>3</td><td>GI2</td></tr><tr><td>13</td><td>25</td><td>0</td><td>V</td></tr><tr><td>14</td><td>16,5</td><td>3</td><td>GI3</td></tr><tr><td>15</td><td>16,5</td><td>0</td><td>W</td></tr><tr><td>16</td><td>3</td><td>0</td><td>NTC1</td></tr><tr><td>17</td><td>0</td><td>0</td><td>NTC2</td></tr><tr><td>18</td><td>7,9</td><td>9,3</td><td>BRC+</td></tr><tr><td>19</td><td>0</td><td>11</td><td>INV+</td></tr></table> |      |      |          | Pin | X | Y | Function | 1 | 0 | 22,5 | BRCE | 2 | 3 | 22,5 | BRCG | 3 | 13,5 | 19,5 | GI6 | 4 | 13,5 | 22,5 | EI6 | 5 | 23,5 | 19,5 | GI5 | 6 | 23,5 | 22,5 | EI5 | 7 | 33,5 | 19,5 | GI4 | 8 | 33,5 | 22,5 | EI4 | 9 | 33,5 | 11 | INV+ | 10 | 33,5 | 3 | GI1 | 11 | 33,5 | 0 | U | 12 | 25 | 3 | GI2 | 13 | 25 | 0 | V | 14 | 16,5 | 3 | GI3 | 15 | 16,5 | 0 | W | 16 | 3 | 0 | NTC1 | 17 | 0 | 0 | NTC2 | 18 | 7,9 | 9,3 | BRC+ | 19 | 0 | 11 | INV+ |
| Pin                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | X    | Y    | Function |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0    | 22,5 | BRCE     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3    | 22,5 | BRCG     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 13,5 | 19,5 | GI6      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 13,5 | 22,5 | EI6      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 23,5 | 19,5 | GI5      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 23,5 | 22,5 | EI5      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 33,5 | 19,5 | GI4      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 33,5 | 22,5 | EI4      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 33,5 | 11   | INV+     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 33,5 | 3    | GI1      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 11                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 33,5 | 0    | U        |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 25   | 3    | GI2      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 13                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 25   | 0    | V        |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 16,5 | 3    | GI3      |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 16,5 | 0    | W        |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 16                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 3    | 0    | NTC1     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 17                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0    | 0    | NTC2     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 18                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 7,9  | 9,3  | BRC+     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| 19                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0    | 11   | INV+     |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |      |          |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |
| <p>Tolerance of pinpositions: ±0.5mm at the end of pins<br/>Dimension of coordinate axis is only offset without tolerance</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |      |      |          |     |   |   |          |   |   |      |      |   |   |      |      |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |      |     |   |      |    |      |    |      |   |     |    |      |   |   |    |    |   |     |    |    |   |   |    |      |   |     |    |      |   |   |    |   |   |      |    |   |   |      |    |     |     |      |    |   |    |      |




Vincotech

# 10-FZ127PA008SC-L156E08

datasheet

## Pinout



## Identification

| ID                           | Component  | Voltage | Current | Function                   | Comment |
|------------------------------|------------|---------|---------|----------------------------|---------|
| T14, T11, T15, T12, T16, T13 | IGBT       | 1200 V  | 8 A     | Inverter Switch            |         |
| DI1, DI4, DI2, DI5, DI3, DI6 | FWD        | 1200 V  | 10 A    | Inverter Diode             |         |
| TB                           | IGBT       | 1200 V  | 8 A     | Brake Switch               |         |
| DB2                          | FWD        | 1200 V  | 10 A    | Brake Diode                |         |
| DB1                          | FWD        | 1200 V  | 3 A     | Brake Sw. Protection Diode |         |
| NTC                          | Thermistor |         |         | Thermistor                 |         |





Vincotech

**10-FZ127PA008SC-L156E08**  
datasheet

| Packaging instruction                 |      |          |      |        |
|---------------------------------------|------|----------|------|--------|
| Standard packaging quantity (SPQ) 135 | >SPQ | Standard | <SPQ | Sample |

| Handling instruction                                                        |
|-----------------------------------------------------------------------------|
| Handling instructions for <i>flow 0</i> packages see vincotech.com website. |

| Package data                                                       |
|--------------------------------------------------------------------|
| Package data for <i>flow 0</i> packages see vincotech.com website. |

| Vincotech thermistor reference                                     |
|--------------------------------------------------------------------|
| See Vincotech thermistor reference table at vincotech.com website. |

| UL recognition and file number                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------|
| This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. |



| Document No.:                 | Date:       | Modification:                             | Pages |
|-------------------------------|-------------|-------------------------------------------|-------|
| 10-FZ127PA008SC-L156E08-D5-14 | 1 May. 2022 | New Datasheet format, module is unchanged |       |

#### DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

#### LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.