





flowPACK 2		1200 V / 75 A	
Topology features		flow 2 17 mm housing	
<ul style="list-style-type: none">• Kelvin Emitter for improved switching performance• Open Emitter configuration• Temperature sensor• 3xHalf Bridge• Tandem inverter diode			
Component features		Schematic	
<ul style="list-style-type: none">• Easy paralleling• Low turn-off losses• Low collector emitter saturation voltage• Positive temperature coefficient• Short tail current• Switching optimized for EMC			
Housing features			
<ul style="list-style-type: none">• Base isolation: Al₂O₃• Convex shaped baseplate for superior thermal contact• Cu baseplate• Thermo-mechanical push-and-pull force relief• Solder pin			
Target applications			
<ul style="list-style-type: none">• Servo Drives			
Types			
<ul style="list-style-type: none">• 30-F2126TA075M7-L288F74			



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	95	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	150	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	191	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1300	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	66	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	150	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	189	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			>12,7	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$		10	0,0075	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	15		75	25 125 150		1,55 1,7 1,75	1,9 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}	0	1200		25			100	μA
Gate-emitter leakage current	I_{GES}	20	0		25			500	nA
Internal gate resistance	r_g						4		Ω
Input capacitance	C_{ies}						16000		pF
Output capacitance	C_{oes}	0	10		25		480		pF
Reverse transfer capacitance	C_{res}						190		pF
Gate charge	Q_g	$V_{CC} = 600$ V	0/15		75	25		570	nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)					0,5		K/W
--	---------------	---------------------------------------	--	--	--	--	-----	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω	±15	600	75	25	259,15		ns
						125	267,6		
						150	269,04		
Rise time	t_r					25	46,65		
						125	55,36		
						150	58,1		
Turn-off delay time	$t_{d(off)}$					25	219,86		
						125	255,55		
		150	264,29						
Fall time	t_f			25	109,12			ns	
				125	132,4				
				150	143,75				
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 1,19$ μC $Q_{tFWD} = 2,99$ μC $Q_{tFWD} = 3,48$ μC				25	3,53		mWs
						125	5,37		
						150	5,77		
Turn-off energy (per pulse)	E_{off}					25	5,52		mWs
						125	7,4		
						150	7,89		



Vincotech

30-F2126TA075M7-L288F74
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		
Inverter Diode										
Static										
Forward voltage	V_F				75	25 125 150		3,36 3,11 3,04	3,84 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1300$ V				25			3,8	μA
Thermal										
Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,5		K/W
Dynamic										
Peak recovery current	I_{RM}					25 125 150		17,26 29,85 31,73		A
Reverse recovery time	t_{rr}					25 125 150		113,84 164,1 175,94		ns
Recovered charge	Q_r	$di/dt=1569$ A/μs $di/dt=1243$ A/μs $di/dt=1312$ A/μs	±15	600	75	25 125 150		1,19 2,99 3,48		μC
Reverse recovered energy	E_{rec}					25 125 150		0,464 1,12 1,31		mWs
Peak rate of fall of recovery current	$(di_r/dt)_{max}$					25 125 150		574,94 433,97 460,14		A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_{CE} [V]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R100	$A_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.




Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$

T_j : 25 °C
125 °C
150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ °C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$

T_j : 25 °C
125 °C
150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,497 K/W$

IGBT thermal model values


R (K/W)	τ (s)
4,16E-02	4,25E+00
5,55E-02	8,53E-01
1,25E-01	1,69E-01
2,12E-01	3,95E-02
4,29E-02	8,08E-03
2,08E-02	7,43E-04



Inverter Switch Characteristics

figure 5. IGBT


Safe operating area
 $I_C = f(V_{CE})$



$D =$ single pulse
 $T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge
 $V_{GE} = f(Q_g)$



$I_C = 75$ A
 $T_j = 25$ °C



Inverter Diode Characteristics

figure 7. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,501	K/W
FWD thermal model values		
R (K/W)	τ (s)	
2,98E-02	3,90E+00	
5,18E-02	7,55E-01	
1,94E-01	8,12E-02	
1,88E-01	1,55E-02	
3,77E-02	1,59E-03	




Thermistor Characteristics

figure 9. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






Inverter Switching Characteristics

figure 10. IGBT

Typical switching energy losses as a function of collector current
 $E = f(I_c)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{gon} =$	4	Ω		150 °C
$R_{goff} =$	4	Ω		

figure 11. IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor
 $E = f(R_g)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_c =$	75	A		150 °C

figure 12. FWD

Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{gon} =$	4	Ω		150 °C

figure 13. FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor
 $E_{rec} = f(R_g)$



With an inductive load at


$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_c =$	75	A		150 °C



Inverter Switching Characteristics

figure 14. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$

figure 15. IGBT


Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 75 \text{ A}$

figure 16. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \text{ } \Omega$
 $T_j:$ — 25 °C
— 125 °C
— 150 °C

figure 17. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$




With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 75 \text{ A}$
 $T_j:$ — 25 °C
— 125 °C
— 150 °C



Inverter Switching Characteristics

figure 18. FWD

Typical recovered charge as a function of collector current
 $Q_r = f(I_c)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 19. FWD

Typical recovered charge as a function of IGBT turn on gate resistor
 $Q_r = f(R_{gon})$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 20. FWD

Typical peak reverse recovery current as a function of collector current
 $I_{RM} = f(I_c)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 21. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor
 $I_{RM} = f(R_{gon})$



With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A


T_j : — 25 °C
 — 125 °C
 — 150 °C



Inverter Switching Characteristics

figure 22. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_C)$




With an inductive load at

$V_{CE} =$	600	V	$T_j =$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{gon} =$	4	Ω		150 °C

figure 23. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{gon})$




With an inductive load at

$V_{CE} =$	600	V	$T_j =$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_C =$	75	A		150 °C

figure 24. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Inverter Switching Definitions

figure 25. IGBT
Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 26. IGBT
Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})



figure 27. IGBT
Turn-off Switching Waveforms & definition of t_f





figure 28. IGBT
Turn-on Switching Waveforms & definition of t_r





Inverter Switching Definitions


figure 29. FWD

Turn-off Switching Waveforms & definition of t_{rr}



figure 30. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)







Vincotech

30-F2126TA075M7-L288F74
datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	30-F2126TA075M7-L288F74
With thermal paste (3,4 W/mK, PSX-P7)	30-F2126TA075M7-L288F74-/3/

Marking						
	Text	Name NN-NNNNNNNNNNNNNN- TTTTTVV	Date code WWYY	UL & VIN UL VIN	Lot LLLLL	Serial SSSS
	Datamatrix	Type&Ver TTTTTTVV	Lot number LLLLL	Serial SSSS	Date code WWYY	


Outline							
Pin table [mm]							
Pin	X	Y	Function	26	54,5	5,4	DC-3
1	0,9	0	S11	27	57,2	0	DC-3
2	0,9	3	G11	28	65,8	0	DC+3
3	3,9	0	DC-1	29	65,8	2,7	DC+3
4	3,9	2,7	DC-1	30	68,5	0	DC+3
5	3,9	5,4	DC-1	31	68,5	2,7	DC+3
6	6,6	0	DC-1	32	64,7	36	G16
7	15,2	0	DC+1	33	61,7	36	S16
8	15,2	2,7	DC+1	34	58,7	36	PH3
9	17,9	0	DC+1	35	56	36	PH3
10	17,9	2,7	DC+1	36	53,3	36	PH3
11	26,2	0	S13	37	50,6	36	PH3
12	26,2	3	G13	38	39,4	36	G14
13	29,2	0	DC-2	39	36,4	36	S14
14	29,2	2,7	DC-2	40	33,4	36	PH2
15	29,2	5,4	DC-2	41	30,7	36	PH2
16	31,9	0	DC-2	42	28	36	PH2
17	32,2	4,05	NTC	43	25,3	36	PH2
18	40,5	0	DC+2	44	14,1	36	G12
19	40,5	2,7	DC+2	45	11,1	36	S12
20	43,2	0	DC+2	46	8,1	36	PH1
21	43,2	2,7	DC+2	47	5,4	36	PH1
22	51,5	0	S15	48	2,7	36	PH1
23	51,5	3	G15	49	0	36	PH1
24	54,5	0	DC-3				
25	54,5	2,7	DC-3				



Tolerance of positions: ±0,05mm on the end of pins.
Dimension of cathode axis is only when without basecoat.



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	75 A	Inverter Switch	
D11-1, D11-2, D12-1, D12-2, D13-1, D13-2, D14-1, D14-2, D15-1, D15-2, D16-1, D16-2	FWD	1300 V	75 A	Inverter Diode	
NTC	Thermistor			Thermistor	




Packaging instruction				
Standard packaging quantity (SPQ) 36	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 2</i> packages see vincotech.com website.

Package data
Package data for <i>flow 2</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
30-F2126TA075M7-L288F74-D2-14	27 Apr. 2023	Change NTC	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.