



**MiniSKiiP® Twin 3**

**1200 V / 50 A**

**Topology features**

- Open Emitter configuration
- Temperature sensor
- 2xInverter
- Tandem diode
- HS IGBT4

**Component features**

- Easy paralleling
- High speed switching
- Low switching losses

**Housing features**

- Base isolation: Al<sub>2</sub>O<sub>3</sub>
- Easy assembly in one mounting step
- Flexible PCB design w/o pin holes
- Rugged solderless spring contacts


**Target applications**

- Embedded Drives
- Industrial Drives


**Types**

- 80-M312WPA050SH01-K889F45

**MiniSKiiP® 3 16 mm housing**



**Schematic**





Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>Inverter Switch</b>				
Collector-emitter voltage	$V_{CES}$		1200	V
Collector current (DC current)	$I_C$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	58	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{jmax}$	150	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	163	W
Gate-emitter voltage	$V_{GES}$		$\pm 20$	V
Short circuit ratings	$t_{SC}$	$V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	$\mu\text{s}$
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

<b>Inverter Diode</b>				
Peak repetitive reverse voltage	$V_{RRM}$		1300	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	40	A
Repetitive peak forward current	$I_{FRM}$	$t_p$ limited by $T_{jmax}$	100	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	109	W
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$

<b>Inverter Switch 2</b>				
Collector-emitter voltage	$V_{CES}$		1200	V
Collector current (DC current)	$I_C$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	58	A
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{jmax}$	150	A
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	163	W
Gate-emitter voltage	$V_{GES}$		$\pm 20$	V
Short circuit ratings	$t_{SC}$	$V_{GE} = 15\text{ V}$ , $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	$\mu\text{s}$
Maximum junction temperature	$T_{jmax}$		175	$^{\circ}\text{C}$



Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
<b>Inverter Diode 2</b>				
Peak repetitive reverse voltage	$V_{RRM}$		1200	V
Forward current (DC current)	$I_F$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	53	A
Surge (non-repetitive) forward current	$I_{FSM}$	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	270	A
Surge current capability	$I^2t$		365	A <sup>2</sup> s
Total power dissipation	$P_{tot}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	123	W
Maximum junction temperature	$T_{jmax}$		175	°C

## Module Properties

### Thermal Properties

Storage temperature	$T_{stg}$		-40...+125	°C
Operation temperature under switching condition	$T_{jop}$		-40...+( $T_{jmax} - 25$ )	°C

### Isolation Properties

Isolation voltage	$V_{isol}$	DC Test Voltage* $t_p = 2\text{ s}$	5500	V
Isolation voltage	$V_{isol}$	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance		With std lid For more informations see handling instructions	6,3	mm
Clearance		With std lid For more informations see handling instructions	6,3	mm
Comparative Tracking Index	CTI		≥ 600	

\*100 % tested in production



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GS}$ [V]	$V_{GE}$ [V]	$V_{DS}$ [V]	$V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	

#### Inverter Switch

##### Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0017	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		50	25 125 150	1,78	2,05 2,38 2,46	2,42 <sup>(1)</sup>	V
Collector-emitter cut-off current	$I_{CES}$		0	1200		25			1	μA
Gate-emitter leakage current	$I_{GES}$		20	0		25			120	nA
Internal gate resistance	$r_g$							4		Ω
Input capacitance	$C_{ies}$	$f = 1 \text{ Mhz}$	0	25		25		2770		pF
Reverse transfer capacitance	$C_{res}$							160		pF
Gate charge	$Q_g$		±15		0	25		380		nC

##### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5 \text{ W/mK}$ (HPTP)						0,58		K/W
--	---------------	--	--	--	--	--	--	------	--	-----

##### Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	±15	600	50	25		92,2		ns
Rise time	$t_r$					125		94,6	ns	
						150		96		
						25		20,2		
Turn-off delay time	$t_{d(off)}$					125		24	ns	
						150		24,6		
		25		184,6						
Fall time	$t_f$	125		236,4	ns					
		150		251,6						
		25		54,57						
Turn-on energy (per pulse)	$E_{on}$	$Q_{tFWD} = 1,61 \mu\text{C}$ $Q_{tFWD} = 3,04 \mu\text{C}$ $Q_{tFWD} = 3,55 \mu\text{C}$				25		2,05	mWs	
						125		2,9		
						150		3,13		
Turn-off energy (per pulse)	$E_{off}$					25		2,01	mWs	
						125		3,18		
						150		3,52		



Vincotech

**80-M312WPA050SH01-K889F45**  
datasheet

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		
<b>Inverter Diode</b>										
<b>Static</b>										
Forward voltage	$V_F$			50	25 125 150		3,23 3,09 3,03	3,84 <sup>(1)</sup>		V
Reverse leakage current	$I_R$	$V_T = 1300$ V			25			2,65		μA
<b>Thermal</b>										
Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)					0,87			K/W
<b>Dynamic</b>										
Peak recovery current	$I_{RM}$	$di/dt=2600$ A/μs $di/dt=2009$ A/μs $di/dt=3015$ A/μs	±15	600	50	25		32,13		A
Reverse recovery time	$t_{rr}$					125		39,68		
						150		43,22		
						25		108,64		
Recovered charge	$Q_r$					125		148,68		
						150		166,83		
		25		1,61						
Reverse recovered energy	$E_{rec}$	125		3,04						
		150		3,55						
		25		0,516						
Peak rate of fall of recovery current	$(di_r/dt)_{max}$	125		0,987						
		150		1,17						
		25		1844						
		125		155,86						
		150		170,69						



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		

#### Inverter Switch 2

##### Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0017	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		50	25 125 150	1,78	2,05 2,38	2,42 <sup>(1)</sup>	V
Collector-emitter cut-off current	$I_{CES}$		0	1200		25			1	μA
Gate-emitter leakage current	$I_{GES}$		20	0		25			120	nA
Internal gate resistance	$r_g$							4		Ω
Input capacitance	$C_{ies}$	$f = 1 \text{ Mhz}$	0	25		25		2770		pF
Reverse transfer capacitance	$C_{res}$							160		pF
Gate charge	$Q_g$		±15		0	25		380		nC

##### Thermal

Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5 \text{ W/mK}$ (HPTP)						0,58		K/W
--	---------------	--	--	--	--	--	--	------	--	-----

##### Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	±15	600	50	25		99		ns
Rise time	$t_r$					125		103	ns	
						150		103		
						25		22		
Turn-off delay time	$t_{d(off)}$					125		24	ns	
						150		25		
		25		185						
Fall time	$t_f$	125		245	ns					
		150		260						
		25		54,75						
Turn-on energy (per pulse)	$E_{on}$	$Q_{tFWD} = 3,7 \mu\text{C}$			mWs					
		$Q_{tFWD} = 7,15 \mu\text{C}$								
		$Q_{tFWD} = 8,84 \mu\text{C}$								
Turn-off energy (per pulse)	$E_{off}$				mWs					



Vincotech

80-M312WPA050SH01-K889F45  
datasheet

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GE}$ [V] $V_{GS}$ [V]	$V_{CE}$ [V] $V_{DS}$ [V] $V_F$ [V]	$I_C$ [A] $I_D$ [A] $I_F$ [A]	$T_j$ [°C]	Min	Typ	Max		
<b>Inverter Diode 2</b>										
<b>Static</b>										
Forward voltage	$V_F$				50	25 125 150		2,22 2,31 2,21	2,54 <sup>(1)</sup> 2,5 <sup>(1)</sup>	V
Reverse leakage current	$I_R$	$V_i = 1200$ V				25 150		4400	60 8800	μA
<b>Thermal</b>										
Thermal resistance junction to sink <sup>(2)</sup>	$R_{th(j-s)}$	$\lambda_{paste} = 2,5$ W/mK (HPTP)						0,77		K/W
<b>Dynamic</b>										
Peak recovery current	$I_{RM}$					25 125 150		52,81 63,56 68,09		A
Reverse recovery time	$t_{rr}$					25 125 150		199,74 355,14 413,02		ns
Recovered charge	$Q_r$	$di/dt=2640$ A/μs $di/dt=2128$ A/μs $di/dt=2300$ A/μs	±15	600	50	25 125 150		3,7 7,15 8,84		μC
Reverse recovered energy	$E_{rec}$					25 125 150		1,33 2,72 3,42		mWs
Peak rate of fall of recovery current	$(di_r/dt)_{max}$					25 125 150		2544 1714 1531		A/μs



Vincotech

### Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		$V_{GS}$ [V]	$V_{GE}$ [V]	$V_{DS}$ [V]	$V_{CE}$ [V]	$I_D$ [A]	$I_C$ [A]	$T_j$ [°C]	Min	

### Thermistor

#### Static

Rated resistance	$R$					25		1		kΩ
Deviation of R100	$A_{R/R}$	$R_{100} = 1670 \Omega$				100	-2		2	%
Maximum Current	$I_{max}$							3		mA
Power dissipation constant	$d$					25		0,76		mW/K
A-value	$A$							$7,635 \times 10^{-3}$		1/K
B-value	$B$							$1,73 \times 10^{-5}$		1/K <sup>2</sup>
Vincotech Thermistor Reference									E	

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.




## Inverter Switch Characteristics

**figure 1.** IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_j:$  — 25 °C  
 — 125 °C  
 — 150 °C

**figure 2.** IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_j = 150 \text{ °C}$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

**figure 3.** IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_j:$  — 25 °C  
 — 125 °C  
 — 150 °C

**figure 4.** IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0,582 \text{ K/W}$   
 IGBT thermal model values  

R (K/W)	$\tau$ (s)
4,36E-02	3,29E+00
7,77E-02	5,45E-01
3,13E-01	8,58E-02
1,16E-01	2,13E-02
3,15E-02	1,87E-03




### Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$  single pulse  
 $T_s = 80 \text{ } ^\circ\text{C}$   
 $V_{GE} = 15 \text{ V}$   
 $T_j = T_{jmax}$



### Inverter Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0,871 \text{ K/W}$   
 FWD thermal model values

R (K/W)	$\tau$ (s)
5,56E-02	2,54E+00
1,83E-01	3,24E-01
4,21E-01	4,60E-02
1,66E-01	7,54E-03
4,56E-02	6,91E-04




## Inverter Switch 2 Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C

figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_j = 150 \text{ }^\circ C$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C

figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0,582 \text{ K/W}$   
IGBT thermal model values  

R (K/W)	$\tau$ (s)
4,36E-02	3,29E+00
7,77E-02	5,45E-01
3,13E-01	8,58E-02
1,16E-01	2,13E-02
3,15E-02	1,87E-03




### Inverter Switch 2 Characteristics

figure 12. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$  single pulse  
 $T_s = 80 \text{ } ^\circ\text{C}$   
 $V_{CE} = 15 \text{ V}$   
 $T_j = T_{jmax}$



## Inverter Diode 2 Characteristics

figure 13. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 14. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 0,77$  K/W  
 FWD thermal model values

$R$ (K/W)	$\tau$ (s)
6,81E-02	2,32E+00
1,41E-01	2,74E-01
4,03E-01	6,14E-02
1,01E-01	8,37E-03
5,84E-02	9,85E-04




## Thermistor Characteristics

figure 15. Thermistor

Typical PTC characteristic as function of temperature

$$R_T = f(T)$$






## Inverter Switching Characteristics

**figure 16.** IGBT

Typical switching energy losses as a function of collector current  
 $E = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	$T_j: 125$ °C
$R_{g(on)} = 8$ Ω	$T_j: 150$ °C
$R_{g(off)} = 8$ Ω	

**figure 17.** IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor  
 $E = f(R_g)$




With an inductive load at

$V_{CE} = 600$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	$T_j: 125$ °C
$I_c = 50$ A	$T_j: 150$ °C

**figure 18.** FWD

Typical reverse recovered energy loss as a function of collector current  
 $E_{rec} = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	$T_j: 125$ °C
$I_{c(on)} = 8$ A	$T_j: 150$ °C

**figure 19.** FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at


$V_{CE} = 600$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	$T_j: 125$ °C
$I_c = 50$ A	$T_j: 150$ °C



## Inverter Switching Characteristics

**figure 20.** IGBT


Typical switching times as a function of collector current  
 $t = f(I_c)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{g(on)} = 8 \text{ } \Omega$   
 $R_{g(off)} = 8 \text{ } \Omega$

**figure 21.** IGBT


Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

**figure 22.** FWD


Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_c)$



With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{g(on)} = 8 \text{ } \Omega$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C

**figure 23.** FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{g(on)})$



With an inductive load at  
 $V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C




## Inverter Switching Characteristics

**figure 24.** FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 8 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 25.** FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 26.** FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 8 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 27.** FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics

**figure 28.** FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 8 \ \Omega$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

**figure 29.** FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ : — 25 °C  
 — 125 °C  
 — 150 °C

**figure 30.** IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$




At  $T_j = 150 \text{ °C}$   
 $R_{gon} = 8 \ \Omega$   
 $R_{goff} = 8 \ \Omega$



## Inverter Switching Characteristics 2

**figure 31.** IGBT

Typical switching energy losses as a function of collector current  
 $E = f(I_c)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{g(on)} =$	8	Ω		150 °C
$R_{g(off)} =$	8	Ω		

**figure 32.** IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor  
 $E = f(R_g)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_c =$	50	A		150 °C

**figure 33.** FWD

Typical reverse recovered energy loss as a function of collector current  
 $E_{rec} = f(I_c)$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$R_{g(on)} =$	8	Ω		150 °C

**figure 34.** FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at


$V_{CE} =$	600	V	$T_j:$	25 °C
$V_{GE} =$	±15	V		125 °C
$I_c =$	50	A		150 °C



## Inverter Switching Characteristics 2

**figure 35.** IGBT

Typical switching times as a function of collector current  
 $t = f(I_c)$




With an inductive load at

$T_j = 150$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 8$   $\Omega$   
 $R_{goff} = 8$   $\Omega$

**figure 36.** IGBT

Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$




With an inductive load at

$T_j = 150$  °C  
 $V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 50$  A

**figure 37.** FWD

Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_c)$




With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 8$   $\Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 38.** FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 50$  A

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C




## Inverter Switching Characteristics 2

figure 39. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 8 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

figure 40. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

figure 41. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 8 \ \Omega$

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

figure 42. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics 2

**figure 43.** FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $R_{gon} = 8$   $\Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 44.** FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 600$  V  
 $V_{GE} = \pm 15$  V  
 $I_c = 50$  A

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 45.** IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$



At  $T_j = 150$  °C  
 $R_{gon} = 8$   $\Omega$   
 $R_{goff} = 8$   $\Omega$



## Switching Definitions

figure 46. IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 47. IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 48. IGBT

Turn-off Switching Waveforms & definition of  $t_f$





figure 49. IGBT

Turn-on Switching Waveforms & definition of  $t_r$





### Switching Definitions

figure 50. FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$





figure 51. FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )






Vincotech

Ordering Code	
Version	Ordering Code
With std lid (6.5mm height) + no thermal grease	80-M312WPA050SH01-K889F45-/0A/
With thin lid (2.8mm height) + no thermal grease	80-M312WPA050SH01-K889F45-/0B/
With std lid (6.5mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M312WPA050SH01-K889F45-/1A/
With thin lid (2.8mm height) + thermal grease (0,8 W/mK, P12, silicone-based)	80-M312WPA050SH01-K889F45-/1B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M312WPA050SH01-K889F45-/4A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, TG20032, silicone-free)	80-M312WPA050SH01-K889F45-/4B/
With std lid (6.5mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M312WPA050SH01-K889F45-/5A/
With thin lid (2.8mm height) + thermal grease (2,5 W/mK, HPTP, silicone-based)	80-M312WPA050SH01-K889F45-/5B/

Marking						
Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTTVV		WWYY	UL VIN	LLLLL
Datamatrix		Type&Ver TTTTTTVV	Lot number LLLLL	Serial SSSS	Date code WWYY	

**Outline**


Pin table [mm]							
Pin	X	Y	Function	45	not assembled		
1	15,83	-25,3	+DC	46	-29,18	8,74	L3
2	15,83	-6,4	G11	47	-29,18	11,94	G5
3	15,83	-3,2	E11	48	-32,82	8,74	L3
4	15,83	0	L3'	49	not assembled		
5	15,83	3,2	L3'	50	-35,68	22,1	-DC/W
6	not assembled			51	-35,68	25,3	-DC/V
7	15,83	15,7	-DC/W'	52	-36,58	-25,3	+DC
8	15,83	18,9	-DC/W'	53	-36,58	-22,1	+DC
9	15,83	22,1	E12	54	not assembled		
10	15,83	25,3	G12	55	not assembled		
11	8,13	-25,3	+DC	56	not assembled		
12	not assembled			57	-36,58	-6,1	L2
13	8,13	22,1	-DC/V'	58	-39,32	15,7	T-
14	8,13	25,3	E10	59	-39,32	18,9	T+
15	not assembled			60	-39,32	22,1	-DC/W
16	1,82	-12,18	G9	61	-39,32	25,3	-DC/V
17	1,82	-8,98	E9	62	not assembled		
18	1,82	-5,79	L2'	63	not assembled		
19	0,43	22,1	-DC/V'	64	not assembled		
20	0,43	25,3	G10	65	-40,22	-12,5	G3
21	not assembled			66	-40,22	-9,3	E3
22	not assembled			67	-40,22	-6,09	L2
23	not assembled			68	-50,18	-25,3	L1
24	not assembled			69	not assembled		
25	-1,82	-5,79	L2'	70	not assembled		
26	not assembled			71	not assembled		
27	-7,27	22,1	-DC/U'	72	not assembled		
28	-7,27	25,3	E8	73	not assembled		
29	-14,97	22,1	-DC/U'	74	not assembled		
30	-14,97	25,3	G8	75	-50,18	9,5	-DC/U
31	not assembled			76	not assembled		
32	not assembled			77	not assembled		
33	not assembled			78	-53,82	-25,3	L1
34	-16,05	-5,42	L1'	79	-53,82	-22,1	G1
35	-19,22	-25,3	+DC	80	-53,82	-18,9	E1
36	not assembled			81	not assembled		
37	-19,7	-11,82	G7	82	not assembled		
38	-19,7	-8,62	E7	83	not assembled		
39	-19,7	-5,42	L1'	84	-53,82	3,1	G2
40	not assembled			85	-53,82	6,3	E2
41	not assembled			86	-53,82	9,5	-DC/U
42	-22,67	22,1	E6	87	-53,82	22,1	E4
43	-22,67	25,3	G6	88	-53,82	25,3	G4
44	not assembled						



Pad positions refers to center point. For more informations on pad design please see package data



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T2, T1, T4, T3, T6, T5	IGBT	1200 V	50 A	Inverter Switch	
D1, D2, D3, D4, D5, D6	FWD	1300 V	50 A	Inverter Diode	
T8, T7, T10, T9, T12, T11	IGBT	1200 V	50 A	Inverter Switch 2	
D7, D8, D9, D10, D11, D12	FWD	1200 V	50 A	Inverter Diode 2	
Rt	Thermistor			Thermistor	



Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 48	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for MiniSKiiP® 3 packages see vincotech.com website.

Package data
Package data for MiniSKiiP® 3 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
80-M312WPA050SH01-K889F45-D2-14	16 Dec. 2022	New datasheet format, module is unchanged	

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.