



flowNPC S3 split

950 V / 600 A

Features

- High power low inductive package
- Improved Rth with AlN DCB
- Integrated NTC

Target applications

- Solar Inverters

Types

- B0-SL10NIB600S702-PA29F78Z
- B0-SL10NIC600S702-PA39F78Z

flow S3 12 mm housing




PA29F78Z




PA39F78Z

Schematic



PA29F78Z



PA39F78Z



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Buck Switch				
Collector-emitter voltage	V_{CES}		950	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	444	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	1200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	864	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C
Buck Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	171	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	728	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 25\text{ °C}$	1040	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	432	W
Maximum junction temperature	T_{jmax}		175	°C
Buck Sw. Protection Diode				
Peak repetitive reverse voltage	V_{RRM}		950	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	77	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	160	W
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Boost Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	528	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	1200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	981	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	9,5	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Boost Diode

Peak repetitive reverse voltage	V_{RRM}		950	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	209	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	600	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	413	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Boost Sw. Inv. Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	220	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	450	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	390	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Boost Sw. Protection Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	40	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	170	A
Surge current capability	I^2t		145	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	113	W
Maximum junction temperature	T_{jmax}		175	°C

Boost D. Protection Diode

Peak repetitive reverse voltage	V_{RRM}		950	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	77	A
Repetitive peak forward current	I_{ERM}	t_p limited by T_{jmax}	200	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	160	W
Maximum junction temperature	T_{jmax}		175	°C

Capacitor (DC)

Maximum DC voltage	V_{MAX}		1000	V
Operation Temperature	T_{op}		-55 ... 125	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance		B0-SL10NIB600S702-PA29F78Z	>12,7	mm
		B0-SL10NIC600S702-PA39F78Z	9,93	
Clearance		B0-SL10NIB600S702-PA29F78Z	11,58	mm
		B0-SL10NIC600S702-PA39F78Z	8,06	
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,00975	25	4,35	5,1	5,85	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		600	25 125 150		1,82 2,07 2,13	2,25 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	950		25			12	μA
Gate-emitter leakage current	I_{GES}		20	0		25			300	nA
Internal gate resistance	r_g							0,5		Ω
Input capacitance	C_{ies}							37800		pF
Output capacitance	C_{oes}	$f = 100$ kHz	0	25		25		810		pF
Reverse transfer capacitance	C_{res}							120		pF
Gate charge	Q_g		±15		0	25		1350		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,11		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$					25 125 150		209,99 213,38 214,94		ns
Rise time	t_r					25 125 150		33,27 36,25 36,92		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		177,2 212,09 222,85		ns
Fall time	t_f					25 125 150		24,57 44,28 51,32		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 0,915$ μC $Q_{tFWD} = 0,935$ μC $Q_{tFWD} = 0,906$ μC				25 125 150		11,85 12,1 11,86		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		9,86 14,73 16,11		mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		
Buck Diode										
Static										
Forward voltage	V_F			160	25 125 150		1,72 2,17 2,32	1,8 ⁽¹⁾		V
Reverse leakage current	I_R	$V_r = 1200$ V			25		280	1600		μA
Thermal										
Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)					0,22			K/W
Dynamic										
Peak recovery current	I_{RRM}	$di/dt=8461$ A/μs $di/dt=6891$ A/μs $di/dt=9642$ A/μs	±15	600	355	25		71		A
						125		73,27		
						150		71,69		
Reverse recovery time	t_{rr}					25		21,99		
						125		22,14		ns
						150		21,83		
Recovered charge	Q_r					25		0,915		μC
						125		0,935		
						150		0,906		
Reverse recovered energy	E_{rec}					25		0,175		mWs
						125		0,188		
						150		0,184		
Peak rate of fall of recovery current	$(di_r/dt)_{max}$					25		9317,6		A/μs
						125		10781,52		
						150		10493,8		



Vincotech

B0-SL10NIB600S702-PA29F78Z
B0-SL10NIC600S702-PA39F78Z
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_F [V]	I_D [A] I_F [A]	T_j [°C]	Min	Typ	

Buck Sw. Protection Diode

Static

Forward voltage	V_F				100	25 125 150	2,1	2,64 2,44 2,36	2,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 950$ V				25			4	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,59		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_C [A]	T_j [°C]	Min	Typ	Max	

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			10	0,06	25	5,4	6	6,6	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		600	25 125 150		1,69 1,88 1,93	1,85 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			300	μA
Gate-emitter leakage current	I_{GES}		20	0		25			1500	nA
Internal gate resistance	r_g							0,667		Ω
Input capacitance	C_{ies}							111000		pF
Output capacitance	C_{oes}		0	10		25		3300		pF
Reverse transfer capacitance	C_{res}							1260		pF
Gate charge	Q_g	$V_{CC} = 600$ V	15		600	25		3600		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,1		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	-----	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$					25 125 150		579,15 583,32 587		ns
Rise time	t_r					25 125 150		159,66 178,99 185,61		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		356,71 389,7 401,8		ns
Fall time	t_f					25 125 150		76,99 97,68 103,24		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 5$ μC $Q_{tFWD} = 14,99$ μC $Q_{tFWD} = 18,2$ μC				25 125 150		69,98 89,22 95,96		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		39,36 49,08 51,32		mWs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		
Boost Diode										
Static										
Forward voltage	V_F				300	25 125 150	2,1	2,59 2,43 2,37	2,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 950$ V				25			12	μA
Thermal										
Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,23		K/W
Dynamic										
Peak recovery current	I_{RRM}					25 125 150		65,6 113,82 120,13		A
Reverse recovery time	t_{rr}					25 125 150		169,26 278,24 317,94		ns
Recovered charge	Q_r	$di/dt=2823$ A/μs $di/dt=2590$ A/μs $di/dt=2276$ A/μs	±15	600	600	25 125 150		5 14,99 18,2		μC
Reverse recovered energy	E_{rec}					25 125 150		1,12 3,78 4,67		mWs
Peak rate of fall of recovery current	$(di_r/dt)_{max}$					25 125 150		722,67 604,7 472,81		A/μs



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Boost Sw. Inv. Diode

Static

Forward voltage	V_F				225	25 125 150	1,45	1,9 1,83 1,8	1,95 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			2,28	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,24		K/W
----------------------------------------------------	---------------	------------------------------------	--	--	--	--	--	------	--	-----

Boost Sw. Protection Diode

Static

Forward voltage	V_F				35	25 125 150		2,53 2,67 2,58	2,62 ⁽¹⁾ 2,62 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150			60 5500	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,84		K/W
----------------------------------------------------	---------------	------------------------------------	--	--	--	--	--	------	--	-----



Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Boost D. Protection Diode

Static

Forward voltage	V_F				100	25 125 150	2,1	2,64 2,44 2,36	2,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 950$ V				25			4	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,59		K/W
----------------------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Capacitor (DC)

Static

Capacitance	C	DC bias voltage = 0 V				25		10		nF
Tolerance							-5		5	%
Dissipation factor		$f = 1$ kHz				25		0,1		%

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	ΔR_{R}	$R_{100} = 1484$ Ω				100	-5		5	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. ± 1 %						3962		K
B-value	$B_{(25/100)}$	Tol. ± 1 %						4000		K
Vincotech Thermistor Reference									I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.




Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$

$T_j:$ — 25 °C
 — 125 °C
 — 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ °C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 24 V$

$T_j:$ — 25 °C
 — 125 °C
 — 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,11 \text{ K/W}$

IGBT thermal model values

R (K/W)	τ (s)
1,72E-02	3,12E+00
2,61E-02	9,92E-01
3,34E-02	1,78E-01
2,60E-02	2,52E-02
7,27E-03	1,28E-03




Vincotech

Buck Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse

$T_s = 80$ °C

$V_{GE} = 15$ V

$T_j = T_{jmax}$



Buck Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,22	K/W
FWD thermal model values		
R (K/W)	τ (s)	
3,69E-02	3,31E+00	
5,12E-02	6,84E-01	
7,45E-02	6,90E-02	
3,95E-02	1,11E-02	
1,79E-02	1,70E-03	



Buck Sw. Protection Diode Characteristics

figure 8. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 9. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,594	K/W
FWD thermal model values		
R (K/W)	τ (s)	
5,02E-02	2,46E+00	
7,95E-02	4,43E-01	
2,28E-01	5,90E-02	
1,50E-01	1,50E-02	
8,75E-02	1,73E-03	




Boost Switch Characteristics

figure 10. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 11. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ °C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 12. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 13. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,097 \text{ K/W}$
 IGBT thermal model values

R (K/W)	τ (s)
1,01E-02	3,90E+00
2,69E-02	9,57E-01
3,87E-02	1,31E-01
1,54E-02	2,17E-02
5,74E-03	9,87E-04




Vincotech

Boost Switch Characteristics

figure 14. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse

$T_s = 80$ °C

$V_{CE} = 15$ V

$T_j = T_{jmax}$



Boost Diode Characteristics

figure 15. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 16. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,23 \text{ K/W}$
 FWD thermal model values

R (K/W)	τ (s)
2,56E-02	2,90E+00
4,35E-02	5,53E-01
9,09E-02	6,81E-02
4,34E-02	1,43E-02
2,66E-02	1,41E-03



Boost Sw. Inv. Diode Characteristics

figure 17. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 18. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,244$ K/W
 FWD thermal model values

R (K/W)	τ (s)
3,51E-02	2,48E+00
5,14E-02	4,38E-01
9,82E-02	5,01E-02
3,42E-02	7,68E-03
2,47E-02	6,90E-04



Boost Sw. Protection Diode Characteristics

figure 19. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 20. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T	
$R_{th(j-s)} =$	0,843	K/W
FWD thermal model values		
R (K/W)	τ (s)	
9,03E-02	1,79E+00	
1,29E-01	1,94E-01	
3,56E-01	2,98E-02	
1,83E-01	3,56E-03	
8,48E-02	6,09E-04	



Boost D. Protection Diode Characteristics

figure 21. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 22. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,594 \text{ K/W}$
 FWD thermal model values

R (K/W)	τ (s)
5,02E-02	2,46E+00
7,95E-02	4,43E-01
2,28E-01	5,90E-02
1,50E-01	1,50E-02
8,75E-02	1,73E-03




Thermistor Characteristics

figure 23. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






Buck Switching Characteristics

figure 24. IGBT


Typical switching energy losses as a function of collector current
 $E = f(I_c)$



With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω
 $R_{goff} = 2$ Ω
 T_j : 25 °C, 125 °C, 150 °C

figure 25. IGBT


Typical switching energy losses as a function of gate resistor
 $E = f(R_g)$



With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 355$ A
 T_j : 25 °C, 125 °C, 150 °C

figure 26. FWD


Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$



With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω
 T_j : 25 °C, 125 °C, 150 °C

figure 27. FWD

Typical reverse recovered energy loss as a function of gate resistor
 $E_{rec} = f(R_g)$




With an inductive load at
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 355$ A
 T_j : 25 °C, 125 °C, 150 °C



Buck Switching Characteristics

figure 28. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \text{ } \Omega$
 $R_{g(off)} = 2 \text{ } \Omega$

figure 29. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 355 \text{ A}$

figure 30. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \text{ } \Omega$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C

figure 31. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{g(off)})$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 355 \text{ A}$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C




Buck Switching Characteristics

figure 32. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 2 \ \Omega$
 $T_j: 25 \text{ }^\circ\text{C}$
 $125 \text{ }^\circ\text{C}$
 $150 \text{ }^\circ\text{C}$

figure 33. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 355 \text{ A}$
 $T_j: 25 \text{ }^\circ\text{C}$
 $125 \text{ }^\circ\text{C}$
 $150 \text{ }^\circ\text{C}$

figure 34. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 2 \ \Omega$
 $T_j: 25 \text{ }^\circ\text{C}$
 $125 \text{ }^\circ\text{C}$
 $150 \text{ }^\circ\text{C}$

figure 35. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 355 \text{ A}$
 $T_j: 25 \text{ }^\circ\text{C}$
 $125 \text{ }^\circ\text{C}$
 $150 \text{ }^\circ\text{C}$



Buck Switching Characteristics

figure 36. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$R_{g\text{on}} = 2$ Ω	$T_j = 150$ °C

figure 37. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{g\text{off}})$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$I_C = 355$ A	$T_j = 150$ °C

figure 38. IGBT

Reverse bias safe operating area
 $I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{g\text{on}} = 2$ Ω
 $R_{g\text{off}} = 2$ Ω




Boost Switching Characteristics

figure 39. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \ \Omega$
 $R_{g(off)} = 2 \ \Omega$

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 40. IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 600 \text{ A}$

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 41. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \ \Omega$

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 42. FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 600 \text{ A}$


T_j : — 25 °C
 — 125 °C
 — 150 °C



Boost Switching Characteristics

figure 43. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \text{ } \Omega$
 $R_{g(off)} = 2 \text{ } \Omega$

figure 44. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 600 \text{ A}$

figure 45. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 2 \text{ } \Omega$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C

figure 46. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{g(off)})$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 600 \text{ A}$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C




Boost Switching Characteristics

figure 47. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 2$ Ω

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 48. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 600$ A

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 49. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 2$ Ω

T_j : — 25 °C
 — 125 °C
 — 150 °C

figure 50. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 600$ A


T_j : — 25 °C
 — 125 °C
 — 150 °C



Boost Switching Characteristics

figure 51. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 2$ Ω

T_j : 25 °C
 125 °C
 150 °C

figure 52. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 600$ A

T_j : 25 °C
 125 °C
 150 °C

figure 53. IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$



At $T_j = 150$ °C
 $R_{goff} = 2$ Ω
 $R_{goff} = 2$ Ω



Switching Definitions

figure 54. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 55. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 56. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 57. IGBT

Turn-on Switching Waveforms & definition of t_r





Switching Definitions

figure 58. FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 59. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

Ordering Code	
Version	Ordering Code
With thermal paste (5,2 W/mK, PTM6000HV)	B0-SL10NIB600S702-PA29F78Z-/7/

Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNNNN- TTTTIV	WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code	
		TTTTIV	LLLLL	SSSS	WWYY	

Outline																																																																																																																																																																																							
B0-SL10NIB600S702-PA29F78Z																																																																																																																																																																																							
<table border="1"> <thead> <tr> <th colspan="4">Pin table [mm]</th> </tr> <tr> <th>Pin</th> <th>X</th> <th>Y</th> <th>Function</th> </tr> </thead> <tbody> <tr><td>1</td><td>6,2</td><td>49,4</td><td>Therm1</td></tr> <tr><td>2</td><td>0</td><td>49,4</td><td>Therm2</td></tr> <tr><td>3</td><td>0,3</td><td>5,4</td><td>DC+</td></tr> <tr><td>4</td><td>3</td><td>5,4</td><td>DC+</td></tr> <tr><td>5</td><td>5,7</td><td>5,4</td><td>DC+</td></tr> <tr><td>6</td><td>8,4</td><td>5,4</td><td>DC+</td></tr> <tr><td>7</td><td>0,3</td><td>2,7</td><td>DC+</td></tr> <tr><td>8</td><td>3</td><td>2,7</td><td>DC+</td></tr> <tr><td>9</td><td>5,7</td><td>2,7</td><td>DC+</td></tr> <tr><td>10</td><td>0,3</td><td>0</td><td>DC+</td></tr> <tr><td>11</td><td>3</td><td>0</td><td>DC+</td></tr> <tr><td>12</td><td>5,7</td><td>0</td><td>DC+</td></tr> <tr><td>13</td><td>14,5</td><td>0</td><td>GND</td></tr> <tr><td>14</td><td>17,2</td><td>0</td><td>GND</td></tr> <tr><td>15</td><td>19,9</td><td>0</td><td>GND</td></tr> <tr><td>16</td><td>22,6</td><td>0</td><td>GND</td></tr> <tr><td>17</td><td>31,8</td><td>0</td><td>GND</td></tr> <tr><td>18</td><td>34,5</td><td>0</td><td>GND</td></tr> <tr><td>19</td><td>37,2</td><td>0</td><td>GND</td></tr> <tr><td>20</td><td>39,9</td><td>0</td><td>GND</td></tr> <tr><td>21</td><td>48,7</td><td>0</td><td>DC-</td></tr> <tr><td>22</td><td>51,4</td><td>0</td><td>DC-</td></tr> <tr><td>23</td><td>51,4</td><td>2,7</td><td>DC-</td></tr> <tr><td>24</td><td>51,4</td><td>5,4</td><td>DC-</td></tr> <tr><td>25</td><td>51,4</td><td>8,1</td><td>DC-</td></tr> <tr><td>26</td><td>51,4</td><td>10,8</td><td>DC-</td></tr> <tr><td>27</td><td>51,4</td><td>13,5</td><td>DC-</td></tr> <tr><td>28</td><td>40,6</td><td>43,7</td><td>Ph</td></tr> <tr><td>29</td><td>37,9</td><td>43,7</td><td>Ph</td></tr> <tr><td>30</td><td>35,2</td><td>43,7</td><td>Ph</td></tr> <tr><td>31</td><td>40,6</td><td>46,4</td><td>Ph</td></tr> <tr><td>32</td><td>37,9</td><td>46,4</td><td>Ph</td></tr> <tr><td>33</td><td>35,2</td><td>46,4</td><td>Ph</td></tr> <tr><td>34</td><td>40,6</td><td>49,1</td><td>Ph</td></tr> <tr><td>35</td><td>37,9</td><td>49,1</td><td>Ph</td></tr> <tr><td>36</td><td>35,2</td><td>49,1</td><td>Ph</td></tr> <tr><td>37</td><td>32,5</td><td>49,1</td><td>Ph</td></tr> <tr><td>38</td><td>12,4</td><td>26,95</td><td>G11</td></tr> <tr><td>39</td><td>16,1</td><td>26,95</td><td>S11</td></tr> <tr><td>40</td><td>32,95</td><td>27,3</td><td>G13</td></tr> <tr><td>41</td><td>36,65</td><td>27,3</td><td>S13</td></tr> <tr><td>42</td><td>21,05</td><td>49,1</td><td>TM11</td></tr> <tr><td>43</td><td>51,4</td><td>33,6</td><td>TM15</td></tr> </tbody> </table>				Pin table [mm]				Pin	X	Y	Function	1	6,2	49,4	Therm1	2	0	49,4	Therm2	3	0,3	5,4	DC+	4	3	5,4	DC+	5	5,7	5,4	DC+	6	8,4	5,4	DC+	7	0,3	2,7	DC+	8	3	2,7	DC+	9	5,7	2,7	DC+	10	0,3	0	DC+	11	3	0	DC+	12	5,7	0	DC+	13	14,5	0	GND	14	17,2	0	GND	15	19,9	0	GND	16	22,6	0	GND	17	31,8	0	GND	18	34,5	0	GND	19	37,2	0	GND	20	39,9	0	GND	21	48,7	0	DC-	22	51,4	0	DC-	23	51,4	2,7	DC-	24	51,4	5,4	DC-	25	51,4	8,1	DC-	26	51,4	10,8	DC-	27	51,4	13,5	DC-	28	40,6	43,7	Ph	29	37,9	43,7	Ph	30	35,2	43,7	Ph	31	40,6	46,4	Ph	32	37,9	46,4	Ph	33	35,2	46,4	Ph	34	40,6	49,1	Ph	35	37,9	49,1	Ph	36	35,2	49,1	Ph	37	32,5	49,1	Ph	38	12,4	26,95	G11	39	16,1	26,95	S11	40	32,95	27,3	G13	41	36,65	27,3	S13	42	21,05	49,1	TM11	43	51,4	33,6	TM15
Pin table [mm]																																																																																																																																																																																							
Pin	X	Y	Function																																																																																																																																																																																				
1	6,2	49,4	Therm1																																																																																																																																																																																				
2	0	49,4	Therm2																																																																																																																																																																																				
3	0,3	5,4	DC+																																																																																																																																																																																				
4	3	5,4	DC+																																																																																																																																																																																				
5	5,7	5,4	DC+																																																																																																																																																																																				
6	8,4	5,4	DC+																																																																																																																																																																																				
7	0,3	2,7	DC+																																																																																																																																																																																				
8	3	2,7	DC+																																																																																																																																																																																				
9	5,7	2,7	DC+																																																																																																																																																																																				
10	0,3	0	DC+																																																																																																																																																																																				
11	3	0	DC+																																																																																																																																																																																				
12	5,7	0	DC+																																																																																																																																																																																				
13	14,5	0	GND																																																																																																																																																																																				
14	17,2	0	GND																																																																																																																																																																																				
15	19,9	0	GND																																																																																																																																																																																				
16	22,6	0	GND																																																																																																																																																																																				
17	31,8	0	GND																																																																																																																																																																																				
18	34,5	0	GND																																																																																																																																																																																				
19	37,2	0	GND																																																																																																																																																																																				
20	39,9	0	GND																																																																																																																																																																																				
21	48,7	0	DC-																																																																																																																																																																																				
22	51,4	0	DC-																																																																																																																																																																																				
23	51,4	2,7	DC-																																																																																																																																																																																				
24	51,4	5,4	DC-																																																																																																																																																																																				
25	51,4	8,1	DC-																																																																																																																																																																																				
26	51,4	10,8	DC-																																																																																																																																																																																				
27	51,4	13,5	DC-																																																																																																																																																																																				
28	40,6	43,7	Ph																																																																																																																																																																																				
29	37,9	43,7	Ph																																																																																																																																																																																				
30	35,2	43,7	Ph																																																																																																																																																																																				
31	40,6	46,4	Ph																																																																																																																																																																																				
32	37,9	46,4	Ph																																																																																																																																																																																				
33	35,2	46,4	Ph																																																																																																																																																																																				
34	40,6	49,1	Ph																																																																																																																																																																																				
35	37,9	49,1	Ph																																																																																																																																																																																				
36	35,2	49,1	Ph																																																																																																																																																																																				
37	32,5	49,1	Ph																																																																																																																																																																																				
38	12,4	26,95	G11																																																																																																																																																																																				
39	16,1	26,95	S11																																																																																																																																																																																				
40	32,95	27,3	G13																																																																																																																																																																																				
41	36,65	27,3	S13																																																																																																																																																																																				
42	21,05	49,1	TM11																																																																																																																																																																																				
43	51,4	33,6	TM15																																																																																																																																																																																				
<p style="text-align: right; font-size: small;">Tolerance of positions: ±0,05mm at the end of pins Dimension of constructs also in only of each tolerance</p>																																																																																																																																																																																							



Vincotech

Ordering Code	
Version	Ordering Code
With thermal paste (5,2 W/mK, PTM6000HV)	B0-SL10NIC600S702-PA39F78Z-/7/


Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTTVV	WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code	
		TTTTTTVV	LLLLL	SSSS	WWYY	

Pin table [mm]				Outline	
Pin	X	Y	Function	<p align="center">B0-SL10NIC600S702-PA39F78Z</p> <p>Tolerance of positions: ±0.1mm at the end of pins. Dimension of conductive pins is only offset without tolerance.</p>	
1	51,45	49,45	Therm1		
2	46	49,45	Therm2		
3	21,8	49,1	Ph		
4	19,1	49,1	Ph		
5	16,4	49,1	Ph		
6	13,7	49,1	Ph		
7	11	49,1	Ph		
8	21,8	46,4	Ph		
9	19,1	46,4	Ph		
10	16,4	46,4	Ph		
11	13,7	46,4	Ph		
12	11	46,4	Ph		
13	0	25	DC+		
14	0	22,3	DC+		
15	0	19,6	DC+		
16	0	16,9	DC+		
17	0	14,2	DC+		
18	0	11,5	DC+		
19	0	8,8	DC+		
20	0	0	GND		
21	2,6	0	GND		
22	5,2	0	GND		
23	7,8	0	GND		
24	39	0	GND		
25	41,6	0	GND		
26	44,2	0	GND		
27	46,8	0	GND		
28	51,1	6,45	DC-		
29	48,4	9,15	DC-		
30	51,1	9,15	DC-		
31	51,1	11,85	DC-		
32	51,1	14,55	DC-		
33	51,1	17,25	DC-		
34	48,4	19,95	DC-		
35	51,1	19,95	DC-		
36	51,1	22,65	DC-		
37	51,1	25,35	DC-		
38	28,6	26,95	G14		
39	32,3	26,95	S14		
40	46,05	29,35	G12		
41	49,75	29,35	S12		
42	7,35	33,6	TM14		
43	32,3	49,1	TM12		



Vincotech

B0-SL10NIB600S702-PA29F78Z




Identification					
ID	Component	Voltage	Current	Function	Comment
T11	IGBT	950 V	600 A	Buck Switch	
D11	FWD	1200 V	160 A	Buck Diode	
D41	FWD	950 V	100 A	Buck Sw. Protection Diode	
T13	IGBT	1200 V	600 A	Boost Switch	
D13	FWD	950 V	300 A	Boost Diode	
D15	FWD	1200 V	225 A	Boost Sw. Inv. Diode	
D43	FWD	1200 V	35 A	Boost Sw. Protection Diode	
D45	FWD	950 V	100 A	Boost D. Protection Diode	
C10, C20	Capacitor	1000 V		Capacitor (DC)	
Rt	Thermistor			Thermistor	



Vincotech

B0-SL10NIC600S702-PA39F78Z



Identification					
ID	Component	Voltage	Current	Function	Comment
T12	IGBT	950 V	600 A	Buck Switch	
D12	FWD	1200 V	160 A	Buck Diode	
D42	FWD	950 V	100 A	Buck Sw. Protection Diode	
T14	IGBT	1200 V	600 A	Boost Switch	
D14	FWD	950 V	300 A	Boost Diode	
D16	FWD	1200 V	225 A	Boost Sw. Inv. Diode	
D44	FWD	1200 V	35 A	Boost Sw. Protection Diode	
D46	FWD	950 V	100 A	Boost D. Protection Diode	
C10, C20	Capacitor	1000 V		Capacitor (DC)	
Rt	Thermistor			Thermistor	



Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 45	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow</i> S3 packages see vincotech.com website.

Package data
Package data for <i>flow</i> S3 packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
B0-SL10NIB600S702-PA29F78Z-D1-14	23 Jul. 2021		
B0-SL10NIB600S702-PA29F78Z-D2-14	16 Jan. 2022	Dynamic measurements without connection of P/N	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.