





Vincotech

10-PY126TA050SH-L828F68Y

datasheet

flowPACK 1		1200 V / 50 A
Features • High speed IGBT4 • Tandem diodes for improved thermal performance • Integrated thermal sensor		flow 1 12mm housing 
Target applications • Embedded Drives • Industrial Drives		Schematic 
Types • 10-PY126TA050SH-L828F68Y		

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C		50	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	150	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	135	W
Gate-emitter voltage	V_{GES}		±20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$ $V_{ce} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	µs
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

10-PY126TA050SH-L828F68Y
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Inverter Diode				
Peak repetitive reverse voltage	V_{RRM}		1300	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	38	A
Repetitive peak forward current	I_{FRM}		100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	102	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance			7,9	mm
Comparative Tracking Index	CTI		> 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{GE} = V_{CE}$			0,0017	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	V_{CEsat}		15		50	25 125 150	1,78	2,04 2,38 2,46	2,42	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			1	μA
Gate-emitter leakage current	I_{GES}		20	0		25			120	nA
Internal gate resistance	r_g							4		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		2770		pF
Reverse transfer capacitance	C_{res}							160		

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,70		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	± 15	600	50	25 125 150		92 95 96		ns
Rise time	t_r					25 125 150		20 24 25		
Turn-off delay time	$t_{d(off)}$					25 125 150		185 236 252		
Fall time	t_f					25 125 150		55 87 90		
Turn-on energy (per pulse)	E_{on}					25 125 150		2,052 2,898 3,130		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		2,008 3,178 3,525		



Vincotech

10-PY126TA050SH-L828F68Y

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				50	25 125 150		3,23 3,09 3,03	3,54	V
Reverse leakage current	I_R			1300		25			2,65	μA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,93		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt = 2600 \text{ A/}\mu\text{s}$ $di/dt = 2009 \text{ A/}\mu\text{s}$ $di/dt = 3015 \text{ A/}\mu\text{s}$	± 15	600	50	25 125 150		32 40 43		A
Reverse recovery time	t_{rr}					25 125 150		109 149 167		ns
Recovered charge	Q_r					25 125 150		1,606 3,039 3,547		μC
Reverse recovered energy	E_{rec}					25 125 150		0,516 0,987 1,172		mWs
Peak rate of fall of recovery current	$(di_{rf}/dt)_{max}$					25 125 150		1844 156 171		A/μs

Thermistor

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		5		mW
Power dissipation constant						25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$				25		3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$				25		4000		K
Vincotech NTC Reference									I	



Vincotech


10-PY126TA050SH-L828F68Y datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (dotted blue line)
 $125 \text{ } ^\circ C$ (solid black line)
 $150 \text{ } ^\circ C$ (dashed red line)

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 100 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (dotted blue line)
 $125 \text{ } ^\circ C$ (solid black line)
 $150 \text{ } ^\circ C$ (dashed red line)

figure 4. IGBT

Transient thermal impedance as function of pulse duration

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,70 \text{ K/W}$
IGBT thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
9,44E-02	1,28E+00
1,86E-01	2,02E-01
3,33E-01	6,13E-02
5,71E-02	9,05E-03
3,26E-02	9,42E-04




Vincotech

Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse
 $T_s =$ 80 °C
 $V_{GE} =$ ±15 V
 $T_j =$ T_{jmax}



Vincotech

Inverter Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$




Thermistor Characteristics

figure 1. Thermistor

Typical NTC characteristic as a function of temperature

$$R = f(T)$$





Vincotech

10-PY126TA050SH-L828F68Y


datasheet

Inverter Switching Characteristics

figure 1. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V

$V_{GE} = \pm 15$ V

$R_{gon} = 8$ Ω

$R_{goff} = 8$ Ω

T_j :

25 °C


125 °C

150 °C

figure 2. IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V

$V_{GE} = \pm 15$ V

$I_c = 50$ A

T_j :

25 °C


125 °C

150 °C

figure 3. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V

$V_{GE} = \pm 15$ V

$R_{gon} = 8$ Ω

T_j :

25 °C


125 °C

150 °C

figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V

$V_{GE} = \pm 15$ V

$I_c = 50$ A

T_j :

25 °C

125 °C

150 °C



Vincotech

10-PY126TA050SH-L828F68Y


datasheet

Inverter Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 50$ A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 50$ A

T_j : 25 °C (dotted blue)
125 °C (solid black)
150 °C (dashed red)




Vincotech

Inverter Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C (blue dotted)
125 °C (black solid)
150 °C (red dashed)

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 50$ A

T_j : 25 °C (blue dotted)
125 °C (black solid)
150 °C (red dashed)

figure 11. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C (blue dotted)
125 °C (black solid)
150 °C (red dashed)

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 50$ A

T_j : 25 °C (blue dotted)
125 °C (black solid)
150 °C (red dashed)




Vincotech

10-PY126TA050SH-L828F68Y
datasheet

Inverter Switching Characteristics

figure 13. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $T_j = 25$ °C
 125 °C
 150 °C

figure 14. FWD

Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 50$ A
 $T_j = 25$ °C
 125 °C
 150 °C

figure 15. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At

$T_j = 125$ °C
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω



Vincotech


Inverter Switching Definitions

General conditions

T_j	=	125 °C
R_{gon}	=	8 Ω
R_{goff}	=	8 Ω

figure 1. IGBT


Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_{doff} =$	236	ns

figure 2. IGBT


Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_{don} =$	95	ns

figure 3. IGBT


Turn-off Switching Waveforms & definition of t_f



$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_f =$	87	ns

figure 4. IGBT

Turn-on Switching Waveforms & definition of t_r



$V_C(100\%) =$	600	V
$I_C(100\%) =$	50	A
$t_r =$	24	ns




Vincotech

Inverter Switching Characteristics

figure 5. FWD


Turn-off Switching Waveforms & definition of t_{rr}



$V_F(100\%) =$	600	V
$I_F(100\%) =$	50	A
$I_{RRM}(100\%) =$	40	A
$t_{rr} =$	149	ns

figure 6. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)



$I_F(100\%) =$	50	A
$Q_r(100\%) =$	3,04	μC



Vincotech

10-PY126TA050SH-L828F68Y

datasheet


Ordering Code & Marking							
Version			Ordering Code				
without thermal paste 12mm housing with Press-fit pins			10-PY126TA050SH-L828F68Y				
with thermal paste 12mm housing with Press-fit pins			10-PY126TA050SH-L828F68Y-/3/				
NN-NNNNNNNNNNNNNN TTTTTIV WWYY UL VIN LLLLL SSSS  	Text	Name		Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN-TTTTTIV		WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
		TTTTTIV	LLLLL	SSSS	WWYY		

Pin table				Outline			
Pin	X	Y	Functions				
1	52,6	0	DC-123				
2	49,9	0	DC-123				
3	42,65	0	G15				
4	39,65	0	S15				
5	35,15	0	Therm1				
6	28,4	0	Therm2				
7	24	0	G13				
8	21	0	S13				
9	12,2	0	G11				
10	9,2	0	S11				
11	2,7	0	DC-123				
12	0	0	DC-123				
13	0	14,65	DC+123				
14	2,7	14,65	DC+123				
15	0	28,6	Ph1				
16	2,7	28,6	Ph1				
17	5,4	28,6	Ph1				
18	9,6	28,6	S12				
19	12,6	28,6	G12				
20	19,6	28,6	Ph2				
21	22,3	28,6	Ph2				
22	25	28,6	Ph2				
23	29,7	28,6	S14				
24	32,7	28,6	G14				
25	39,7	28,6	S16				
26	42,7	28,6	G16				
27	47,2	28,6	Ph3				
28	49,9	28,6	Ph3				
29	52,6	28,6	Ph3				
30	52,6	14,65	DC+123				
31	49,9	14,65	DC+123				

Tolerance of pinpositions: ±0.5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	50 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1300 V	50 A	Inverter Diode	
Rt	NTC			Thermistor	



Vincotech

10-PY126TA050SH-L828F68Y
datasheet

Packaging instruction			
Standard packaging quantity (SPQ) 100	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow 1</i> packages see vincotech.com website.

Package data
Package data for <i>flow 1</i> packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-PY126TA050SH-L828F68Y-D1-14	26 Oct. 2018		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.