





Vincotech

flowCON 0	1600 V / 75 A
<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Features</p> <ul style="list-style-type: none"> Three-phase half-controlled rectifier </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Target applications</p> <ul style="list-style-type: none"> Industrial Drives Embedded Drives UPS </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Types</p> <ul style="list-style-type: none"> V23990-P640-H10-PM </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p style="text-align: center; background-color: #ccc; margin: 0;"><i>flow 0 17 mm housing</i></p>  </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; background-color: #ccc; margin: 0;">Schematic</p>  </div>

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Rectifier Diode				
Peak repetitive reverse voltage	V_{RRM}		1600	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	78	A
Surge (non-repetitive) forward current	I_{FSM}	50 Hz Single Half Sine Wave $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	740	A
Surge current capability	I_{Pt}		2740	A^2s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	88	W
Maximum junction temperature	T_{jmax}		150	$^{\circ}C$



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Rectifier Thyristor				
Repetitive peak reverse voltage	V_{RRM}		1600	V
Forward average current	I_{FAV}	sine, $d = 0,5$ $T_j = T_{jmax}$	53	A
Surge forward current	I_{FSM}	$t_p = 10\text{ ms}$ $T_j = 130\text{ °C}$	450	A
I^2t value	I^2t		1010	A ² s
Mean total power loss	$P_{tot(AV)}$	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	67	W
Maximum Junction Temperature	T_{jmax}		130	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...(T _{jmax} - 25)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance			min. 12,7	mm
Comparative Tracking Index	CTI		> 200	

*100 % tested in production



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max		

Rectifier Diode

Static

Forward voltage	V_F				80	25 125		1,18 1,15	1,23	V
Reverse leakage current	I_R			1600		25 150			50 1500	μ A

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,79		K/W
-------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Rectifier Thyristor

Static

Forward voltage	V_F				45	25 125		1,41 1,45		V
On-state threshold voltage	$V_{T(TO)}$				45	130			0,85	V
On-state slope resistance	r_T				45	130			7,9	m Ω
Critical rate of rise of off-state voltage	$(dv/dt)_{cr}$					130			50	V/ μ s
Critical rate of rise of on-state current	$(di_T/dt)_{cr}$					130			1000	A/ μ s
Circuit commutated turn-off time	t_q					130		150		μ s
Holding current	I_H					25			165	mA
Latching current	I_L					25			330	mA
Gate trigger voltage	V_{GT}					25			1,98	V
Gate trigger current	I_{GT}					25			100	mA
Gate non-trigger voltage	V_{GD}					130	0,25			V
Gate non-trigger current	I_{GD}					115	6			mA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,75		K/W
-------------------------------------	---------------	---------------------------------------	--	--	--	--	--	------	--	-----




Rectifier Diode Characteristics

figure 1. Rectifier Diode

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$ $T_j: 25 \text{ }^\circ\text{C}$ (blue dotted line) $125 \text{ }^\circ\text{C}$ (black solid line)

figure 2. Rectifier Diode

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,79 \text{ K/W}$

Diode thermal model values

R (K/W)	τ (s)
3,05E-02	5,20E+00
8,93E-02	9,97E-01
2,82E-01	1,58E-01
3,51E-01	5,43E-02
3,93E-02	2,64E-03



Rectifier Thyristor Characteristics

figure 1. Thyristor

Typical forward characteristics

$$I_F = f(V_F)$$





figure 2. Thyristor

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$




Thyristor thermal model values

R (K/W)	τ (s)
5,49E-02	3,07E+00
1,27E-01	4,52E-01
4,30E-01	9,34E-02
1,02E-01	2,77E-02
3,72E-02	3,01E-03

figure 3. Thyristor

Gate trigger characteristics

$$V_G = f(I_G)$$





Vincotech


Ordering Code & Marking									
Version				Ordering Code					
without thermal paste 17 mm housing with solder pins				V23990-P640-H10-PM					
VIN WWYY NNNNNNVV UL LLLL SSSS			Text	VIN	Date code	Name&Ver	UL	Lot	Serial
				VIN	WWYY	NNNNNNVV	UL	LLLL	SSSS
			Datamatrix	Type&Ver	Lot number	Serial	Date code		
			TTTTTIV	LLLL	SSSS	WWYY			

Pin table			
Pin	X	Y	Function
1			Not assembled
2			Not assembled
3	26,4	0	DC-
4	23,9	0	DC-
5	21,4	0	DC-
6	18,9	0	DC-
7	11,9	0	G5
8	7,5	0	G3
9	4,7	0	G1
10	0	0	DC+
11	0	2,5	DC+
12	0	5	DC+
13	0	7,5	DC+
14	0	22,5	L1
15	2,5	22,5	L1
16	5	22,5	L1
17	12	22,5	L2
18	14,5	22,5	L2
19	17	22,5	L2
20	24	22,5	L3
21	26,5	22,5	L3
22	29	22,5	L3
23			Not assembled
24			Not assembled
25			Not assembled

Tolerance of pinpositions: ±0.5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
D2, D4, D6	Rectifier	1600 V	80 A	Rectifier Diode	
D1, D3, D5	Thyristor	1600 V	75 A	Rectifier Thyristor	




Vincotech

Packaging instruction			
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
V23990-P640-H10-D1-14	12 Jul. 2018		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.