





flowPIM 0		1200 V / 8 A	
Features		flow 0 12 mm housing	
<ul style="list-style-type: none">• 2 Clips housing in 12 mm height• Trench Fieldstop Technology IGBT4• Integrated BRC			
Target applications		Schematic	
<ul style="list-style-type: none">• Industrial Drives			
Types			
<ul style="list-style-type: none">• V23990-P849-A49Y-PM			



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	16	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	24	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	61	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	19	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	20	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	46	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Brake Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	9	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	12	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	37	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Brake Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	9	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	6	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	25	W
Maximum junction temperature	T_{jmax}		150	°C

Rectifier Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	35	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	200	A
Surge current capability	I^2t		200	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	44	W
Maximum junction temperature	T_{jmax}		150	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance			>12,7	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$				0,00015	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15			8	25 125	1,58	1,87	2,07 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200			25			1	μA
Gate-emitter leakage current	I_{GES}		20	0			25			120	nA
Internal gate resistance	r_g								None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25			25		490		pF
Reverse transfer capacitance	C_{res}								30		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	15			8	25		53		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)							1,57		K/W
--	---------------	---	--	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 32 \Omega$ $R_{goff} = 32 \Omega$	±15	600	8	25		71,4		ns
Rise time	t_r					125		70,6		ns
Turn-off delay time	$t_{d(off)}$					25		18,6		ns
Fall time	t_f					125		22,8		ns
Turn-on energy (per pulse)	E_{on}					25		194,4		mWs
Turn-off energy (per pulse)	E_{off}					125		236,4		mWs
						25		78,46		mWs
		125		108,16		mWs				
		25		0,499		mWs				
		125		0,748		mWs				
		25		0,435		mWs				
		125		0,624		mWs				



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Inverter Diode

Static

Forward voltage	V_F				10	25 150	1,35	1,85 1,77	2,05 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			2,7	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						2,07		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=452$ A/μs $di/dt=399$ A/μs	±15	600	8	25		8,46		A
						125		9,88		
Reverse recovery time	t_{rr}					25		250,51		ns
						125		382,73		
Recovered charge	Q_r					25		0,885		μC
						125		1,57		
Reverse recovered energy	E_{rec}	25		0,345		mWs				
		125		0,634						
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$	25		83,99		A/μs				
		125		69,05						



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Brake Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,00015	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		4	25 125	1,58	1,95 2,17	2,02 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			0,5	µA
Gate-emitter leakage current	I_{GES}		20	0		25			120	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		250		pF
Reverse transfer capacitance	C_{res}							15		pF

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						2,58		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 64 \Omega$ $R_{goff} = 64 \Omega$	±15	600	4	25		93		ns			
						125		89,8					
						150		90,6					
Rise time	t_r									25		18,8	ns
										125		24	
										150		24,2	
Turn-off delay time	$t_{d(off)}$									25		184,4	ns
						125		226					
						150		235					
Fall time	t_f					25		71,34	ns				
						125		98,45					
						150		101,98					
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 0,442 \mu\text{C}$ $Q_{tFWD} = 0,76 \mu\text{C}$ $Q_{tFWD} = 0,871 \mu\text{C}$				25		0,253	mWs				
						125		0,339					
						150		0,366					
Turn-off energy (per pulse)	E_{off}					25		0,221	mWs				
						125		0,303					
						150		0,324					



Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Brake Diode

Static

Forward voltage	V_F				3	25 125	1,23	1,73 1,64	1,97 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			27	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						2,8		K/W
--	---------------	---------------------------------------	--	--	--	--	--	-----	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=204$ A/μs $di/dt=202$ A/μs $di/dt=191$ A/μs	±15	600	4	25		4,22		A
Reverse recovery time	t_{rr}					125		4,65	ns	
						150		4,74		
						25		268,29		
Recovered charge	Q_r					125		0,76	μC	
						150		0,871		
		25		0,176						
Reverse recovered energy	E_{rec}	125		0,324	mWs					
		150		0,378						
		25		44,17						
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$	125		39,91	A/μs					
		150		36,33						
		25								



Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Rectifier Diode

Static

Forward voltage	V_F			8	25 125 150		0,976 0,879 0,85	1,21 ⁽¹⁾ 1,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1600$ V			25			50	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)					1,59		K/W
--	---------------	---------------------------------------	--	--	--	--	------	--	-----

Thermistor

Static

Rated resistance	R				25		22		kΩ
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1484$ Ω			100	-5		5	%
Power dissipation	P						5		mW
Power dissipation constant	d				25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. ±1 %					3962		K
B-value	$B_{(25/100)}$	Tol. ±1 %					4000		K
Vincotech Thermistor Reference								I	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.




Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ — 25 °C
— 125 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 125 \text{ °C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j:$ — 25 °C
— 125 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,566 \text{ K/W}$

IGBT thermal model values

R (K/W)	τ (s)
1,42E-01	5,98E-01
6,32E-01	7,71E-02
3,98E-01	2,43E-02
2,86E-01	6,16E-03
1,08E-01	1,44E-03




Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



D = single pulse
T_s = 80 °C
V_{GE} = 15 V
T_j = T_{jmax}



Inverter Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 2,066\text{ K/W}$

FWD thermal model values

R (K/W)	τ (s)
5,09E-02	4,26E+00
1,55E-01	5,03E-01
7,75E-01	7,89E-02
5,33E-01	2,68E-02
3,54E-01	5,03E-03
1,97E-01	9,09E-04




Brake Switch Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25 \text{ } ^\circ C$ (blue), $125 \text{ } ^\circ C$ (red)

figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 125 \text{ } ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25 \text{ } ^\circ C$ (blue), $125 \text{ } ^\circ C$ (red)

figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 2,577 K/W$

IGBT thermal model values

R (K/W)	τ (s)
8,49E-02	6,59E+00
1,97E-01	3,69E-01
1,01E+00	6,94E-02
4,64E-01	1,61E-02
4,43E-01	4,16E-03
3,82E-01	6,88E-04




Brake Switch Characteristics

figure 12. IGBT

Safe operating area

$I_C = f(V_{CE})$



$D =$ single pulse
 $T_s = 80$ °C
 $V_{CE} = 15$ V
 $T_j = T_{jmax}$




Brake Diode Characteristics

figure 13. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$
 $T_j: \text{ — } 25 \text{ }^\circ\text{C}$
 $\text{ — } 125 \text{ }^\circ\text{C}$

figure 14. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 2,796 \text{ K/W}$
 FWD thermal model values

$R \text{ (K/W)}$	$\tau \text{ (s)}$
7,82E-02	2,45E+00
1,95E-01	2,65E-01
9,84E-01	4,77E-02
6,58E-01	1,23E-02
5,09E-01	2,70E-03
3,71E-01	5,98E-04



Rectifier Diode Characteristics

figure 15. Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 16. Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = \frac{t_p}{T}$
 $R_{th(j-s)} = 1,594 \text{ K/W}$

Rectifier thermal model values

R (K/W)	τ (s)
3,44E-02	9,66E+00
1,12E-01	1,22E+00
5,81E-01	1,45E-01
4,89E-01	5,05E-02
2,38E-01	9,26E-03
1,22E-01	1,79E-03
1,81E-02	7,88E-04




Thermistor Characteristics

figure 17. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






Inverter Switching Characteristics

figure 18. IGBT


Typical switching energy losses as a function of collector current
 $E = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 32 \ \Omega$
 $R_{goff} = 32 \ \Omega$
 T_j : — 25 °C
— 125 °C

figure 19. IGBT


Typical switching energy losses as a function of gate resistor
 $E = f(R_g)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 8 \text{ A}$
 T_j : — 25 °C
— 125 °C

figure 20. FWD


Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 32 \ \Omega$
 T_j : — 25 °C
— 125 °C

figure 21. FWD

Typical reverse recovered energy loss as a function of gate resistor
 $E_{rec} = f(R_g)$




With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 8 \text{ A}$
 T_j : — 25 °C
— 125 °C



Inverter Switching Characteristics

figure 22. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 32 \text{ } \Omega$
 $R_{goff} = 32 \text{ } \Omega$

figure 23. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 8 \text{ A}$

figure 24. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 32 \text{ } \Omega$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$

figure 25. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 8 \text{ A}$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$




Inverter Switching Characteristics

figure 26. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 32$ Ω

T_j : — 25 °C
— 125 °C

figure 27. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 8$ A

T_j : — 25 °C
— 125 °C

figure 28. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 32$ Ω

T_j : — 25 °C
— 125 °C

figure 29. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 8$ A


T_j : — 25 °C
— 125 °C



Inverter Switching Characteristics

figure 30. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 32 \text{ } \Omega$

T_j : — 25 °C
 — 125 °C

figure 31. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 8 \text{ A}$

T_j : — 25 °C
 — 125 °C

figure 32. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 125 \text{ } ^\circ\text{C}$
 $R_{goff} = 32 \text{ } \Omega$
 $R_{goff} = 32 \text{ } \Omega$




Brake Switching Characteristics

figure 33. IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	— 25 °C
$V_{GE} =$	±15	V		— 125 °C
$R_{gon} =$	64	Ω		— 150 °C
$R_{goff} =$	64	Ω		

figure 34. IGBT

Typical switching energy losses as a function of gate resistor

$$E = f(R_g)$$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	— 25 °C
$V_{GE} =$	±15	V		— 125 °C
$I_c =$	4	A		— 150 °C

figure 35. FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$




With an inductive load at

$V_{CE} =$	600	V	$T_j:$	— 25 °C
$V_{GE} =$	±15	V		— 125 °C
$R_{gon} =$	64	Ω		— 150 °C

figure 36. FWD

Typical reverse recovered energy loss as a function of gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at


$V_{CE} =$	600	V	$T_j:$	— 25 °C
$V_{GE} =$	±15	V		— 125 °C
$I_c =$	4	A		— 150 °C



Brake Switching Characteristics

figure 37. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 64 \text{ } \Omega$
 $R_{goff} = 64 \text{ } \Omega$

figure 38. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 150 \text{ }^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 4 \text{ A}$

figure 39. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 64 \text{ } \Omega$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C

figure 40. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{goff})$



With an inductive load at
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 4 \text{ A}$
 $T_j:$ — 25 °C
 — 125 °C
 — 150 °C




Brake Switching Characteristics

figure 41. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 64$ Ω

T_j : — 25 °C
— 125 °C
— 150 °C

figure 42. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 4$ A

T_j : — 25 °C
— 125 °C
— 150 °C

figure 43. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 64$ Ω

T_j : — 25 °C
— 125 °C
— 150 °C

figure 44. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 4$ A


T_j : — 25 °C
— 125 °C
— 150 °C



Brake Switching Characteristics

figure 45. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$R_{goff} = 64$ Ω	$T_j = 150$ °C

figure 46. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_r/dt = f(R_{goff})$




With an inductive load at

$V_{CE} = 600$ V	$T_j = 25$ °C
$V_{GE} = \pm 15$ V	$T_j = 125$ °C
$I_c = 4$ A	$T_j = 150$ °C

figure 47. IGBT

Reverse bias safe operating area
 $I_c = f(V_{CE})$



At $T_j = 150$ °C
 $R_{goff} = 64$ Ω
 $R_{goff} = 64$ Ω



Switching Definitions

figure 48. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 49. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 50. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 51. IGBT

Turn-on Switching Waveforms & definition of t_r





Switching Definitions

figure 52. FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 53. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Ordering Code	
Version	Ordering Code
Without thermal paste	V23990-P849-A49Y-PM
With thermal paste (5,2 W/mK, PTM6000HV)	V23990-P849-A49Y-/7/-PM
With thermal paste (3,4 W/mK, PSX-P7)	V23990-P849-A49Y-/3/-PM

Marking							
	Text	VIN VIN	Date code WWYY	Type&Ver TTTTITVV	UL UL	Lot LLLLL	Serial SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code		
		TTTTITVV	LLLLL	SSSS	WWYY		


Pin table [mm]			
Pin	X	Y	Function
1	25,5	2,7	NTC1
2	25,5	0	NTC2
3	22,8	0	-DC
4	20,1	0	BRCG
5	16,2	0	BRCE
6	13,5	0	G6
7	10,8	0	E6
8	8,1	0	G5
9	5,4	0	E5
10	2,7	0	G4
11	0	0	E4
12	0	19,8	G1
13	0	22,5	U
14	7,5	19,8	G2
15	7,5	22,5	V
16	15	19,8	G3
17	15	22,5	W
18	22,8	22,5	+INV
19	25,5	22,5	+DC
20	33,5	22,5	BRC+
21	33,5	15	L1
22	33,5	7,5	L2
23	33,5	0	L3

Outline

Tolerance of pinpositions: ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T4, T1, T5, T2, T6, T3	IGBT	1200 V	8 A	Inverter Switch	
D1, D4, D2, D5, D3, D6	FWD	1200 V	10 A	Inverter Diode	
T7	IGBT	1200 V	4 A	Brake Switch	
D7	FWD	1200 V	3 A	Brake Diode	
D8, D9, D10, D11, D12, D13	Rectifier	1600 V	25 A	Rectifier Diode	
NTC	Thermistor			Thermistor	



Vincotech

Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow 0</i> packages see vincotech.com website.				
Package data				
Package data for <i>flow 0</i> packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
UL recognition and file number				
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
V23990-P849-A49Y-PM-D9-14	30 Sep. 2021	New Datasheet format, module is unchanged Correct Static values of Inverter Diode, Brake Diode, Rectifier Diode Correct Thermal values of Brake Switch, Brake Diode Separate datasheet	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.